

Dip Switches

Product Overview

- Using excellent heat and chemical resistance engineering plastic.
- Using standard gold-plated contact points ensure reliability and longer life of the switch.
- Have the advantage of self-cleaning when the switch in ON-OFF state.
- Using widely in manual programproducts, like data processing, communications, remote controls and burglar alarmsystem.

Soldering Information

- Soldering iron under 30Wand under 350℃ for 3 seconds max or 270℃ for 5 seconds max.
- Wave crest soldering: 240℃ within 20seconds max, .Keep all actuators in "off" position during soldering and cleaning process.

Specifications









- Contact capacity
 - OFF: 25mA,24VDC
 - ON: 100mA,50VDC
- Contact resistance
 - Initial: 50mΩ 24VDC /100mA
 - After life test: 100mΩ typical, 24VDC /100mA
- Insulation resistance: ≥100MΩ ,500VDC
- Dielectr ic strength: 500VDC RMS min.
- Operating force: DS/DA:1000g Max
- DP: 400g Max
- Operation Life expectancy
 - Mechanical: 3000 operations
 - Electrical: 2000 operations
- Temperature range operating/storage: -25℃-70℃

Implication of Type

DS DA DP	★	-	◇	◆	-	△	▲
Code of series: DS slide type DA right-angle type DP piano type	Key type: R hiding type No letter means extended type.	Number of switch pairs: 01:1 position 07:7 osition 02:2 position 08:8 osition 03:3 position 09:9 osition 04:4 position 10:10 osition 05:5 position 12:12 osition 06:6 position	Terminal length: L:long(5mm) S:short(3mm) No letter means standard(3.6mm)	Shell color: R Red(default) B blue N black	Sealing type: T: top tape sealed (just for recessed type actuator type)		

Note: DP series only has positions of 2,4,6,8 ;the length of DA terminal only has one standard rating(3mm).

Product Cutline

	Slide Type	Right-angle Type	Piano Type
Extended Type	DS-◇◆-△▲ 	DA-◇S-△▲ 	DP-◇◆-△▲ 
Hiding Type	DSR-◇◆-△▲ 	DAR-◇S-△▲ 	DPR-◇◆-△▲ 
Shape % Dimensions	DS: 	DA: 	DP: 