

The pythontex package

Geoffrey M. Poore

gpoore@gmail.com

github.com/gpoore/pythontex

Version 0.12? from 2013/08/26

Abstract

Python_{TEX} provides access to Python from within L^AT_EX documents. It allows Python code entered within a L^AT_EX document to be executed, and the results to be included within the original document. Python code may be adjacent to the figure or calculation it produces. The package also makes possible macro definitions that mix Python and L^AT_EX code. In addition, Python_{TEX} provides syntax highlighting for many programming languages via the Pygments syntax highlighter.

Python_{TEX} is fast and user-friendly. Python code is only executed when it has been modified, or when user-specified criteria are met. When code is executed, user-defined sessions automatically run in parallel. If Python code produces errors, the error message line numbers are synchronized with the L^AT_EX document line numbering, simplifying debugging. Dependencies may be specified so that code is automatically re-executed whenever they are modified.

Because documents that use Python_{TEX} mix L^AT_EX and Python code, they are less suitable than plain L^AT_EX documents for journal submission, sharing, and conversion to other formats. Python_{TEX} includes a `depythontex` utility that creates a copy of a document in which all Python_{TEX} content is replaced by its output.

While Python is the focus of Python_{TEX}, adding basic support for an additional language is usually as simple as creating a new class instance and a few templates, usually totaling less than 100 lines of code. The following languages are already have built-in support: Ruby.

Warning

Python_{TEX} makes possible some pretty amazing things. But that power brings with it a certain risk and responsibility. Compiling a document that uses Python_{TEX} involves executing Python code, and potentially other programs, on your computer. You should only compile Python_{TEX} documents from sources you trust. Python_{TEX} comes with NO WARRANTY.¹ The copyright holder and any additional authors will not be liable for any damages.

¹All L^AT_EX code is licensed under the [L^AT_EX Project Public License \(LPPL\)](#) and all Python code is licensed under the [BSD 3-Clause License](#).

Contents

1	Introduction	5
2	Installing and running	8
2.1	Installing Python _{TEX}	8
2.2	Compiling documents using Python _{TEX}	11
3	Usage	13
3.1	Package options	13
3.2	Commands and environments	19
3.2.1	Inline commands	19
3.2.2	Environments	21
3.2.3	Console command and environment families	21
3.2.4	Default families	22
3.2.5	Custom code	23
3.2.6	Python _{TEX} utilities class	25
3.2.7	Formatting of typeset code	28
3.2.8	Access to printed content (stdout) and error messages (stderr)	29
3.3	Pygments commands and environments	30
3.4	General code typesetting	31
3.4.1	Listings float	31
3.4.2	Background colors	31
3.4.3	Referencing code by line number	32
3.4.4	Beamer compatibility	33
3.5	Advanced Python _{TEX} usage	33
4	depythontex	35
4.1	Preparing a document that will be converted	35
4.2	Removing Python _{TEX} dependence	36
4.3	Technical details	38
5	L_{TEX} programming with Python_{TEX}	41
5.1	Macro programming with Python _{TEX}	41
5.2	Package writing with Python _{TEX}	42
6	Support for additional languages	42
6.1	Ruby	42
6.2	Julia	43
6.3	Adding support for a new language	43
6.3.1	Template	44
6.3.2	Wrapper	46
6.3.3	The CodeEngine class	46
6.3.4	Creating the L _{TEX} interface	48
7	Troubleshooting	48

8	The future of PythonTeX	49
8.1	To Do	49
8.1.1	Modifications to make	49
8.1.2	Modifications to consider	49
	Version History	50
9	Implementation	59
9.1	Package opening	59
9.2	Required packages	59
9.3	Package options	60
9.3.1	Enabling command and environment families	60
9.3.2	Gobble	60
9.3.3	Beta	60
9.3.4	Runall	60
9.3.5	Rerun	61
9.3.6	Hashdependencies	61
9.3.7	Autoprint	61
9.3.8	Debug	62
9.3.9	makestderr	62
9.3.10	stderrfilename	63
9.3.11	Python's <code>__future__</code> module	63
9.3.12	Upquote	63
9.3.13	Fix math spacing	64
9.3.14	Keep temporary files	64
9.3.15	Pygments	64
9.3.16	Python console environment	66
9.3.17	depythontex	67
9.3.18	Process options	67
9.4	Utility macros and input/output setup	68
9.4.1	Automatic counter creation	68
9.4.2	Saving verbatim content in macros	68
9.4.3	Code context	69
9.4.4	Code groups	70
9.4.5	File input and output	71
9.4.6	Interface to <code>fancyvrb</code>	76
9.4.7	Access to printed content (stdout)	78
9.4.8	Access to stderr	81
9.4.9	depythontex	82
9.5	Inline commands	86
9.5.1	Inline core macros	86
9.5.2	Inline command constructors	91
9.6	Environments	95
9.6.1	Block and verbatim environment constructors	95
9.6.2	Code environment constructor	101
9.6.3	Console environment constructor	104

9.7	Constructors for command and environment families	106
9.8	Default commands and environment families	109
9.9	Listings environment	109
9.10	Pygments for general code typesetting	110
9.11	Pygments utilities macros	111
	9.11.1 Inline Pygments command	111
	9.11.2 Pygments environment	112
	9.11.3 Special Pygments commands	114
	9.11.4 Creating the Pygments commands and environment	116
9.12	Final cleanup	118
9.13	Compatibility with beta releases	118

1 Introduction

This introduction provides background and objectives for the PythonTeX package. To jump right in and get started, you may wish to consult the `pythontex_quickstart` and `pythontex_gallery` documents, as well as Sections 2 and 3, below. If you are primarily interested in using PythonTeX with a language other than Python, see Section 6.

L^AT_EX can do a lot,² but the programming required can sometimes be painful.³ In spite of the many packages available for L^AT_EX, the libraries and packages of a general-purpose programming language are lacking. Furthermore, it can be convenient to include non-L^AT_EX code in a document to make it more reproducible. For these reasons, there have been multiple systems that allow other languages to be used within L^AT_EX documents.⁴

- `PerlTeX` allows the bodies of L^AT_EX macros to be written in Perl.
- `SageTeX` allows code for the Sage mathematics software to be executed from within a L^AT_EX document.
- Martin R. Ehmsen’s `python.sty` provides a very basic method of executing Python code from within a L^AT_EX document.
- `SympyTeX` allows more sophisticated Python execution, and is largely based on a subset of SageTeX.
- `LuaTeX` extends the pdfTeX engine to provide Lua as an embedded scripting language, and as a result yields tight, low-level Lua integration.

PythonTeX attempts to fill a perceived gap in the current integrations of L^AT_EX with an additional language. It has a number of objectives, only some of which have been met by previous packages.

Execution speed

In the approaches mentioned above, all the non-L^AT_EX code is executed at every compilation of the L^AT_EX document (`PerlTeX`, `LuaTeX`, and `python.sty`), or all the non-L^AT_EX code is executed every time it is modified (`SageTeX` and `SympyTeX`). However, many tasks such as plotting and data analysis take a significant time to execute. We need a way to fine-tune code execution, so that independent blocks of slow code may be separated into their own sessions and are only executed when modified. If we are going to split code into multiple sessions, we might as well run these sessions in parallel, further increasing speed. A byproduct of this approach is that it now becomes much more feasible to include slower code, since we can still have fast compilations whenever the slow code isn’t modified.

²TeX is a Turing-complete language.

³As I learned in creating this package.

⁴I am not including the various web and weave dialects in my discussion, since they typically involve a web or weave document from which the .tex source is generated, and thus weaker integration with L^AT_EX. Two sophisticated examples of this approach are `Sweave` and `knitr`, both of which combine L^AT_EX with the R language for tasks such as dynamic report generation.

Compiling without executing

Even with all of these features to boost execution speed, there will be times when we have to run slow code. Thus, we need the execution of non- \LaTeX code to be separated from compiling the \LaTeX document. We need to be able to edit and compile a document containing unexecuted code. Unexecuted code should be invisible or be replaced by placeholders. Sage \TeX and Sympy \TeX have implemented such a separation of compiling and executing. In contrast, Lua \TeX and Perl \TeX execute all the code at each compilation—but that is appropriate given their goal of simplifying macro programming.

Error messages

Whenever code is saved from a \LaTeX document to an external file and then executed, the line numbers for any error messages will not correspond to the line numbering of the original \LaTeX document. At one extreme, `python.sty` doesn't attempt to deal with this issue, while at the other extreme, Sage \TeX uses an ingenious system of `Try/Except` statements on every chunk of code. We need a system that translates all error messages so that they correspond to the line numbering of the original \LaTeX document, with minimal overhead when there are no errors.

Syntax highlighting

Once we begin using non- \LaTeX code, sooner or later we will want to typeset some of it, which means we need syntax highlighting. A number of syntax highlighting packages currently exist for \LaTeX ; perhaps the most popular are `listings` and `minted`. `listings` uses pure \LaTeX . It has not been updated since 2007, which makes it a less ideal solution in some circumstances. `minted` uses the Python-based syntax highlighter Pygments to perform highlighting. Pygments can provide superior syntax highlighting, but `minted` can be very slow because all code must be highlighted at each compilation and each instance of highlighting involves launching an external Python process. We need high-speed, user-friendly syntax highlighting via Pygments.⁵

Printing

It would be nice for the `print` statement/function,⁶ or its equivalent, to automatically return its output within the \LaTeX document. For example, using `python.sty` it is possible to generate some text while in Python, open a file, save the text to it, close the file, and then `\input` the file after returning to \LaTeX . But it is much simpler to generate the text and `print` it, since the printed content is automatically included in the \LaTeX document. This was one of the things that `python.sty` really got right.

Pure code

\LaTeX has a number of special characters (`# $ % & ~ _ ^ \ { }`), which

⁵The author recently started maintaining the `minted` package. In the near future, `minted` will inherit Python \TeX 's speed enhancements, and the two packages will become more compatible.

⁶In Python, `print` was a statement until Python 3, when it became a function. The function form is available via `import from __future__` in Python 2.6 and later.

complicates the entry of non- \LaTeX code since these same characters are common in many languages. Sage \TeX and Sympy \TeX delimit all inline code with curly braces ($\{\}$), but this approach fails in the (somewhat unlikely) event that code needs to contain an unmatched brace. More seriously, they do not allow the percent symbol $\%$ (modular arithmetic and string formatting in Sage and Python) to be used within inline code. Rather, a $\backslash\text{percent}$ macro must be used instead. This means that code must (sometimes) be entered as a hybrid between \LaTeX and the non- \LaTeX language. Lua \TeX is somewhat similar: “The main thing about Lua code in a TeX document is this: the code is expanded by TeX before Lua gets to it. This means that all the Lua code, even the comments, must be valid TeX!”⁷ In the case of Lua \TeX , though, there is the `luacode` package that allows for pure Lua.

This language hybridization is not terribly difficult to work around in the Sage \TeX and Sympy \TeX cases, and is actually a Lua \TeX feature in many contexts. But if we are going to create a system for general-purpose access to a non- \LaTeX language, we need **all** valid code to work correctly in **all** contexts, with no hybridization of any sort required. We should be able to copy and paste valid code into a \LaTeX document, without having to worry about hybridizing it. Among other things, this means that inline code delimiters other than \LaTeX 's default curly braces $\{\}$ must be available.

Hybrid code

Although we need a system that allows input of pure non- \LaTeX code, it would also be convenient to allow hybrid code, or code in which \LaTeX macros may be present and are expanded before the code is executed. This allows \LaTeX data to be easily passed to the non- \LaTeX language, facilitating a tighter integration of the two languages and the use of the non- \LaTeX language in macro definitions.

Math and science libraries

The author decided to create Python \TeX after writing a physics dissertation using \LaTeX and realizing how frustrating it can be to switch back and forth between a \TeX editor and plotting software when fine-tuning figures. We need access to a non- \LaTeX language like Python, MATLAB, or Mathematica that provides strong support for data analysis and visualization. To maintain broad appeal, this language should primarily involve open-source tools, should have strong cross-platform support, and should also be suitable for general-purpose programming.

Language-independent implementation

It would be nice to have a system for executing non- \LaTeX code that depends very little on the language of the code. We should not expect to escape all language dependence. But if the system is designed to be as general as possible, then it may be expanded in the future to support additional languages.

⁷http://wiki.contextgarden.net/Programming_in_LuaTeX

Python was chosen as the language to fulfill these objectives for several reasons.

- It is open-source and has good cross-platform support.
- It has a strong set of scientific, numeric, and visualization packages, including [NumPy](#), [SciPy](#), [matplotlib](#), and [SymPy](#). Much of the initial motivation for Python_{TeX} was the ability to create publication-quality plots and perform complex mathematical calculations without having to leave the _{TeX} editor.
- We need a language that is suitable for scripting. Lua is already available via Lua_{TeX}, and in any case lacks the math and science tools.⁸ Perl is already available via Perl_{TeX}, although Perl_{TeX}'s emphasis on Perl for macro creation makes it rather unsuitable for scientific work using the [Perl Data Language \(PDL\)](#) or for more general programming. Python is one logical choice for scripting.

Now at this point there will almost certainly be some reader, sooner or later, who wants to object, “But what about language *X*!” Well, yes, in some respects the choice to use Python did come down to personal preference. But you should give Python a try, if you haven’t already. You may also wish to consider the many interfaces that are available between Python and other languages. If you still aren’t satisfied, keep in mind Python_{TeX}'s “language-independent” implementation! In many cases, adding support for additional languages is relatively simple (see Section 6).

2 Installing and running

2.1 Installing Python_{TeX}

Python_{TeX} requires a _{TeX} installation. It has been tested with [_{TeX} Live](#) and [MiK_{TeX}](#), but should work with other distributions. The following L^A_{TeX} packages, with their dependencies, are required: `fancyvrb`, `etex`, `etoolbox`, `xstring`, `pgfopts`, `newfloat`, `currfile`, and `color` or `xcolor`. A current _{TeX} installation is recommended, since some features require recent versions of the packages. If you are creating and including graphics, you will also need `graphicx`. The `mdframed` package is recommended for enclosing typeset code in boxes with fancy borders and/or background colors; `tcolorbox` and `framed` are alternatives.

Python_{TeX} also requires a [Python](#) installation. Python 2.7 is recommended for the greatest compatibility with scientific tools, although many scientific packages are now compatible with Python 3. Python_{TeX} is compatible with Python 2.7 and 3.2+. The Python package [Pygments](#) must be installed for syntax highlighting to function. Python_{TeX} has been tested with Pygments 1.4 and later, but the latest version is recommended. For scientific work, or to compile `pythontex_gallery.tex`, the following are also recommended: [NumPy](#), [SciPy](#), [matplotlib](#), and [SymPy](#).

⁸One could use [Lunatic Python](#), and some numeric packages for Lua are [in development](#).

Python \TeX also provides support for other languages such as Ruby, so you will need to install any additional languages you plan to use. Typically, the most recent major version of these languages is supported.

Python \TeX consists of the following files:

- Installer file `pythontex.ins`
- Documented \LaTeX source file `pythontex.dtx`, from which `pythontex.pdf` and `pythontex.sty` are generated
- Main script `pythontex.py`, which imports from `pythontex2.py` or `pythontex3.py`, based on the Python version
- Language definitions `pythontex_engines.py`
- Utilities class `pythontex_utils.py`
- `depythontex.py`, which imports from `depythontex2.py` or `depythontex3.py`, based on the Python version; used to remove Python \TeX dependence
- README (in rst style)
- `pythontex_gallery.tex` and `pythontex_gallery.pdf`
- `pythontex_quickstart.tex` and `pythontex_quickstart.pdf`
- Optional installation script `pythontex_install_texlive.py` for \TeX Live
- Optional batch file `pythontex.bat` for use in launching `pythontex.py` under Windows
- Optional conversion script `pythontex_2to3.py` for converting Python \TeX code written for Python 2 into a form compatible with Python 3

The style file `pythontex.sty` may be generated by running \LaTeX on `pythontex.ins`. The documentation you are reading may be generated by running \LaTeX on `pythontex.dtx`. Some code is provided in two forms, one for Python 2 and one for Python 3 (names ending in 2 and 3). Whenever this is the case, a version-independent wrapper is supplied that automatically runs the correct code based on the Python version. For example, there are two main scripts, `pythontex2.py` and `pythontex3.py`, but you should actually run `pythontex.py`, which imports the correct code based on the Python version.⁹

If you want the absolute latest version of Python \TeX , you should install it manually from github.com/gpoore/pythontex. A Python installation script is provided for use with \TeX Live. It has been tested with Windows, Linux, and OS X, but may need manual input or slight modifications depending on your system. The

⁹Unfortunately, it is not possible to provide full Unicode support for both Python 2 and 3 using a single script. Currently, all code is written for Python 2, and then the Python 3 version is automatically generated via the `pythontex_2to3.py` script. This script comments out code that is only for Python 2, and un-comments code that is only for Python 3.

installation script performs the steps described below. **Note that for a typical $\text{T}_{\text{E}}\text{X}$ setup under Linux, you may need to run the script with elevated privileges, and may need to run it with the user's `PATH`.** This can be necessary when you are using a Linux distribution that includes an outdated version of $\text{T}_{\text{E}}\text{X}$ Live, and have installed a new version manually. **If you are installing Python $\text{T}_{\text{E}}\text{X}$ on a machine with multiple version of $\text{T}_{\text{E}}\text{X}$, make sure you install Python $\text{T}_{\text{E}}\text{X}$ for the correct version.** For example, under Ubuntu Linux, you will probably need the following command if you have installed the latest version of $\text{T}_{\text{E}}\text{X}$ Live manually:

```
sudo env PATH=$PATH python pythontex_install_texlive.py
```

The installer creates the following files. It will offer to create the paths if they do not exist. If you are installing in `TEXMFLOCAL`, the paths will have an additional `local/` at the end.

- $\langle \text{T}_{\text{E}}\text{X tree root} \rangle / \text{doc/latex/pythontex/}$
 - `pythontex.pdf`
 - `README`
 - `pythontex_quickstart.tex`
 - `pythontex_quickstart.pdf`
 - `pythontex_gallery.tex`
 - `pythontex_gallery.pdf`
- $\langle \text{T}_{\text{E}}\text{X tree root} \rangle / \text{scripts/pythontex/}$
 - `pythontex.py`, `pythontex2.py` and `pythontex3.py`
 - `pythontex_engines.py`
 - `pythontex_utils.py`
 - `depythontex.py`, `depythontex2.py` and `depythontex3.py`
- $\langle \text{T}_{\text{E}}\text{X tree root} \rangle / \text{source/latex/pythontex/}$
 - `pythontex.dtx`
 - `pythontex.ins`
- $\langle \text{T}_{\text{E}}\text{X tree root} \rangle / \text{tex/latex/pythontex/}$
 - `pythontex.sty`

After the files are installed, the system must be made aware of their existence. The installer runs `mktexlsr` to do this. In order for `pythontex.py` and `depythontex.py` to be executable, a symlink ($\text{T}_{\text{E}}\text{X}$ Live under Linux), launching wrapper ($\text{T}_{\text{E}}\text{X}$ Live under Windows), or batch file (general Windows) should be created in the `bin/⟨system⟩` directory. The installer attempts to create a

symlink or launching wrapper automatically. For \TeX Live under Windows, it copies `bin/win32/runscript.exe` to `bin/win32/pythontex.exe` to create the wrapper.¹⁰

2.2 Compiling documents using Python \TeX

Compiling a document with Python \TeX involves three steps: running a \LaTeX -compatible \TeX engine (binary executable), running `pythontex.py` (preferably via a symlink, wrapper, or batch file, as described above), and finally running the \TeX engine again. The first \TeX run saves code into an external file where Python \TeX can access it. The second \TeX run pulls the Python \TeX output back into the document.

If you plan to use code that contains non-ASCII characters such as Unicode, you should make sure that your document is properly configured:

- Under pdfLaTeX, your documents need `\usepackage[T1]{fontenc}` and `\usepackage[utf8]{inputenc}`, or a similar configuration.
- Under LuaLaTeX, your documents need `\usepackage{fontspec}`, or a similar configuration.
- Under XeLaTeX, your documents need `\usepackage{fontspec}` as well as `\defaultfontfeatures{Ligatures=TeX}`, or a similar configuration.

For an example of a Python \TeX document that will correctly compile under all three engines, see the `pythontex_gallery.tex` source.

If you use XeLaTeX, and your non- \LaTeX code contains tabs, you **must** invoke XeLaTeX with the `-8bit` option so that tabs will be written to file as actual tab characters rather than as the character sequence `^^I`.¹¹

`pythontex.py` requires a single command-line argument: the name of the `.tex` file to process. The filename can be passed with or without an extension; the script really only needs the `\jobname`, so any extension is stripped off.¹² The filename may include the path to the file; you do not have to be in the same directory as the file to run Python \TeX . If you are configuring your editor to run Python \TeX automatically via a shortcut, you may want to wrap the filename in double quotes `"` to allow for space characters.¹³ For example, under Windows with \TeX Live and Python 2.7 we would create the wrapper `pythontex.exe`. Then we could run Python \TeX on a file `\langle file name \rangle.tex` using the command `pythontex.exe "\langle file name \rangle"`.

`pythontex.py` accepts the following optional command-line arguments. Some of these options duplicate package-level options, so that settings may be configured either within the document or at the command line. In the event that the

¹⁰See the output of `runscript -h` under Windows for additional details.

¹¹See <http://tex.stackexchange.com/questions/58732/how-to-output-a-tabulation-into-a-file> for more on tabs with XeTeX.

¹²Thus, Python \TeX works happily with `.tex`, `.ltx`, `.dtx`, and any other extension.

¹³Using spaces in the names of `.tex` files is apparently frowned upon. But if you configure things to handle spaces whenever it doesn't take much extra work, then that's one less thing that can go wrong.

command-line and package options conflict, the package options always override the command-line options. For variations on these options that are acceptable, run `pythontex.py -h`.

- `--encoding=<encoding>` This sets the file encoding. Any encoding supported by Python’s `codecs` module may be used. The encoding should match that of the \LaTeX document. If an encoding is not specified, Python \TeX uses UTF-8. If support for characters beyond ASCII is required, then additional \LaTeX packages are required; see the discussion of \TeX engines above.
- `--error-exit-code={true,false}` By default, `pythontex.py` returns an exit code of 1 if there were any errors, and an exit code of 0 otherwise. This may be useful when Python \TeX is used in a scripting or command-line context, since the presence of errors may be easily detected. It is also useful with some \TeX editors. For example, `TeXworks` automatically hides the output of external programs unless there are errors.

In some contexts, returning a nonzero exit code can be redundant. For example, with the `WinShell` editor under Windows with TeX Live, the complete output of Python \TeX is always available in the “Output” view, so it is clear if errors have occurred. Having a nonzero exit code causes `runscript.exe` to return an additional, redundant error message in the “Output” view. In such situations, it may be desirable to disable the nonzero exit code.

- `--runall=[{true,false}]` This causes **all** code to be executed, regardless of modification or `rerun` settings. It is useful when code has not been modified, but a dependency such as a library or external data has changed. Note that the Python \TeX utilities class also provides a mechanism for automatically re-executing code that depends on external files when those external files are modified.

There is an equivalent `runall` package option. The command-line option `--rerun=always` is essentially equivalent.

- `--rerun={never,modified,errors,warnings,always}` This sets the threshold for re-executing code. By default, Python \TeX will rerun code that has been modified or that produced errors on the last run. Sometimes, we may wish to have a more lenient setting (only rerun if modified) or a more stringent setting (rerun even for warnings, or just rerun everything). **never** never executes code; a warning is issued if there is modified code. **modified** only executes code that has been modified (or that has modified dependencies). **errors** executes all modified code as well as all code that produced errors on the last run; this is the default. **warnings** executes all modified code, as well as all code that produced errors or warnings. **always** executes all code always and is essentially equivalent to `--runall`.

There is an equivalent `rerun` package option.

- `--hashdependencies=[{true,false}]` This determines whether dependencies (external files highlighted by Pygments, code dependencies specified via

`pytex.add_dependencies()`, etc.) are checked for changes via their hashes or modification times. By default, `mtime` is used, since it is faster. The package option `hashdependencies` is equivalent.

- `--verbose` This gives more verbose output, including a list of all processes that are launched.
- `--interpreter` This allows the interpreter for a given language to be specified. The argument should be in the form

```
--interpreter "<interpreter>:<command>, <interp>:<cmd>, ..."
```

where `<interpreter>` is `python`, `ruby`, etc., and `<command>` is the command for invoking the desired interpreter. The argument to `--interpreter` may also be in the form of a Python dictionary. The argument need not be enclosed in quotation marks if it contains no spaces.

For example, by default Python code is executed with whatever interpreter the `python` command invokes. But Python 3 could be specified using `--interpreter python:python3` (many Linux distributions) or `--interpreter "python:py -3"` (Windows, with Python 3.3 installed so that the `py` wrapper is available).

PythonTeX attempts to check for a wide range of errors and return meaningful error messages. But due to the interaction of L^AT_EX and Python code, some strange errors are possible. If you cannot make sense of errors when using PythonTeX, the simplest thing to try is deleting all files created by PythonTeX, then recompiling. By default, these files are stored in a directory called `pythontex-files-<jobname>`, in the same directory as your `.tex` document. See Section 7 for more details regarding troubleshooting.

3 Usage

3.1 Package options

Package options may be set in the standard manner when the package is loaded:

```
\usepackage[<options>]{pythontex}
```

All options are described as follows. The option is listed, followed by its possible values. When a value is not required, `<none>` is listed as a possible value. In this case, the value to which `<none>` defaults is also given. Each option lists its default setting, if the option is not invoked when the package is loaded.

Some options have a command-line equivalent. Package options override command-line options.

All options related to printed content are provided in two forms for convenience: one based on the word `print` and one based on `stdout`.

`usefamily=<basename>/{<basename1, basename2, ...>}`

By default, only the `py`, `sympy`, and `pylab` families of commands and environments are defined, to prevent possible package conflicts.¹⁴ This option defines preconfigured families for other available languages. It takes either a single language base name, or a list of comma-separated names enclosed in curly braces. Currently, the Ruby families `rb` and `ruby` may be created.

`gobble=none/auto`
`default:none`

This option is still under development and may change somewhat in future releases. If that occurs, equivalent functionality will be provided.

This option determines how code indentation is handled. By default, indentation is left as-is; leading whitespace is significant. `auto` will dedent all code by gobbling the largest common leading whitespace, using Python's `textwrap.dedent()`.¹⁵ Keep in mind that Python's `dedent` will not work correctly with mixed tabs and spaces.

The `gobble` option always works correctly with **executed** code. However, currently the option **only works with typeset code when Pygments is used**. The option is currently only available at the document level, but finer-grained control is planned in the future.

The `gobble` option is supported by `depythontex`.

`beta=<none>/true/false`
`default:false <none>=true`

This option provides compatibility with the beta releases from before the full v0.11 release, which introduced some changes in syntax and command names. This option should **only** be used with old PythonTeX documents that require it.

You are encouraged to update old documents, since this compatibility option will only be provided for a few releases.

`runall=<none>/true/false`
`default:false <none>=true`

This option causes all code to be executed, regardless of whether it has been modified. This option is primarily useful when code depends on external files, and needs to be re-executed when those external files are modified, even though the code itself may not have changed. Note that the PythonTeX utilities class also provides a mechanism for automatically re-executing code that depends on external files when those external files are modified.

A command-line equivalent `--runall` exists for `pythontex.py`. The package option `rerun=always` is essentially equivalent.

`rerun=never/modified/errors/warnings/always`
`default:errors`

¹⁴For example, a `\ruby` command for Ruby code, and the `\ruby` command defined by the Ruby package in the [CJK package](#).

¹⁵It would be possible to do the dedent on the L^AT_EX side, as is done manually in the `fancyvrb` and `listings` packages with the `gobble` option and is done automatically in the `lstautogobble` package. This is not done for stability and security reasons. `lstautogobble` determines the dedent by extracting the leading whitespace from the first line of code, and then applying this dedent to each subsequent line. This is adequate for **typesetting** code, since the worst-case scenario is that a subsequent line with less indentation will be typeset with the first few characters missing. Such an approach is not acceptable when the code will be **executed**, since a few missing characters could in principle cause serious damage. Doing the dedent on the Python side ensures that no characters are discarded, even if that results in an indentation error.

This option sets the threshold for re-executing code. By default, `PythonTeX` will rerun code that has been modified or that produced errors on the last run. Sometimes, we may wish to have a more lenient setting (only rerun if modified) or a more stringent setting (rerun even for warnings, or always rerun). `never` never executes code; a warning is issued if there is modified code. `modified` only executes code that has been modified. `errors` executes all modified code as well as all code that produced errors on the last run; this is the default. `warnings` executes all modified code, as well as all code that produced errors or warnings. `always` executes all code regardless of its condition.

A command-line equivalent `--rerun` exists for `pythontex.py`.

```
hashdependencies=<none>/true/false
  default:false <none>=true
```

When external code files are highlighted with Pygments, or external dependencies are specified via the `PythonTeX` utilities class, they are checked for modification via their modification time (Python's `os.path.getmtime()`). Usually, this should be sufficient—and it offers superior performance, which is important if data sets are large enough that hashing takes a noticeable amount of time. However, occasionally hashing may be necessary or desirable, so this option is provided.

A command-line equivalent `--hashdependencies` exists for `pythontex.py`.

```
autoprint=<none>/true/false
  default:true <none>=true
autostdout=<none>/true/false
  default:true <none>=true
```

Whenever a `print` command/statement is used, the printed content will automatically be included in the document, unless the code doing the printing is being typeset.¹⁶ In that case, the printed content must be included using the `\printpythontex` or `\stdoutpythontex` commands.

Printed content is pulled in directly from the external file in which it is saved, and is interpreted by \LaTeX as \LaTeX code. If you wish to avoid this, you should print appropriate \LaTeX commands with your content to ensure that it is typeset as you desire. Alternatively, you may use `\printpythontex` or `\stdoutpythontex` to bring in printed content in verbatim form, using those commands' optional `verb` and `verbatim` options.

The `autoprint` (`autostdout`) option sets autoprint behavior for the entire document. This may be overridden within the document using the `\setpythontexautoprint` command.

`debug`

This option aids in debugging invalid \LaTeX code that is brought in from Python. It disables the inclusion of printed content/content written to `stdout`.

¹⁶Note that `autoprint` only works within the body of the document. The `code` command and environment can be used in the preamble, but `autoprint` is disabled there. It is usually a not a good idea to print in the preamble, because nothing can be typeset; the only thing that could be validly printed is \LaTeX commands that do not typeset content, such as macro definitions. Thus, it is appropriate that printed content is only brought in while in the preamble if it is explicitly requested via `\printpythontex`. This approach is also helpful for writing packages using `PythonTeX`, since the author does not have to worry about any \LaTeX commands printed by the package either not being included (if `autoprint` is relied upon, but the user turns it off) or being included twice (if `\printpythontex` is used and `autoprint` is enabled). Printing should only be used in the preamble with great care.

Since printed content should almost **always** be included, a warning is raised when this option is used.

Not including printed content is useful when the printed content contains L^AT_EX errors, and would cause document compilation to fail. When the document fails to compile, this can prevent modified Python code from being written to the code file, resulting in an inescapable loop unless printed content is disabled or the saved output is deleted.

Note that since commands like `\py` involve printing, they are also disabled.

`makestderr=<none>/true/false`
`default:false <none>=true`

This option determines whether the stderr produced by scripts is available for input by Python_TE_X, via the `\stderrpythontex` macro. This will not be needed in most situations. It is intended for typesetting incorrect code next to the errors that it produces. This option is not **true** by default, because additional processing is required to synchronize stderr with the document.

`stderrfilename=full/session/genericfile/genericscript`
`default:full`

This option governs the file name that appears in `stderr`. Python errors begin with a line of the form

File "<file or source>", line <line>

By default (option `full`), `<file or source>` is the actual name of the script that was executed. The name will be in the form *(family name)₋(session)₋(restart)_.(extension)*. For example, an error produced by a `py` command or environment, in the session `mysession`, using the default restart (that is, the default `\restartpythontexsession` treatment), would be reported in `py_mysession_default.py`. The `session` option replaces the full file name with the name of the session, `mysession.py` in this example. The `genericfile` and `genericscript` options replace the file name with `<file>` and `<script>`, respectively.

`pyfuture=none/all/default`
`default:default`

Under Python 2, this determines what is automatically imported from `__future__` for all code. It does not apply to `console` content. `none` imports nothing from `__future__`. `all` imports everything available in Python 2.7 (`absolute_import`, `division`, `print_function`, and `unicode_literals`). `default` imports a default set of features that should be compatible with almost all packages. Everything except `unicode_literals` is imported, since `unicode_literals` can occasionally cause conflicts. Note that imports from `__future__` are also allowed within sessions, so long as they are at the very beginning of the session, as they would have to be in a normal script.

This option has no effect under Python 3.

`pyconfuture=none/all/default`
`default:none`

This is the equivalent of `pyfuture` for Python `console` content. The two options are separate, because in the `console` context it may be desirable to show explicitly all code that is executed.

`upquote=<none>/true/false`
`default:true <none>=true`

This option determines whether the `upquote` package is loaded. In general, the `upquote` package should be loaded, because it ensures that quotes within verbatim contexts are “upquotes,” that is, `'` rather than `’`.

Using `upquote` is important beyond mere presentation. It allows code to be copied directly from the compiled PDF and executed without any errors due to quotes ' being copied as acute accents ´.

```
fixlr=<none>/true/false
default:false <none>=true
```

This option removes “extra” spacing around `\left` and `\right` in math mode. This spacing is sometimes undesirable, especially when typesetting functions such as the trig functions. See the implementation for details. Similar functionality is provided by the `mlefttright` package

```
keeptemps=<none>/all/code/none
default:none <none>=all
```

When PythonTeX runs, it creates a number of temporary files. By default, none of these are kept. The `none` option keeps no temp files, the `code` option keeps only code temp files (these can be useful for debugging), and the `all` option keeps all temp files (code, stdout and stderr for each code file, etc.). Note that this option does not apply to any user-generated content, since PythonTeX knows very little about that; it only applies to files that PythonTeX automatically creates by itself.

```
prettyprinter=pygments/fancyvrb
default:pygments
```

This allows the user to determine at the document level whether code is typeset using Pygments or `fancyvrb`.

The package-level option can be overridden for individual command and environment families, using the `\setpythontexprettyprinter` command. Overriding is never automatic and should generally be avoided, since using Pygments to highlight only some content results in an inconsistent style. Keep in mind that Pygment’s `text` lexer and/or `bw` style can be used when content needs little or no syntax highlighting.

```
prettyprintinline=<none>/true/false
default:true <none>=true
```

This determines whether inline content is pretty printed. If it is turned off, inline content is typeset with `fancyvrb`.

```
pygments=<none>/true/false
default:true <none>=true
```

This allows the user to determine at the document level whether code is typeset using Pygments rather than `fancyvrb`. It is an alias for `prettyprinter=pygments`.

```
pyginline=<none>/true/false
default:true <none>=true
```

This option governs whether inline code, not just code in environments, is highlighted when Pygments highlighting is in use. When Pygments is in use, it will highlight everything by default.

It is an alias for `prettyprintinline`.

```
pyglexer=<pygments lexer>
default:<none>
```

This allows a Pygments lexer to be set at the document level. In general, this option should **not** be used. It overrides the default lexer for all commands and environments, for both PythonTeX and Pygments content, and this is usually not desirable. It should be useful primarily when all content uses the same lexer, and multiple lexers are compatible with the content.

```
pygopt={<pygments options>}
default:<none>
```

This allows Pygments options to be set at the document level. The options must be enclosed in curly braces `{}`. Currently, three options may be passed in this manner: `style=<style name>`, which sets the formatting

style; `texcomments`, which allows L^AT_EX in code comments to be rendered; and `mathescape`, which allows L^AT_EX math mode (\dots) in comments. The `texcomments` and `mathescape` options may be used with an argument (for example, `texcomments=True/False`); if an argument is not supplied, `True` is assumed. Example: `pygopt={style=colorful, texcomments=True, mathescape=False}`.

Pygments options for individual command and environment families may be set with the `\setpythontexpygopt` macro; for Pygments content, there is `\setpygmentspygopt`. These individual settings are always overridden by the package option.

`fvextfile=<none>/<integer>`
`default:∞ <none>=25`

This option speeds the typesetting of long blocks of code that are created on the Python side. This includes content highlighted using Pygments and the `console` environment. Typesetting speed is increased at the expense of creating additional external files (in the Python_TE_X directory). The `<integer>` determines the number of lines of code at which the system starts using multiple external files, rather than a single external file. See the implementation for the technical details; basically, an external file is used rather than `fancyvrb`'s `SaveVerbatim`, which becomes increasingly inefficient as the length of the saved verbatim content grows. In most situations, this option should not be needed, or should be fine with the default value or similar "small" integers.

`pyconbanner=none/standard/default/pyversion`
`default:none`

This option governs the appearance (or disappearance) of a banner at the beginning of Python console environments. (A banner only appears in the first environment within each session.) The options `none` (no banner), `standard` (standard Python banner), `default` (default banner for Python's `code` module, standard banner plus interactive console class name), and `pyversion` (banner in the form Python x.y.z) are accepted.

`pyconfilename=stdin/console`
`default:stdin`

This governs the form of the filename that appears in error messages in Python console environments. Python errors messages have a form such as the following:

```
>>> z = 1 + 34 +
      File "<name>", line 1
        z = 1 + 34 +
              ^
SyntaxError: invalid syntax
```

The `stdin` option replaces `<name>` with `<stdin>`, as it appears in a standard Python interactive session. The `console` option uses `<console>` instead, which is the default setting for the Python `code` module used by Python_TE_X to create Python console environments.

`depythontex=<none>/true/false`
`default:false <none>=true`

This option is used to create a version of the L^AT_EX document that does not require the Python_TE_X package. When invoked, it creates an auxiliary file called `<filename>.depytx`. The script `depythontex.py` uses the original document and this auxiliary file to create a new document in which all Python_TE_X commands and

environments have been replaced by typeset code and code output. For additional information on `depythontex`, see Section 4.

3.2 Commands and environments

PythonTeX provides four types of commands for use with inline code and three environments for use with multiple lines of code, plus special commands and environments for `console` content. All commands and environments are named using a base name and a command- or environment-specific suffix. A complete set of commands and environments with the same base name constitutes a **command and environment family**. In what follows, the different commands and environments are described using the `py` base name (the `py` family) as an example.

Most commands and environments cannot be used in the preamble, because they typeset material and that is not possible in the preamble. The one exception is the `code` command and environment. These can be used to enter code, but need not typeset anything. This allows you to collect your PythonTeX code in the preamble, if you wish, or even use PythonTeX in package writing. Note that the package option `autoprint` is never active in the preamble, so even if a `code` command or environment did print in the preamble, printed content would never be inputted unless `\printpythontex` or `\stdoutpythontex` were used.

All commands and environments take a session name as an optional argument. The session name determines the session in which the code is executed. This allows code to be executed in multiple independent sessions, increasing speed (sessions run in parallel) and preventing naming conflicts. If a session is not specified, then the `default` session is used. Session names should use the characters a-z, A-Z, 0-9, the hyphen, and the underscore. All characters used **must** be valid in file names, since session names are used to create temporary files. The colon is also allowed, but it is replaced with a hyphen internally, so the sessions `code:1` and `code-1` are identical.

In addition, all environments take `fancyvrb` settings as a second, optional argument. See the [fancyvrb documentation](#) for an explanation of accepted settings. This second optional argument **must** be preceded by the first optional argument (session name). If a named session is not desired, the optional argument can be left empty (`default` session), but the square brackets `[]` must be present so that the second optional argument may be correctly identified:

```
\begin{environment}[] [fancyvrb settings]
```

3.2.1 Inline commands

Inline commands are suitable for single lines of code that need to be executed within the body of a paragraph or within a larger body of text. The commands use arbitrary code delimiters (like `\verb` does), which allows the code to contain arbitrary characters. Note that this is only guaranteed to work properly when the inline commands are **not** inside other macros. If an inline command is used within another macro, the code will be read by the external macro before PythonTeX

can read the special code characters (that is, L^AT_EX will tokenize the code). The inline commands can work properly within other macros, but it is best to stick with curly braces for delimiters in this case and you may have trouble with the hash # and percent % characters.

`\py[session][opening delim]codeclosing delim`

This command is used for including variable values or other content that can be converted to a string. It is an alternative to including content via the `print` statement/function within other commands/environments.

The `\py` command sends *code* to Python, and Python returns a string representation of *code*. *opening delim* and *closing delim* must be either a pair of identical, non-space characters, or a pair of curly braces. If curly braces are used as delimiters, then curly braces may only be used within *code* if they are paired. Thus, `\py{1+1}` sends the code `1+1` to Python, Python evaluates the string representation of this code, and the result is returned to L^AT_EX and included as 2. The commands `\py#1+1#` and `\py@1+1@` would have the same effect. The command can also be used to access variable values. For example, if the code `a=1` had been executed previously, then `\py{a}` simply brings the string representation of `a` back into the document as 1.

Assignment is **not** allowed using `\py`. For example, `\py{a=1}` is **not** valid. This is because assignment cannot be converted to a string.¹⁷

The text returned by Python must be valid L^AT_EX code. Verbatim and other special content is allowed under the pdfTeX and XeTeX engines (a known bug prevents it from working with LuaTeX). The primary reasons for using `\py` rather than `print` are (1) `\py` is more compact and (2) `print` requires an external file to be created for every command or environment in which it is used, while `\py` and equivalents for other families share a single external file. Thus, use of `\py` minimizes the creation of external files, which is a key design goal for PythonT_EX.¹⁸ The main reason for using `print` rather than `\py` is if you need to include a very large amount of material; `print`'s use of external files won't use up T_EX's memory, and may give noticeably better performance once the material is sufficiently long.

`\pyc[session][opening delim]codeclosing delim`

This command is used for executing but not typesetting *code*. The suffix `c` is an abbreviation of `code`. If the `print` statement/function is used within *code*, printed content will be included automatically so long as the package `autoprint` option is set to true (the default setting).

¹⁷It would be simple to allow any code within `\py`, including assignment, by using a `try/except` statement. In this way, the functionality of `\py` and `\pyc` could be merged. While that would be simpler to use, it also has serious drawbacks. If `\py` is not exclusively used to typeset string representations of *code*, then it is no longer possible on the L^AT_EX side to determine whether a command should return a string. Thus, it is harder to determine, from within a T_EX editor, whether `pythontex.py` needs to be run; warnings for missing Python content could not be issued, because the system wouldn't know (on the L^AT_EX side) whether content was indeed missing.

¹⁸For `\py`, the text returned by Python is stored in macros and thus must be valid L^AT_EX code, because L^AT_EX interprets the returned content. The use of macros for storing returned content means that an external file need not be created for each use of `\py`. Rather, all macros created by `\py` and equivalent commands from other families are stored in a single file that is inputted. Note that even though the content is stored in macros, verbatim content is allowed, through the use of special macro definitions combined with `\scantokens`.

`\pyv[session][opening delim]codeclosing delim`

This command is used for typesetting but not executing *code*. The suffix *v* is an abbreviation for **verb**.

`\pyb[session][opening delim]codeclosing delim`

This command both executes and typesets *code*. Since it is unlikely that the user would wish to typeset code and then **immediately** include any output of the code, printed content is **not** automatically included, even when the package `autoprint` option is set to true. Rather, any printed content is included at a user-designated location via the `\printpythontex` or `\stdoutpythontex` macros.

3.2.2 Environments

`pycode [session][fancyvrb settings]`

This environment encloses code that is executed but not typeset. The second optional argument *fancyvrb settings* is irrelevant since nothing is typeset, but it is accepted to maintain parallelism with the `verbatim` and `block` environments. If the `print` statement/function is used within the environment, printed content will be included automatically so long as the package `autoprint` option is set to true (the default setting).

`pyverbatim [session][fancyvrb settings]`

This environment encloses code that is typeset but not executed.

`pyblock [session][fancyvrb settings]`

This environment encloses code that is both executed and typeset. Since it is unlikely that the user would wish to typeset code and then **immediately** print any output of the code, printed content is **not** automatically included, even when the package `autoprint` option is set to true. Rather, any printed content is included at a user-designated location via the `\printpythontex` or `\stdoutpythontex` macros.

3.2.3 Console command and environment families

So far, we have considered the `py` command and environment family. `PythonTeX` also provides families for `console` content. These emulate the behavior of a Python interactive console. In what follows, the `pycon` family is described

The `pycon` family includes a `\pyconv` and `pyconverbatim` that typeset a console session pasted from an interpreter. It also includes a `\pyconc` and `pyconcode` that execute code but typeset nothing. These should be used with care, since it may often be advisable to show all executed code when working with an interactive console.

The `pycon` family also includes a special environment and command.

`pyconsole [session][fancyvrb settings]`

This environment treats its contents as a series of commands passed to an interactive Python console. Python's `code` module is used to intersperse the commands with their output, to emulate an interactive Python interpreter.

When a multi-line command is entered (for example, a function definition), a blank line after the last line of the command may be necessary.

For example,

```
a = 1
b = 2
a + b
```

produces

```
>>> a = 1
>>> b = 2
>>> a + b
3
```

`\pycon[session][opening delim]code[closing delim]`

This command executes *code* using the emulated interpreter, and brings the output back into the document, **discarding the input**. The output is typeset verbatim (since it will not in general be valid L^AT_EX), with the same font used for the `pyconsole` environment.

For example, `\pycon{a + b}` would create 3.

This command is primarily for use in referencing console variable values.

Notice that there is **not** a command or environment for `console` content that parallels the `block` command and environment. That is, there is not a command or environment that both typesets and executes code in the console, but does not show the output. This is intentional. In most cases, if you are going to use the console, you should use it consistently, showing input and output together.

3.2.4 Default families

By default, three command and environment families are defined, with three corresponding console families.

- Python
 - Base name `py`: `\py`, `\pyc`, `\pyv`, `\pyb`, `pycode`, `pyverbatim`, `pyblock`.
 - Base name `pycon`: `\pycon`, `\pyconc`, `\pyconv`, `pyconsole`, `pyconcode`, `pyconverbatim`.
 - Imports: None.
- Python + `pylab` (matplotlib module)
 - Base name `pylab`: `\pylab`, `\pylabc`, `\pylabv`, `\pylabb`, `pylabcode`, `pylabverbatim`, `pylabblock`.
 - Base name `pylabcon`: `\pylabcon`, `\pylabconc`, `\pylabconv`, `pylabconsole`, `pylabconcode`, `pylabconverbatim`.
 - Imports: matplotlib's `pylab` module, which provides access to much of matplotlib and NumPy within a single namespace. `pylab` content is brought in via `from pylab import *`.

- Additional notes: matplotlib added a [pgf backend](#) in version 1.2. You will probably want to use this for creating most plots. However, this is not currently configured automatically because many users will want to customize font, T_EX engine, and other settings. Using T_EX to create plots also introduces a performance penalty.
- Python + SymPy
 - Base name `sympy`: `\sympy`, `\sympyc`, `\sympyv`, `\sympyb`, `sympycode`, `sympyverbatim`, `sympyblock`, `sympyconsole`.
 - Base name `sympycon`: `\sympycon`, `\sympyconc`, `\sympyconv`, `sympyconsole`, `sympyconcode`, `sympyconverbatim`.
 - Imports: SymPy via `from sympy import *`.
 - Additional notes: By default, content brought in via `\sympy` is formatted using a context-sensitive interface to SymPy’s `LatexPrinter` class, described below.

Under Python 2.7, all non-console families import `absolute_import`, `division`, and `print_function` from `__future__` by default. This may be changed using the package option `pyfuture`. There is an equivalent `pyconfuture` for console families. Keep in mind that importing `unicode_literals` from `__future__` may break compatibility with some packages; this is why it is not imported by default. Imports from `__future__` are also possible without using the `pyfuture` option. You may use the `\pythontexcustomc` command or `pythontexcustomcode` environment (described below), or simply enter the import commands immediately at the beginning of a session.

3.2.5 Custom code

You may wish to customize the behavior of one or more families within a document by adding custom code to the beginning and end of each session. The custom code command and environment make this possible. While the custom code command and environment work with `console` content, most of the discussion below is geared toward the non-`console` case.

If you wish to share these customizations among several documents, you can create your own document class or package containing custom code commands and environments.

While custom code can be added anywhere in a document, it is probably best for organizational reasons to add it in the preamble or near the beginning of the document.

Note that custom code is executed, but never typeset. Only code that is actually entered within a `block` (or `verbatim`) command or environment is ever typeset. This means that you should be careful about how you use custom code. For example, if you are documenting code, you probably want to show absolutely all code that is executed, and in that case using custom code might not be appropriate. If you are using PythonT_EX to create figures or automate text, are

using many sessions, and require many imports, then custom code could save some typing by centralizing the imports.

Any errors or warnings due to custom code will be correctly synchronized with the document, just like normal errors and warnings. Any errors or warnings will be specifically identified as originating in custom code.

Custom code is not allowed to print or write to stdout. It would be pointless for custom code at the beginning of a session to print, because all printed content would be identical since custom code at the beginning comes before any regular code that might make the output session-specific. In addition, it is not obvious where printed content from custom code would be included, especially for custom code at the end of a session. Furthermore, custom code may be in the preamble, where nothing can be typeset.

If custom code does attempt to print, a warning is raised and the printed content is included in the PythonTeX run summary. This gives you access to the printed content, while not including it in the document. This can be useful in cases where you cannot control whether content prints (for example, if a library automatically prints debugging information).

```
\pythontexcustomec[<position>]{<family>}{<code>}
```

This macro allows custom code to be added to all sessions within a command and environment family. *<position>* should be either **begin** or **end**; it determines whether the custom code is executed at the beginning or end of each session. By default, custom code is executed at the beginning. *<code>* should be a **single line** of code. For example, `\pythontexcustomec{py}{a=1; b=2}` would create the variables **a** and **b** within all sessions of the **py** family, by adding that line of code at the beginning of each session.

If you need to add more than a single line of custom code, you could use the command multiple times, but it will be more efficient to use the `pythontexcustomecode` environment.

<code> may contain imports from `__future__`. These must be the first elements in any custom code command or environment, since `__future__` imports are only possible at the very beginning of a Python script and only the very beginning of custom code is checked for them. If imports from `__future__` are present at the beginning of both custom code and the user's code, all imports will work correctly; the presence of the imports in custom code, before user code, does not turn off checking for `__future__` imports at the very beginning of user code. However, it is probably best to keep all `__future__` imports in a single location.

```
pythontexcustomecode[<position>]{<family>}
```

This is the environment equivalent of `\pythontexcustomec`. It is used for adding multi-line custom code to a command and environment family. In general, the environment should be preferred to the command unless only a very small amount of custom code is needed. The environment has the same properties as the command, including the ability to contain imports from `__future__`.

3.2.6 Python \TeX utilities class

All non-console families import `pythontex_utils.py`, and create an instance of the Python \TeX utilities class called `pytex`. This provides various utilities for interfacing with \LaTeX and Python \TeX .

The utilities class provides an interface for determining how Python objects are converted into strings in commands such as `\py`. The `pytex.set_formatter(formatter)` method is used to set the conversion. Two formatters are provided:

- `'str'` converts Python objects to a string, using the `str()` function under Python 3 and the `unicode()` function under Python 2. (The use of `unicode()` under Python 2 should not cause problems, even if you have not imported `unicode_literals` and are not using unicode strings. All encoding issues should be taken care of automatically by the utilities class.)
- `'sympy_latex'` uses SymPy's `LatexPrinter` class to return context-sensitive \LaTeX representations of SymPy objects. Separate `LatexPrinter` settings may be created for the following contexts: `'display'` (displaystyle math), `'text'` (textstyle math), `'script'` (superscripts and subscripts), and `'scriptscript'` (superscripts and subscripts, of superscripts and subscripts). Settings are created via `pytex.set_sympy_latex(context, settings)`. For example, `pytex.set_sympy_latex('display', mul_symbol='times')` sets multiplication to use a multiplication symbol \times , but only when math is in displaystyle.¹⁹ See the [SymPy documentation](#) for a list of possible settings for the `LatexPrinter` class.

By default, `'sympy_latex'` only treats matrices differently based on context. Matrices in displaystyle are typeset using `pmatrix`, while those in all other styles are typeset via `smallmatrix` with parentheses.

The context-sensitive interface to SymPy's `LatexPrinter` is always available via `pytex.sympy_latex()`.

The Python \TeX utilities formatter may be set to a custom function that returns strings, simply by reassigning the `pytex.formatter()` method. For example, define a formatter function `my_func()`, and then `pytex.formatter=my_func`.

The utilities class also provides methods for tracking dependencies and created files.

- `pytex.add_dependencies(dependencies)` This adds *dependencies* to a list. If any dependencies in the list change, code is re-executed, even if the code itself has not changed (unless `rerun=never`). Modified dependencies are determined via either modification time (default) or hash; see the package option `hashdependencies` for details. This method is useful for tracking changes in external data and similar files.

¹⁹Internally, the `'sympy_latex'` formatter uses the `\mathchoice` macro to return multiple representations of a SymPy object, if needed by the current settings. Then `\mathchoice` typesets the correct representation, based on context.

dependencies) should be one or more strings, separated by commas, that are the file names of dependencies. Dependencies should be given with relative paths from the current working directory, with absolute paths, or with paths based on the user's home directory (that is, starting with a tilde ~). Paths can use a forward slash "/" even under Windows. Remember that by default, the working directory is the `pythontex-files-jobname` directory where all PythonTeX temporary files are stored. This can be adjusted with `\setpythontexworkingdir`.

It is possible that a dependency of one session might be modified by another session while PythonTeX runs. The first session might not be executed during the PythonTeX run because its dependency was unmodified at the beginning. A more serious case occurs when the first session does run, but we don't know whether it accessed the dependency before or after the dependency was updated (remember, sessions run in parallel). PythonTeX keeps track of the time at which it started. Any sessions with dependencies that were modified after that time are set to re-execute on the next run. A warning is also issued to indicate that this is the case.

- `pytex.add_created(created files)` This adds *created files* to a list of files created by the current session. Any time the code for the current session is executed, **all of these files will be deleted**. Since this method deletes files, it should be used with care. It is intended for automating cleanup when code is modified. For example, if a figure's name is changed, the old figure would be deleted if its name had been added to the list. By default, PythonTeX can only clean up the temporary files it creates; it knows nothing about user-created files. This method allows user-created files to be specified, and thus added to PythonTeX's automatic cleanup.

created files) should be one or more strings, separated by commas, that are the file names of created files. Paths should be the same as for `pytex.add_dependencies()`: relative to the working directory, absolute, or based on the user's home directory. Again, paths can use a forward slash "/" even under Windows.

Depending on how you use PythonTeX, this method may not be very beneficial. If all of the output is contained in the default output directory, or a similar directory of your choosing, then manual cleanup may be simple enough that this method is not needed.

These two methods for tracking files may be used manually. However, that is prone to errors, since you will have to modify both a PythonTeX utilities command and an open or save command every time you change a file name or add or remove a dependency or created file. It may be better to redefine your open and save commands, or define new ones, so that a single command opens (or saves) and adds a dependency (or adds a created file). For example, the following would create a version of the standard `open()` that automatically tracks dependencies and created files.

```

def track_open(file, mode='r', *args, **kwargs):
    if mode in ('r', 'rb'):
        pytex.add_dependencies(file)
    elif mode in ('w', 'wb'):
        pytex.add_created(file)
    return open(file, mode, *args, **kwargs)
pytex.open = track_open

```

Notice that this approach does not deal with files opened for appending or updating; such cases require more complex logic.

The utilities class provides a pair of methods, `before()` and `after()`, that are called immediately before and after each chunk of user code. These may be redefined to customize the output of user code. For example, \LaTeX commands could be printed at the beginning and end of each command or environment, wrapping any content printed by the user. Or any matplotlib figures that were created in the chunk of code could be detected and saved, and \LaTeX commands to include them in the document could be printed. Or `stdout` could be redirected to a `StringIO` stream in `before()`, then processed in `after()` before being sent to the original `stdout`.

You may redefine `before()` and `after()` at the class level. For example,

```

def open(self):
    <body>
PythontexUtils.open = open

```

Or you may redefine these methods as instance attributes that happen to be functions (rather than bound methods). Notice that in this case `self` is not allowed.

```

def open():
    <body>
pytex.open = open

```

Finally, you may redefine these methods as bound methods for the `pytex` instance.

```

def open(self):
    <body>
import types
pytex.open = types.MethodType(open, pytex)

```

The first and third approaches are necessary if you want to be able to use `self` (for example, to access instance attributes). Notice that `before()` and `after()` take no arguments (except `self` where applicable).

An example of using the `after()` method to automatically save and include all matplotlib figures created in a command or environment is shown below. This example is designed for the `pylab` family of commands, or when

from pylab import * is used. If pyplot is imported as plt instead, then plt.get_fignums(), plt.figure(), plt.savefig(), plt.close(), etc., would be needed.

```
# Basename for figures that will be created
pytex.basename = '_' .join([pytex.input_type, pytex.input_session,
                             pytex.input_restart])

# Need to keep track of total number of figures in each session
pytex.fignum = 0

# The figure could be included in more sophisticated ways
# For example, a ‘figure‘ environment could be used
def after():
    for num in get_fignums():
        fname = pytex.basename + '_fig' + str(pytex.fignum) + '.pdf'
        pytex.fignum += 1
        figure(num)
        savefig(fname)
        pytex.add_created(fname)
        close(num)
        print(r'\includegraphics{' + fname + '}')

# In this case, I'm taking the easy approach to redefine ‘open()‘
pytex.after = after
```

3.2.7 Formatting of typeset code

`\setpythontexfv[⟨family⟩]{⟨fancyvrb settings⟩}`

This command sets the `fancyvrb` settings for all command and environment families. Alternatively, if an optional argument *⟨family⟩* is supplied, the settings only apply to the family with that base name. The general command will override family-specific settings.

Each time the command is used, it completely overwrites the previous settings. If you only need to change the settings for a few pieces of code, you should use the second optional argument in `block` and `verb` environments.

Note that `\setpythontexfv` and `\setpygmentsfv` are equivalent when they are used without an optional argument; in that case, either may be used to determine the document-wide `fancyvrb` settings, because both use the same underlying macro.

`\setpythontexprettyprinter[⟨family⟩]{⟨printer⟩}`

This should generally not be needed. It sets the pretty printing used by the document, or by *⟨family⟩* if given. Valid options for *⟨printer⟩* are `fancyvrb` and `pygments`. The option `auto` may be given for *⟨family⟩*, in which case the formatter is inherited from the document-level settings. Using either of the other two options will force *⟨family⟩* to use that printer, regardless of the document-level settings. By default, families use `auto`.

Remember that Pygments has a `text` lexer and a `bw` style. These are an alternative to setting the formatter to `fancyvrb`.

```
\setpythontexpyglexer[⟨family⟩]{⟨pygments lexer⟩}
```

This allows the Pygments lexer to be set for $\langle family \rangle$. $\langle pygments\ lexer \rangle$ should use a form of the lexer name that does not involve any special characters. For example, you would want to use the lexer name `csharp` rather than `C#`. This will be a consideration primarily when using the Pygments commands and environments to typeset code of an arbitrary language.

If a $\langle family \rangle$ is not specified, the lexer is set for the entire document.

```
\setpythontexpygopt[⟨family⟩]{⟨pygments options⟩}
```

This allows the Pygments options for $\langle family \rangle$ to be redefined. Note that any previous options are overwritten. The same Pygments options may be passed here as are available via the package `pygopt` option. Note that for each available option, individual family settings will be overridden by the package-level `pygopt` settings, if any are given.

If a $\langle family \rangle$ is not specified, the options are set for the entire document.

3.2.8 Access to printed content (stdout) and error messages (stderr)

The macros that allow access to printed content and any additional content written to `stdout` are provided in two identical forms: one based off of the word `print` and one based off of `stdout`. Macro choice depends on user preference. The `stdout` form provides parallelism with the macros that provide access to `stderr`.

```
\printpythontex[⟨mode⟩][⟨options⟩]
```

```
\stdoutpythontex[⟨mode⟩][⟨options⟩]
```

Unless the package option `autoprint` is true, printed content from `code` commands and environments will not be automatically included. Even when the `autoprint` option is turned on, `block` commands and environments do not automatically include printed content, since we will generally not want printed content immediately after typeset code. This macro brings in any printed content from the `last` command or environment. It is reset after each command/environment, so its scope for accessing particular printed content is very limited. It will return an error if no printed content exists.

$\langle mode \rangle$ determines how printed content is handled. It may be `raw` (interpreted as \LaTeX), `verb` (inline verbatim), or `verbatim`; `raw` is the default. Verbatim content is brought in via `fancyvrb`. $\langle options \rangle$ consists of `fancyvrb` settings.

```
\saveprintpythontex{⟨name⟩}
```

```
\savestdoutpythontex{⟨name⟩}
```

```
\useprintpythontex[⟨verbatim options⟩][⟨fancyvrb options⟩]{⟨name⟩}
```

```
\usestdoutpythontex[⟨verbatim options⟩][⟨fancyvrb options⟩]{⟨name⟩}
```

We may wish to be able to access the printed content from a command or environment at any point after the code that prints it, not just before any additional commands or environments are used. In that case, we may save access to the content under $\langle name \rangle$, and access it later via `\useprintpythontex{⟨name⟩}`. $\langle mode \rangle$ must be `raw`, `verb`, or `verbatim`. If content is brought in verbatim, then $\langle fancyvrb\ options \rangle$ are applied.

`\stderrpythontex[mode][fancyvrb options]`

This brings in the `stderr` produced by the last command or environment. It is intended for typesetting incorrect code next to the errors that it produces. By default, `stderr` is brought in verbatim. *mode* may be set to `raw`, `verb`, or `verbatim`. In general, bringing in `stderr raw` should be avoided, since `stderr` will typically include special characters that will make \TeX unhappy.

The line number given in the `stderr` message will correctly align with the line numbering of the typeset code. Note that this only applies to `code` and `block` environments. Inline commands do not have line numbers, and as a result, they **do not** produce `stderr` content.

By default, the file name given in the message will be in the form

*(family name)*_*(session)*_*(group)*.*(extension)*

For example, an error produced by a `pycode` environment, in the session `mysession`, using the default group (that is, the default `\restartpythontexsession` treatment), would be reported in `py_mysession_default.py`. The package option `stderrfilename` may be used to change the reported name to the following forms: `mysession.py`, `<file>`, `<script>`.

`\savestderrpythontex{name}`

`\usestderrpythontex[mode][fancyvrb options]{name}`

Content written to `stderr` may be saved and accessed anywhere later in the document, just as `stdout` content may be. These commands should be used with care. Using Python-generated content at multiple locations within a document may often be appropriate. But an error message will usually be most meaningful in its context, next to the code that produced it.

`\setpythontexautoprint{boolean}`

`\setpythontexautostdout{boolean}`

This allows `autoprint` behavior to be modified at various points within the document. The package-level `autoprint` option is also available for setting `autoprint` at the document level, but it is overridden by `\setpythontexautoprint`. *boolean* should be `true` or `false`.

3.3 Pygments commands and environments

Although Python \TeX 's goal is primarily the execution and typesetting of Python code from within \LaTeX , it also provides access to syntax highlighting for any language supported by Pygments.

`\pygment{lexer}(opening delim)(code)(closing delim)`

This command typesets *code* in a suitable form for inline use within a paragraph, using the specified Pygments *lexer*. Internally, it uses the same macros as the Python \TeX inline commands. *(opening delim)* and *(closing delim)* may be a pair of any characters except for the space character, or a matched set of curly braces `{}`.

As with the inline commands for code typesetting and execution, there is not an optional argument for `fancyvrb` settings, since almost all of them are not relevant

for inline usage, and the few that might be should probably be used document-wide if at all.

`pygments [fancyvrb settings]{lexer}`

This environment typesets its contents using the specified Pygments *lexer* and applying the *fancyvrb settings*.

`\inputpygments[fancyvrb settings]{lexer}{external file}`

This command brings in the contents of *external file*, highlights it using *lexer*, and typesets it using *fancyvrb settings*.

`\setpygmentsfv[lexer]{fancyvrb settings}`

This command sets the *fancyvrb settings* for *lexer*. If no *lexer* is supplied, then it sets document-wide *fancyvrb settings*. In that case, it is equivalent to `\setpythontexfv{fancyvrb settings}`.

`\setpygmentspygopt[lexer]{pygments options}`

This sets *lexer* to use *pygments options*. If there is any overlap between *pygments options* and the package-level `pygopt`, the package-level options override the lexer-specific options.

If *lexer* is not given, options are set for the entire document.

`\setpygmentsprettyprinter{printer}`

This usually should not be needed. It allows the pretty printer for the document to be set; it is equivalent to using `\setpythontexprettyprinter` without an optional argument. Valid options for *printer* are `fancyvrb` and `pygments`.

Remember that Pygments has a `text` lexer and a `bw` style. These are an alternative to setting the formatter to use `fancyvrb`.

3.4 General code typesetting

3.4.1 Listings float

`listing`

Python_{TeX} will create a float environment `listing` for code listings, unless an environment with that name already exists. The `listing` environment is created using the `newfloat` package. Customization is possible through `newfloat`'s `\SetupFloatingEnvironment` command.

`\setpythontexlistingenv{alternate listing environment name}`

In the event that an environment named `listing` already exists for some other purpose, Python_{TeX} will not override it. Instead, you may set an alternate name for Python_{TeX}'s `listing` environment, via `\setpythontexlistingenv`.

3.4.2 Background colors

Python_{TeX} uses `fancyvrb` internally to typeset all code. Even code that is highlighted with Pygments is typeset afterwards with `fancyvrb`. Using `fancyvrb`, it is possible to set background colors for individual lines of code, but not for entire blocks of code, using `\FancyVerbFormatLine` (you may also wish to consider the `formatcom` option). For example, the following command puts a green background behind all the characters in each line of code:

```
\renewcommand{\FancyVerbFormatLine}[1]{\colorbox{green}{#1}}
```

If you need a completely solid colored background for an environment, or a highly customizable background, you should consider the `mdframed` package. Wrapping Python \TeX environments with `mdframed` frames works quite well. You can even automatically add a particular style of frame to all instances of an environment using the command

```
\surroundwithmdframed[{frame options}]{{environment}}
```

Or you could consider using `etoolbox` to do the same thing with `mdframed` or another framing package of your choice, via `etoolbox`'s `\BeforeBeginEnvironment` and `\AfterEndEnvironment` macros.

3.4.3 Referencing code by line number

It is possible to reference individual lines of code, by line number. If code is typeset using pure `fancyvrb`, then \LaTeX labels can be included within comments. The labels will only operate correctly (that is, be treated as \LaTeX rather than verbatim content) if `fancyvrb`'s `commandchars` option is used. For example, `commandchars=\\{\}` makes the backslash and the curly braces function normally **within** `fancyvrb` environments, allowing \LaTeX macros to work, including label definitions. Once a label is defined within a code comment, then referencing it will return the code line number.

The disadvantage of the pure `fancyvrb` approach is that by making the backslash and curly braces command characters, we can produce conflicts if the code we are typesetting contains these characters for non- \LaTeX purposes. In such a case, it might be possible to make alternate characters command characters, but it would probably be better to use Pygments.

If code is typeset using Pygments (which also ties into `fancyvrb`), then this problem is avoided. The Pygments option `texcomments=true` has Pygments look for \LaTeX code only within comments. Possible command character conflicts with the language being typeset are thus eliminated.

Note that when labels are created within comments, the labels themselves will be invisible within the final document but the comment character(s) and any other text within comments will still be visible. For example, the following

```
abc = 123 # An important line of code!\label{lst:important}
```

would appear as

```
abc = 123 # An important line of code!
```

If a comment only contains the `\label` command, then only the comment character `#` would actually be visible in the typeset code. If you are typesetting code for instructional purposes, this may be less than ideal. Unfortunately, Pygments currently does not allow escaping to \LaTeX outside of comments (though this feature has been requested). At the same time, by only allowing references within

comments, Pygments does force us to create code that would actually run. And in many cases, if a line is important enough to label, it is also important enough for a brief comment.

3.4.4 Beamer compatibility

Python_{TEX} is compatible with Beamer. Since Python_{TEX} typesets code as verbatim content, Beamer’s `fragile` option must be used for any frame that contains typeset code. Beamer’s `fragile` option involves saving frame contents to an external file and bringing it back in. This use of an external file breaks Python_{TEX}’s error line number synchronization, since the error line numbers will correspond to the temporary external file rather than to the actual document.

If you need to typeset code with Beamer, but don’t need to use overlays on the slides containing code, you should use the `fragile=singleslide` option. This allows verbatim content to be typeset without using an external file, so Python_{TEX}’s error line synchronization will work correctly.

3.5 Advanced Python_{TEX} usage

```
\restartpythontexsession{<counter value(s)>}
```

This macro determines when or if sessions are restarted (or “subdivided”). Whenever *<counter value(s)>* change, the session will be restarted.

By default, each session corresponds to a single code file that is executed. But sometimes it might be convenient if the code from each chapter or section or subsection were to run within its own file, as its own session. For example, we might want each chapter to execute separately, so that changing code within one chapter won’t require that all the code from all the other chapters be executed. But we might not want to have to go to the bother and extra typing of defining a new session for every chapter (like `\py[ch1]{<code>}`). To do that, we could use `\restartpythontexsession{\thechapter}`. This would cause all sessions to restart whenever the chapter counter changes. If we wanted sessions to restart at each section within a chapter, we would use `\restartpythontexsession{\thechapter<delim>\thesection}`. *<delim>* is needed to separate the counter values so that they are not ambiguous (for example, we need to distinguish chapter 11-1 from chapter 1-11). Usually *<delim>* should be a hyphen or an underscore; it must be a character that is valid in file names.

Note that **counter values**, and not counters themselves, must be supplied as the argument. Also note that the command applies to **all** sessions. If it did not, then we would have to keep track of which sessions restarted when, and the lack of uniformity could easily result in errors on the part of the user.

Keep in mind that when a session is restarted, all continuity is lost. It is best not to restart sessions if you need continuity. If you must restart a session, but also need to keep some data, you could save the data before restarting the session and then load the saved data after the restart. This approach should be used with

extreme caution, since it can result in unanticipated errors due to sessions not staying synchronized.²⁰

This command can only be used in the preamble.

```
\setpythontexoutdir{output directory}
```

By default, Python_{TEX} saves all temporary files and automatically generated content in a directory called `pythontex-files-sanitized jobname`, where *sanitized jobname* is just `\jobname` with any space characters or asterisks replaced with hyphens. This directory will be created by `pythontex.py`. If we wish to specify another directory (for example, if `\jobname` is long and complex, and there is no danger of two files trying to use the same directory), then we can use the `\setpythontexoutdir` macro to redefine the output directory.²¹

Any slashes in *output directory* should be forward slashes “/” (even under Windows).

```
\setpythontexworkingdir{working directory}
```

The Python_{TEX} working directory is the current working directory for Python_{TEX} scripts. This is the directory in which any open or save operations will take place, unless a path is explicitly specified. By default, the working directory is the same as the output directory. For example, if you are writing `my_file.tex` and save a matplotlib figure with `savefig('my_figure.pdf')`, then `my_figure.pdf` will be created in the output directory `pythontex-files-my_file`. But maybe you have a directory called `plots` in your document root directory. In that case, you could leave the working directory unchanged, and simply specify the relative path to `plots` when saving. Or you could set the working directory to `plots` using `\setpythontexworkingdir{plots}`, so that all content would automatically be saved there. If you want your working directory to be the document root directory, you should use a period (`.`) for *working directory*: `\setpythontexworkingdir{.}`.

Any slashes in *working directory* should be forward slashes “/” (even under Windows).

The working directory is automatically added to Python’s `sys.path`, so that code in the working directory there may be imported without a path being specified.

Note that in typical use scenarios, you should be able to use the output directory as the working directory. The `graphicx` package will automatically look for images and figures in the output directory, so long as you do not use the

²⁰For example, suppose sessions are restarted based on chapter. `session-ch1` saves a data file, and `session-ch2` loads it and uses it. You write the code, and run Python_{TEX}. Then you realize that `session-ch1` needs to be modified and make some changes. The next time Python_{TEX} runs, it will only execute `session-ch1`, since it detects no code changes in `session-ch2`. This means that `session-ch2` is not updated, at least to the extent that it depends on the data from `session-ch1`. Again, saving and loading data between restarted sessions, or just between sessions in general, can produce unexpected behavior. This can be avoided by using the `pytex.add_dependencies()` method for all data that is loaded. It will ensure that all sessions stay in sync.

²¹In the rare event that both `\setpythontexoutdir` is used and `\printpythontex` is needed in the preamble, `\setpythontexoutdir` must be used first, so that `\printpythontex` will know where to look for output.

`\graphicspath` command outside the preamble.²²

It is also possible to change the working directory from within Python code, via `os.chdir()`.

4 depyhtextex

PythonTeX can greatly simplify the creation of documents. At the same time, by introducing dependence on non-L^AT_EX external tools, it can constrain how these documents are used. For example, many publishers will not accept L^AT_EX documents that require special packages or need special macros. To address this issue, the package includes a feature called `depyhtextex` that can convert a PythonTeX document into a plain L^AT_EX document.

4.1 Preparing a document that will be converted

The conversion process should work flawlessly in most cases, with no special formatting required.

For best results, keep the following in mind.

- The PythonTeX package should have its own `\usepackage`.
- Currently, `depyhtextex` only supports the standard PythonTeX commands and environments. Support for user-defined commands and environments that incorporate PythonTeX is planned for a future release.
- If you need to insert content from Python in inline contexts, it is best to use `\py` or an equivalent command. If you use `print`, either directly (for example, from within `\pyc`) or via `\printpyhtextex`, make sure that the spacing following the printed content is correct. You may need to print an `\endinput` or `%` at the end of your content to prevent an extra trailing space. `depyhtextex` will attempt to reproduce the spacing of the original document, even if it is not ideal. See Section 4.3 for additional details.
- Some L^AT_EX environments, such as the `verbatim` environment from the `verbatim` package and the `Verbatim` environment from `fancyvrb`, do not allow text to follow the `\end{environment}`. If you bring Python-generated content that ends with one of these environments into your document, using `print` or `\py`, make sure that the end-of-environment command is followed by a newline. For example, if you are assembling a `Verbatim` environment to bring in, the last line should be the string

²²`graphicx` looks for graphics in the document root directory and in the most recent graphics path defined by `\graphicspath`. `\graphicspath` stores the graphics path in `\Ginput@path`, overwriting any previous value. At the end of the preamble, PythonTeX appends the output directory to `\Ginput@path`. Thus, that directory will always be checked for graphics, so long as `\Ginput@path` is not overwritten by a subsequent use of `\graphicspath`. If you need to use `\graphicspath` within the document, you could consider creating a custom version that redefines `\Ginput@path` with the PythonTeX output directory automatically appended.

```
'\end{Verbatim}\n'
```

Even if you neglect a final newline, `depythontex` will still function correctly in most cases. Whenever Python-generated content does not end with a newline, `depythontex` usually inserts one and gobbles spaces that follow the environment. This preserves the correct spacing while avoiding any issues produced by an end-of-environment command. But in some cases, `depythontex` cannot do this. For example, if `\py` is used to bring in a `Verbatim` environment, and there is text immediately after the `\py`, without any intervening space, `depythontex` cannot substitute a newline for spaces, because there are none. Because of the way that `print` and `\py` content is brought in, everything may still work correctly in the original `PythonTeX` document. But it would fail in the `depythontex` output.

- Do not create `PythonTeX` commands or environments on the Python side and `print` or otherwise bring them in. That is too many levels of complexity!
- `depythontex` is only designed to replace `PythonTeX` commands and environments that are actually in the main document file. Do not bring in anything that contains `PythonTeX` commands or environments via `\input`, `\include`, or `\usepackage`. The only exception is `PythonTeX` commands and environments that do not typeset anything (for example, `code` environments that don't print). If these are brought in via a package or external file, the command `\DepythontexOff` must come before them, and they must be followed by the command `\DepythontexOn`. Basically, `depythontex` must be disabled for commands and environments brought in via external files. This works so long as the commands and environments only provide code and settings, rather than any typeset content.

Tools for automatically removing the `\usepackage` for packages that contain `PythonTeX` commands will be added soon; for now, these `\usepackage`'s must be removed manually in the `depythontex` output.

- Keep in mind that the file produced by `depythontex` will need to include any graphics that you create with `PythonTeX`. Make sure any graphics are saved in a location where they are easily accessible.

4.2 Removing `PythonTeX` dependence

Converting a document requires three steps.

1. Turn on the package option `depythontex`. Then compile the document, run `pythontex.py`, and compile the document again. Depending on the document, additional compiles may be necessary (for example, to resolve references). Any syntax highlighting will be turned off automatically during this process, to remove dependence on `Pygments`.

During compilation, an auxiliary file called $\langle jobname \rangle$.depytx is created. This file contains information about the location of the PythonTeX commands and environments that need to be replaced, and about the content with which they are to be replaced.

2. Run the `depythontex.py` script. This takes the following arguments.
 - `--encoding` `ENCODING` This is the encoding of the L^AT_EX file and all related files. If an encoding is not specified, UTF-8 is assumed.
 - `--overwrite` This turns off the user prompt in the event that a file already exists with the output name, making overwriting automatic.
 - `--listing` This option specifies the commands and environments that are used for any typeset code. This can be `verbatim`, `fancyvrb`, `listings`, `minted`, or `pythontex`.²³ `verbatim` is used by default. An appropriate `\usepackage` command is automatically added to the output document's preamble.

When code is typeset with any option other than `verbatim`, listing line numbering from the original document will be preserved. When code is typeset with any option other than `verbatim` and `fancyvrb`, syntax highlighting will also be preserved. The only exception is when `listings` is used, and `listings`'s language name does not correspond to Pygments' lexer name. In this case, you should use the `--lexer-dict` option to specify how the Pygments lexer is to be translated into a `listings` language.

- `--lexer-dict` This option is used to specify how Pygments lexers are converted to `listings` languages, when the two do not have the same name. It takes a comma-separated list of the form

```
"<Pygments lexer>:<listings language>, ..., ... "
```

A Python-style dict will also be accepted.

- `--preamble` This option allows additional commands to be added to the output document's preamble. This is useful when you want the output document to load a package that was automatically loaded by PythonTeX, such as `upquote`.
- `--graphicspath` This option adds the `outputdir` to any existing graphics path defined by `\graphicspath`, or adds a `\graphicspath` command if one does not already exist. This causes the `depythontex` document to automatically look in the `outputdir` for graphics. Only use this option if you want to continue using the `outputdir` with the `depythontex` document. Graphics are further discussed below.

²³The `pythontex` option is included for completeness. In most cases, you would probably use `depythontex` to remove all dependence on PythonTeX. But sometimes it might be useful to remove all Python code while still using PythonTeX for syntax highlighting.

- `TEXTNAME` The name of the \LaTeX file whose Python \TeX dependence is to be removed.
 - `[OUTFILE]` By default, the script takes a file `<filename>.<ext>` and creates a new file called `depythontex_<filename>.<ext>`. If a name is given for the output file, that is used instead.
3. Compile the `depythontex` file, and compare it to the original.

The original and `depythontex` files should be nearly identical. All Python-generated content is substituted directly, so it should be unchanged. Usually, any differences will be due to changes in the way that code is typeset. For example, by default all code in the `depythontex` file is typeset with `\verb` and `verbatim`. But `\verb` is more fragile than the inline Python \TeX commands (it isn't allowed inside other commands), and `verbatim` does not support line numbering or syntax highlighting.

Remember that the `depythontex` file will need to include any graphics created by Python \TeX . By default, these are saved in the Python \TeX `outputdir`, which is `pythontex-files-<jobname>` unless you have customized it. They may be in other locations if you have set a non-default `workingdir` or have specified a path when saving graphics. Depending on your needs and configuration, you may wish to copy the graphics into a new location or specify their location via `\graphicspath`. Or you can run `depythontex` with the `--graphicspath` option, which will add the `outputdir` to any existing usage of `\graphicspath`, or add a `\graphicspath` command if one does not already exist.²⁴

Depending on your needs, you may wish to customize `depythontex.py`. The actual substitutions are performed in a few functions that are defined at the beginning of the script.

4.3 Technical details

The `depythontex` process should go smoothly under most circumstances, and the document produced usually should not need manual tweaking. There are a few technical details that may be of interest.

- Content that is printed (actually printed, not from a command like `\py`) is always followed by a space when included as \LaTeX code rather than as `verbatim`. Usually this is only noticeable when the content is used inline, adjacent to other text. In such cases, you need to make sure that the spacing is correct in your original document, and need to be aware of how `depythontex` handles the conversion.

This spacing behavior is due to \LaTeX 's `\input`. When the file of printed content is brought in via `\input`, \LaTeX removes any newline characters (`\n`,

²⁴Keep in mind that any time `\graphicspath` is used, it overwrites any previously specified path. If your document is using `\graphicspath` at multiple points in the preamble, or using it anywhere outside the preamble, then the `--graphicspath` option will fail due to the path being overwritten.

`\r`, or `\r\n`) at the end of each line, and adds a space at the end of each line (even if there wasn't a newline character). Thus, when the printed content is brought in, a space is added to its end. Since this space is within the `\input`'s curly braces `{}`, it is not combined with any following spaces in the \LaTeX document to make a single space. Rather, if the printed content is followed by one or more spaces, two spaces will result; and if it is followed immediately by text, there will be a single space before the text.

The space added by `\input` is often invisible, and even when it is not, it is sometimes desirable.²⁵ But this space can be an issue in some inline contexts. The simplest solution is to use a command like `\py` to bring in content inline.

If a command like `\py` is not practical for some reason, there are at least three ways to deal with the space introduced by `\input`: by printing `\endinput` at the end of the printed content (ending the content before the final space), by printing `%` at the end of the printed content (commenting out the final space), or by using `\unskip` after the printed content (eating preceding spaces). `depythontex` will work with all three approaches, but only under a limited range of circumstances. In summary, `depythontex` works with `\endinput` and `%` only if they are the very last thing printed (before a final newline), and works with a following `\unskip`.²⁶

- `\endinput` cannot be left in the printed content that is substituted into the new document, because it would cause the new document to end immediately. `depythontex` checks the very end of printed content for `\endinput`, and removes it if it is there before substituting the content. The terminating `\endinput` is only removed if it is not a string, `\string\endinput`.

If `\endinput` is anywhere else in the printed content, and it is not immediately preceded by `\string`, `depythontex` issues a warning.

- A terminating `%` cannot be left in the printed content that is substituted into the new document, because it would comment out any text in the remainder of the line into which it is substituted (in `\input`, its effect is limited to the print file). `depythontex` checks the very end of printed content for `%`, and removes it if it is there before substituting the content. `depythontex` only removes the terminating `%` if it is not a literal character `\%` or `\string%`.

²⁵For example, `\printpythontex` behaves as a normal command, and gobbles following spaces, but the space from `\input` puts a space back. So you often get the space you want in inline contexts.

²⁶It would be possible to make `depythontex` work with `\endinput` and `%` anywhere, not just at the very end of printed content. But doing so would require a lot of additional parsing, especially for `\endinput`, to be absolutely sure that we found an actual command rather than a string. Furthermore, there is no reason that there should be any content after an `\endinput` or `%`, since such content would never be included in the document. Indeed, the current approach prevents any printed content from accidentally being eliminated in this manner.

`depythontex` checks the last line of printed content for other `%` characters, and issues a warning if there are any `%` characters that are not part of `\%` or `\string%`.

- A following `\unskip` could be left in the new document, since it would not produce incorrect spacing. But it would be undesirable, since it was only there in the first place because of the way that `PythonTeX` was used. `depythontex` checks for `\unskip`, and if it is found, attempts to correct the spacing and remove the `\unskip`. This removal process is only possible if `\unskip` immediately follows a command (otherwise, it wouldn't work anyway) or is on the line immediately after the end of an environment.

If `depythontex` finds `\unskip` following printed content, but cannot replace it (it doesn't immediately follow a command, or isn't on the line immediately after the end of an environment), a warning is issued. It is possible that the `\unskip` is not correctly positioned, and even if it produces the correct spacing, the user should know that due to its location it will survive in the converted document.

If one of the above approaches is not used to eliminate the space introduced by the final newline in printed content, `depythontex` still makes sure that the spacing in the new document matches that of the original document, even if that means forcing a double space. In the majority of cases, `depythontex` can create the correct spacing using actual spaces and newlines. But in a few instances, it will include a `\space{}` to ensure a double space that matches the original document. In those situations, a warning is issued in case the spacing was not intentional.

- Strings such as `\}`, `\{`, and `\string` can occur in `PythonTeX` content that is being replaced. It is possible that they might decrease performance somewhat in larger or more complex documents.

`PythonTeX` commands for entering code allow the code to be delimited with either matched braces `{}` or with a repeated character such as `#` (as in `\verb`). Any verbatim code delimited by braces cannot **contain** any braces **unless** they are paired. So it is easy for `depythontex.py` to find the end of the delimited code.

However, `depythontex.py` must also replace `PythonTeX` commands that take a normal, non-verbatim argument delimited by braces (for example, the various `\setpythontex...` commands). Finding the closing brace for these commands is usually straightforward, but it can be tricky because the argument might contain a literal brace such as `\}` or `\string}`. `depythontex.py` automatically accounts for `\}`. If it detects `\string`, it also accounts for it, but doing so requires more intense parsing. Similarly, `\}` requires extra parsing, because depending on what comes before it, the first backslash `\` could be literal (for example, if preceded by `\string`), or the two backslashes `\` could go together to indicate a new line.

5 L^AT_EX programming with PythonT_EX

This section will be expanded in the future. For now, it offers a brief summary.

5.1 Macro programming with PythonT_EX

In many situations, you can use PythonT_EX commands inside macro definitions without any special consideration. For example, consider the following macro, for calculating powers.

```
\newcommand{\pow}[2]{\py{#1**#2}}
```

Once this is defined, we can calculate $2^{**}8$ via `\pow{2}{8}`: 256. Similarly, we can reverse a string.

```
\newcommand{\reverse}[1]{\py{"#1"[::-1]}}
```

Now we can use `\reverse{‘‘This is some text!’’}`: `!txet emos si sihT`.

Such approaches will break down when some special L^AT_EX characters such as percent % and hash # must be passed as arguments. In such cases, the arguments need to be captured verbatim. The `xparse` and `newverbs` packages provide commands for creating macros that capture verbatim arguments. You could also consult the PythonT_EX implementation, particularly the implementation of the inline commands. In either case, you may need to learn about T_EX’s catcodes and tokenization, if you aren’t already familiar with them.

Of course, there are many cases where macros don’t need arguments. Here is code for creating a macro that generates random polynomials.

```
\begin{sympycode}
from sympy.stats import DiscreteUniform, sample
x = Symbol('x')
a = DiscreteUniform('a', range(-10, 11))
b = DiscreteUniform('b', range(-10, 11))
c = DiscreteUniform('c', range(-10, 11))
def randquad():
    return Eq(sample(a)*x**2 + sample(b)*x + sample(c))
\end{sympycode}
\newcommand\randquad{\sympy{randquad()}}
```

If you are considering writing macros that involve PythonT_EX, you should keep a few things in mind.

- Do you really need to use PythonT_EX? If another package already provides the functionality you need, it may be simpler to use an existing tool, particularly if you are working with special characters and thus need to capture verbatim arguments.

- A feature called `depythontex` has recently been added. It creates a copy of the original \LaTeX document in which all `PythonTeX` commands and environments are replaced by their output, so that the new document does not depend on `PythonTeX` at all. This is primarily of interest for publication, since publishers tend not to like special packages or macros. `depythontex` does not yet support custom user commands. So if you decide to create custom macros now, and expect to need `depythontex`, you should expect to have to edit your macros before they will work with `depythontex`.

5.2 Package writing with `PythonTeX`

As of v0.10beta, the custom code command and environment, and the regular code command and environment, work in the preamble. This means that it is now possible to write packages that incorporate `PythonTeX`! At this point, packages are probably a good way to keep track of custom code that you use frequently, and maybe some macros that use `PythonTeX`.

However, you are encouraged not to develop a huge mathematical or scientific package for \LaTeX using `PythonTeX`. At least not yet! As discussed above, `depythontex` will bring changes to macro programming involving `PythonTeX`. So have fun writing packages if you want—but keep in mind that `PythonTeX` will keep changing, and some things that are difficult now may be very simple in the future.

6 Support for additional languages

Beginning with v0.12, it is much simpler to add support for languages beyond Python. Support for several additional languages will be added in coming months.

In the immediate future, support for additional languages will be part of `PythonTeX`. Later, it may make sense to provide an alternative interface for other languages. For example, a package could be created that provides access to `PythonTeX` internals in a language-agnostic manner, without having the word “python” as part of the command names.

Languages beyond Python will typically not be enabled by default, to prevent potential macro naming conflicts with other packages. At least two possible base names for commands and environments will be provided for each language. Typically these will be the name of the language and the language’s file extension. For example, Ruby has the `ruby` and `rb` base names. You can choose which base name to use for creating a family of commands and environments based on personal preference and potential naming conflicts.

6.1 Ruby

Support for Ruby was added in v0.12. Ruby support should be almost at the same level as that for Python.

The utilities class is called `RubyTeXUtils`, and the class instance is `rbtex`. The variables and methods are the same as those for Python (Section 3.2.6), except that there is not currently a `set_formatter()` method. (The Python utilities class has the special SymPy formatter, but there aren't yet any specialized formatters for Ruby.)

A family of commands and environments for Ruby is not created by default. Two base names are provided for families: `ruby` and `rb`. Preconfigured families for these names may be created via the `usefamily` package option. Keep in mind that a `ruby` command is defined as part of the Ruby package in the [CJK package](#). I am unaware of a package that provides an `\rb` command.

Ruby exceptions are synchronized with the document, but the line numbering does not always correspond to the Python equivalent. For example, suppose that `\pyc{1+}` is on line 10 of a document. The `SyntaxError` will then be synchronized with line 10. If `\rubyc{1+}` were on the same line, the resulting error would be synchronized with line 11. This is because Ruby allows addition to continue on subsequent lines of code, so an error is only raised when the next line of code that is executed does not contain a number (there is always template code after user code).

6.2 Julia

Support for Julia was added in v0.12. Julia support should be at almost the same level as that for Python. The format of Julia `stderr` is somewhat different from that of Python and Ruby. This required a modified parsing and synchronization algorithm. The current system is functional but will likely change somewhat in the future.

The utilities class is called `JuliaTeXUtils`, and the class instance is `jltex`. The variables and methods are the same as those for Python (Section 3.2.6), except that there is not currently a `set_formatter()` method. (The Python utilities class has the special SymPy formatter, but there aren't yet any specialized formatters for Julia.)

A family of commands and environments for Ruby is not created by default. Two base names are provided for families: `julia` and `j1`. Preconfigured families for these names may be created via the `usefamily` package option. Keep in mind that Pygments only added Julia support in version 1.6, so you may need to update your Pygments installation, or just change the default lexer.

Julia exceptions are synchronized with the document, but the line numbering does not always correspond to the Python equivalent. This is because Julia allows expressions to be continued on subsequent lines in ways that Python does not.

6.3 Adding support for a new language

Adding support for an additional language involves creating two templates, creating a new instance of a class, and using a `PythonTeX` macro. In some cases, additional changes may be necessary for full support. The information below

does not deal with creating `console` families; additional support for user-defined `console` families will be added in the future.

The system for adding languages should be relatively stable, but is subject to change as additional languages with additional requirements are added. The current system is sufficient for Python and similar languages. Languages with less regular `stderr` may require additional features and may not be able to have full synchronization between `stderr` and the L^AT_EX document. Keep in mind that if Python_TE_X is unable to classify exceptions as errors or warnings, it treats them as errors or warnings based on the script exit status.

It may be helpful to refer to `pythontex_engines.py`, specifically the templates and utilities classes, while reading the section below.

6.3.1 Template

Python_TE_X executes user code by inserting it in a script template. Replacement fields in the template are indicated by double curly braces: `{{field}}`. Space between `field` and the braces is allowed; `{{ field }}` is valid. Replacement fields (**including** the braces) should be surrounded by quotation marks or equivalent when the replacement is to be a string rather than literal code.

The template should perform the following tasks.

- Set the script encoding. The `{{encoding}}` field will be replaced with a user-specified encoding or the default UTF-8. If you are not using anything beyond ASCII, this is not strictly necessary.
- Python templates should have a `{{future}}` field at the beginning, for compatibility with Python 2 and the package option `pyfuture`.²⁷
- Set the `stdout` and `stderr` encoding, again using `{{encoding}}`. As before, this is not strictly necessary when only ASCII support is needed.
- Create a language-specific equivalent of the Python_TE_X utilities class.²⁸ Create an instance of this class. It is recommended that the class be called `<language name>TeXUtils` and the instance `<language extension>tex`, by analogy with the Python case.²⁹ When the `<language extension>` is only a single character or is shared by multiple languages, it may be better to

²⁷The beginning of user code is parsed for imports from `__future__`. Any imports are collected and inserted into the `{{future}}` field.

²⁸Python templates can import the Python_TE_X utilities class. In that case, `sys.path.append('{{utilspath}}')` is needed before the import, so that the location of the utilities class is known.

²⁹The class could be called `<language name>TeX`. In that case, the class and the instance would have the very same name (except for capitalization) in cases where the language name and extension are the same (for example, Lua). That is probably not desirable, and besides, `Utils` adds additional clarity. The instance name `<language extension>tex` is recommended because it will be short and easily remembered. Plain `tex` could be used instead, but that would be less descriptive (it lacks the interface connotations) and would not remind the user of the language currently in use (which could be beneficial in a document combining multiple languages, each with its own slightly different utilities class).

use the full *(language name)* or an abbreviation in the name of the class instance.

For full Python \TeX support, the utilities class should provide the following methods:

- `formatter()`: For formatting content for inline commands equivalent to `\py`. This should take a single argument of any type. By default, it should return a standard string representation of its argument.
- `before()` and `after()`: Initially, these should do nothing; they are provided to be redefined by the user. They should take no arguments.
- `add_dependencies()` and `add_created()`: These should accept an arbitrary number of comma-separated strings (if supported by the language). Each method should append its arguments to a list or equivalent data structure, for later use.
- `cleanup()`: This prints a dependencies delimiter string `{{dependencies_delim}}` to `stdout`, then prints all dependencies (one per line), then prints a created files delimiter string `{{created_delim}}`, then prints all created files (one per line). The delimiters should be printed even if there are no dependencies or created files. The delimiters contain no backslashes or quotes.

The utilities class should also provide several variables, as described below.

- Attempt to change to the working directory `{{workingdir}}`. Raise an error and exit if this is not possible. For convenience, the script should check for a `--manual` command line argument. If this argument is present, the script should proceed even if the working directory cannot be found. This allows the user to manually invoke the script for debugging (the script can be saved via `keeptemps`).

The working directory should be added to the module search path (Python `sys.path`, Ruby `$:` or `$LOAD_PATH`, etc.), unless it is the same as the document root directory or is otherwise already on the module search path.

- For full compatibility, the template should have an `{{extend}}` field where additional module imports or other code may be inserted. This allows a basic template to be created for each language. The basic template may then be customized for specific purposes. The `{{extend}}` field should be after the utilities class instance has been created, so that the workings of the utilities class (`formatter()`, `before()`, `after()`, etc.) may be customized by it.
- \LaTeX -related variables of the utilities class instance that do not change should be set. These use the fields `{{input_family}}`, `{{input_session}}`, and `{{input_restart}}`; all should be strings. These variables should be named after the fields if possible (for example, `pytex.input_family`). These variables are not strictly necessary, but they allow user code to access information about its \LaTeX context.

- There should be a `{{body}}` field where the body of the script is inserted.
- The script should end by calling the `cleanup()` method.

6.3.2 Wrapper

Each chunk of user code is inserted into a wrapper template. This performs the following tasks.

- Set additional L^AT_EX-related utilities variables: `{{input_command}}`, `{{input_context}}`, `{{input_args}}`, `{{input_instance}}`, `{{input_line}}`. All of these should be strings. They are not required, but make possible closer L^AT_EX integration. `{{input_context}}` and `{{input_args}}` are not yet supported on the L^AT_EX side, but will allow information about the L^AT_EX context (for example, page width) and arguments from L^AT_EX commands to be passed to user code.
- Write a delimiter `{{stdout_delim}}` to `stdout` and a delimiter `{{stderr_delim}}` to `stderr`. Both delimiters should be strings. Both should be written in such a way that the delimiter is followed by a newline; the delimiters that are inserted in the wrapper template **do not** contain a newline. For example, something like `"{{stderr_delim}}\n"` might be necessary. The delimiters contain no backslashes or quotation marks.
- Call `before()`.
- Have a `{{code}}` field into which the current chunk of user code is inserted.
- Call `after()`. For languages like Ruby that allow statements to continue onto subsequent lines, without enclosing parentheses or other delimiters, the call to `after()` should immediately follow user code, without any intervening empty lines. That way, any syntax errors from the last line of user code will be caught as early as possible, and the corresponding line numbers will be more meaningful.

6.3.3 The CodeEngine class

The final step in adding support for a language is creating a new instance of the `CodeEngine` class. The `CodeEngine` class manages the process of inserting user code into code templates and creates the records needed for synchronizing `stderr` with the document.

A new `CodeEngine` instance is initialized with the following arguments. All arguments are strings unless noted otherwise.

- The instance name. This will be the base name for commands and environments that use the instance. For example, `\py`, `\pyc`, `pycode`, etc., rely on the `py` instance of the `CodeEngine` class.
- The name of the language. In some cases, this may be the same as the instance name.

- The filename extension for scripts (with or without a period).
- The command for running scripts. The script that is executed should be referred to as “`{{file}}.<extension>`” (without the quotes).³⁰ The interpreter may be hardcoded (`python {{file}}.py`), but it is best to leave it as a substitution field (`{{python}} {{file}}.py`) so that the `--interpreter` command-line option can be used to provide a specific interpreter.
- The script template.
- The wrapper template.
- A template that specifies how code from commands like `\py` should be inserted into a call to the `formatter()` method. The user code is specified by `{{code}}`. The output of the `formatter()` method should be written to `stdout`, so something like `'print(pytex.formatter({{code}}))'` is needed.
- An optional list of strings (or an individual string) that gives patterns for identifying error messages.
- An optional list of strings (or an individual string) that gives patterns for identifying warning messages.
- An optional list of strings (or an individual string) that gives patterns for identifying code line numbers in `stderr`. These patterns use the field `{{number}}`. These patterns are searched for in any line of `stderr` that contains the name of the script that was executed.
- An optional boolean that specifies whether the engine emulates an interactive console. Currently, user-defined engines that emulate consoles are not supported.
- An optional string of startup commands for engines that emulate consoles.
- An optional list of strings (or an individual string) that specifies any files created during execution, beyond the script `{{file}}.<extension>`. The field `{{file}}` may be used in file names.

An example of creating the `py` engine is shown below. The `python_template` and `python_wrapper` are long enough that they are defined separately.

```
CodeEngine('py', 'python', '.py', 'python {{file}}.py',
           python_template, python_wrapper,
           'print(pytex.formatter({{code}}))',
           'Error:', 'Warning:', ['line {{number}}', ':{number}:'])
```

³⁰It might seem that the extension is redundant, since it is specified separately. The command is specified in this form to simplify cases where there may be intermediary files in the execution process.

The script template and wrapper templates may be defined with Python’s triple-quoted strings. All content within such a string may be indented for clarity, as can be seen in `pythontex_engines.py`. Strings are automatically dedented when `CodeEngine` instances are created.

In addition to the `CodeEngine` class, there is also a `SubCodeEngine` class. It allows a new engine to be created based on an existing engine. It requires the name of the engine from which to inherit and the name of the new engine. All of the other arguments listed above are optional; if any are provided, they overwrite the inherited arguments. The class also takes one additional optional argument, `extend`. This is a string that specifies additional code to be entered in the inherited template, in the `{\extend}` field. Subengines of subengines may be created; in that case, any `extends` are cumulative.

6.3.4 Creating the L^AT_EX interface

Once a new engine has been created, access from the L^AT_EX side must be provided. `PythonTEX` provides a macro for this purpose.

```
\makepythontexfamily[options]{engine}
```

This command creates a non-console family of commands and environments for *engine*: `code`, `block`, and `verbatim` commands and environments, and an inline command like `\py`.

This command is appropriate for user-defined languages, but it is preferable (and more convenient) to use the package option `usefamily` when using an engine that is included with `PythonTEX`. The package option will create a preconfigured family in which things such as the appropriate Pygments lexer have already been set.

options allows `prettyprinter`, `pyglexer`, and `pygopt` to be specified for the family.

7 Troubleshooting

- If a `PythonTEX` document will not compile, you may want to delete the directory in which `PythonTEX` content is stored and try compiling from scratch. It is possible for `PythonTEX` to become stuck in an unrecoverable loop. Suppose you tell Python to print some L^AT_EX code back to your L^AT_EX document, but make a fatal L^AT_EX syntax error in the printed content. This syntax error prevents L^AT_EX from compiling. Now suppose you realize what happened and correct the syntax error. The problem is that the corrected code cannot be executed until L^AT_EX correctly compiles and saves the code externally, but L^AT_EX cannot compile until the corrected code has already been executed. One solution in such cases is to correct the code, delete all files in the `PythonTEX` directory, compile the L^AT_EX document, and then run `PythonTEX` from scratch. You can also disable the inclusion of printed content using the `debug` package options.

- Dollar signs \$ may appear as £ in italic code comments typeset by Pygments. This is a font-related issue. One fix is to `\usepackage[T1]{fontenc}`.

8 The future of Python \TeX

This section consists of a To Do list for future development. The To Do list is primarily for the benefit of the author, but also gives users a sense of what changes are in progress or under consideration.

8.1 To Do

8.1.1 Modifications to make

- Add support for `depythontex` to remove the `\usepackage` for a package that contains Python \TeX commands and environments.
- Add better support for macro programming, including `depythontex` support for user-defined commands and environments.
- Add Pygments commands and environments that are compatible with basic `listings` and `minted` syntax. This will make it easier to work with documents converted to \LaTeX from another format, for example via Pandoc.
- User-defined custom commands and environments for general Pygments typesetting.
- Additional documentation for the Python code (Sphinx?).
- Improved testing framework.
- It might nice to include some methods in the Python \TeX utilities for formatting numbers (especially with SymPy and Pylab).
- Test the behavior of files brought in via `\input` and `\include` that contain Python \TeX content.
- Continue adding support for additional languages. In preparation: Julia. Under consideration: Perl, Lua, MATLAB, Mathematica, Sage, R, Octave.

8.1.2 Modifications to consider

- Consider fixing error line number synchronization with Beamer (and other situations involving error lines in externalized files). The `filehook` and `currfile` packages may be useful in this. One approach may be to patch the macros associated with `\beamer@doframeinput` in `beamerbaseframe.sty`. Note: Beamer's `fragile=singleslide` option makes this much less of an issue. This is low priority.

- Allow \LaTeX in code, and expand \LaTeX macros before passing code to `pythontex.py`. Maybe create an additional set of inline commands with additional `exp` suffix for `expanded`? This can already be done by creating a macro that contains a `PythonTeX` macro, though.
- Built-in support for background colors for blocks and verbatim, via `mdframed` or a similar package?
- Support for executing external scripts, not just internal code? It would be nice to be able to typeset an external file, as well as execute it by passing command-line arguments and then pull in its output.
- Is there any reason that saved printed content should be allowed to be brought in before the code that caused it has been typeset? Are there any cases in which the output should be typeset **before** the code that created it? That would require some type of external file for bringing in saved definitions.
- Consider some type of primitive line-breaking algorithm for use with Pygments. Could break at closest space, indent 8 spaces further than parent line (assuming 4-space indents; could auto-detect the correct size), and use \LaTeX counter commands to keep the line numbering from being incorrectly incremented. Such an approach might not be hard and might have some real promise.
- Consider allowing names of files into which scripts are saved to be specified. This could allow `PythonTeX` to be used for literate programming, general code documentation, etc. Also, it could allow writing a document that describes code and also produces the code files, for user modification (see the `bashful` package for the general idea). Doing something like this would probably require a new, slightly modified interface to preexisting macros.

Acknowledgements

Thanks to Nicholas Lu Chee Seng for help testing the earliest versions.

Thanks to Øystein Bjørndal for many suggestions and for help with OS X compatibility.

Version History

v0.12 (2013/08/26)

- Added support for the Julia language, with the `julia` and `j1` families of commands and environments. (Note that Pygments only added Julia support in version 1.6.)

- Warnings and errors are now synchronized with the line numbers of files brought in via `\input`, `\include`, etc. This is accomplished using the `currfile` package.
- Added package option `gobble`. When `gobble=auto`, all code is dedented before being executed and/or typeset. The current implementation is functional but basic; it will be improved and extended in the future.
- The document root directory is now always added to `sys.path` (or its equivalent), even when it is not the working directory. (The working directory has been added to `sys.path` since v0.12beta.) The document directory is added after the working directory, so that the working directory has precedence.
- Fixed a bug in `console` commands and environments; `sys.path` now contains the working and document directories, and the working directory is now the output directory by default. This parallels the behavior of non-`console` commands and environments.
- Added command-line option `--interpreter` that allows an interpreter to be invoked via a specific command. This allows, for example, a specific version of Python to be invoked.
- Improved synchronization of `stderr` in cases when an error is triggered far after its origin (for example, an error caused by a multiline string that is lacking a closing quote/delimiter, and thus may span several chunks of user code).
- Modified usage of the `shlex` module to work around its lack of Unicode support in Python versions prior to 2.7.3.
- Fixed a bug from v0.12beta that prevented `\inputpygments` from working when `pygments=true`.
- Fixed a bug with counters that caused errors when content spanning multiple columns was created within a `tabular` environment.
- Added checking for compatible Python versions in `pythontex.py`.
- Improved execution of `*.bat` and `*.cmd` files under Windows. The solution from v0.12beta allowed `*.bat` and `*.cmd` to be found and executed when the extension was not given, but did not give correct return codes.

v0.12beta (2013/06/24)

- Merged `pythontex_types*.py` into a single replacement `pythontex_engines.py` compatible with both Python 2 and 3. It is now much simpler to add support for additional languages.
- Added support for the Ruby language as a demonstration of new capabilities. The `ruby` and `rb` families of commands and environments may be enabled via the new `usefamily` package option. Support for

additional languages is coming soon. See the new section in the documentation on support for other languages for more information.

- Reimplemented treatment of Pygments content for better efficiency. Now a Pygments process only runs if there is content to highlight. Eliminated redundant highlighting of unmodified code.
- Improved treatment of dependencies. If a dependency is modified (`os.path.getmtime()`) after the current PythonTeX run starts, then code that depends on it will be re-executed the next time PythonTeX runs. A message is also issued to indicate that this is the case.
- The utilities class now has `before()` and `after()` methods that are called immediately before and after user code. These may be redefined to customize output. For example, LaTeX commands could be printed before and after user code; stdout could be redirected to `StringIO` for further processing; or matplotlib figures could be automatically detected, saved, and included in the document.
- Added explanation of how to track dependencies and created files automatically, and how to include matplotlib figures automatically, to the documentation for the PythonTeX utilities class.
- Created a new system for parsing and synchronizing stderr.
 - Exceptions that do not reference a line number in user code (such as those from `warnings.warn()` in a module) are now traced back to a single command or environment. Previously no synchronization was attempted. This is accomplished by writing delimiters to stderr before executing the code from each command/environment.
 - Exceptions that do reference a line in user code are more efficiently synchronized with a document line number. This is accomplished by careful record keeping as each script is assembled. Line number synchronization no longer involves parsing the script that was executed.
 - Improved and generalized parsing of stderr, in preparation for supporting additional languages. Exceptions that cannot be identified as errors or warnings are treated based on `Popen.returncode`.
- Created a new system for `console` content.
 - There are now separate families of `console` commands and environments. No Pygments or `fancyvrb` settings are shared with the non-`console` families, as was previously the case. There is a new family of commands and environments based on `pycon`, including the `\pycon` command (inline reference to console variable), `pyconsole` environment (same as the old one), `\pyconnc` and `pyconcode` (execute only), and `\pyconv` and `pyconverbatimim` (typeset only). There are equivalent families based on `pylabcon` and `sympycon`.
 - Each console session now runs in its own process and is cached individually. Console output is now cached so that changing Pygments settings no longer requires re-execution.

- Unicode is now supported under Python 2.
 - The new package option `pyconfuture` allows automatic imports from `__future__` for `console` families under Python 2, paralleling the `pyfuture` option.
 - Any errors or warnings caused by code that is not typeset (`code` command and environment, startup code) are reported in the run summary. This ensures that such code does not create mischief.
 - `customcode` is now supported for `console` content.
- Better support for `latexmk` and similar build tools. PythonTeX creates a file of macros (`*.pytxmcr`) that is always included in a document, and thus can be automatically detected and tracked by `latexmk`. This file now contains the time at which PythonTeX last created files. When new files are created, the macro file will have a new hash, triggering another document compile.
 - Improved the way in which the PythonTeX `outputdir` is added to the graphics path. This had been done with `\graphicspath`, but that overwrites any graphics path previously specified by the user. Now the `outputdir` is appended to any pre-existing path.
 - Added the `depythontex` option `--graphicspath`. This adds the `outputdir` to the graphics path of the `depythontex` document.
 - The installer now provides more options for installation locations. It will now create missing directories if desired.
 - The working directory (`workingdir`) is now appended to `sys.path`, so that code there may be imported.
 - Under Windows, `subprocess.Popen()` is now invoked with `shell=True` if `shell=False` results in a `WindowsError`. This allows commands involving `*.bat` and `*.cmd` files to be executed when the extension is not specified; otherwise, only `*.exe` can be found and run.
 - The path to `utils` is now found in `pythontex.py` via `sys.path[0]` rather than `kpsewhich`. This allows the PythonTeX scripts to be executed in an arbitrary location; they no longer must be installed in a `texmf` tree where `kpsewhich` can find them.
 - Added `rerun` value `never`.
 - At the end of each run, data and macros are only saved if modified, improving efficiency.
 - The number of temporary files required by each process was reduced by one. All macros for commands like `\py` are now returned within `stdout`, rather than in their own file.
 - Fixed a bug with `\stderrpythontex`; it was defaulting to `verb` rather than `verbatim` mode.

v0.11 (2013/04/21)

- As the first non-beta release, this version adds several features and introduces several changes. You should read these release notes carefully, since some changes are not backwards-compatible. Changes are based on a thorough review of all current and planned features. PythonTeX's capabilities have already grown beyond what was originally intended, and a long list of features still remains to be implemented. As a result, some changes are needed to ensure consistent syntax and naming in the future. Insofar as possible, all command names and syntax will be frozen after this release.
- Added the `pythontex.py` and `depythontex.py` wrapper scripts. When run, these detect the current version of Python and import the correct PythonTeX code. It is still possible to run `pythontex*.py` and `depythontex*.py` directly, but the new wrapper scripts should be used instead for simplicity. There is now only a single `pythontex_utils.py`, which works with both Python 2 and Python 3.
- Added the `beta` package option. This makes the current version behave like v0.11beta, for compatibility. This option is temporary and will probably only be retained for a few releases.
- Backward-incompatible changes (require the `beta` option to restore old behavior)
 - The `pyverb` environment has been renamed `pyverbatim`. The old name was intended to be concise, but promoted confusion with LaTeX's `\verb` macro.
 - For `\printpythontex`, `\stdoutpythontex`, and `\stderrpythontex`, the modes `inlineverb` and `v` have been replaced by `verb`, and the old mode `verb` has been replaced by `verbatim`. This brings naming conventions in line with standard LaTeX `\verb` and `verbatim`, avoiding a source of potential confusion.
 - The `\setpythontexpyglexer`, `\setpythontexpygopt`, and `\setpygmentspygopt` commands now take an optional argument and a mandatory argument, rather than two mandatory arguments. This creates better uniformity among current and planned settings macros.
 - The `\setpythontexformatter` and `\setpygmentsformatter` commands have been replaced by the `\setpythontexprettyprinter` and `\setpygmentsprettyprinter` commands. This anticipates possible upcoming features. It also avoids potential confusion with Pygments's formatters and the utilities class's `formatter()` method.
- Deprecated (still work, but raise warnings; after a few releases, they will raise errors instead, and after that eventually be removed)
 - The `rerun` setting `all` was renamed `always`, in preparation for upcoming features.

- The `stderr` option is replaced by `makestderr`. The `print/stdout` option is replaced by `debug`. These are intended to prevent confusion with future features.
- The `fixlr` option is deprecated. It was originally introduced to deal with some of SymPy’s LaTeX formatting, which has since changed.
- The utilities class method `init_sympy_latex()` is deprecated. The `sympy_latex()` and `set_sympy_latex()` methods now automatically initialize themselves on first use.
- Added `autostdout` package option and `\setpythontexautostdout`, to complement `autoprint`. Added `prettyprinter` and `prettyprintinline` package options to complement new settings commands.
- Added quickstart guide.
- Installer now installs gallery and quickstart files, if present.

v0.11beta (2013/02/17)

- Commands like `\py` can now bring in any valid LaTeX code, including verbatim content, under the pdfTeX and XeTeX engines. Verbatim content was not allowed previously. LuaTeX cannot bring in verbatim, due to a known bug.
- Added package option `depythontex` and scripts `depythontex*.py`. These allow a PythonTeX document to be converted into a pure LaTeX document, with no Python dependency. The package option creates an auxiliary file with extension `.depytx`. The `depythontex*.py` scripts take this auxiliary file and the original LaTeX document, and combine the two to produce a new document that does not rely on the PythonTeX package. All PythonTeX commands and environments are replaced by their output. All Python-generated content is substituted directly into the document. By default, all typeset code is wrapped in `\verb` and `verbatim`, but `depythontex*.py` has a `--listing` option that allows `fancyvrb`, `listings`, `minted`, or `pythontex` to be used instead.
- The current PythonTeX version is now saved in the `.pytxcode`. If this does not match the version of the PythonTeX scripts, a warning is issued. This makes it easier to determine errors due to version mismatches.
- Fixed an incompatibility with the latest release of `xstring` (version 1.7, 2013/01/13).
- Fixed a bug in the `console` environment that could cause problems when switching from Pygments highlighting to `fancyvrb` when using the `fvextfile` option. Fixed a bug introduced in the v0.10beta series that prevented the `console` environment from working with `fancyvrb`.

- Fixed a bug with PythonTeX verbatim commands and environments that use Pygments. The verbatim commands and environments were incorrectly treated as if they had the attributes of executed code in the v0.10beta series.
- Fixed a bug from the v0.10beta series that sometimes prevented imports from `__future__` from working when there were multiple sessions.
- Fixed a bug related to hashing dependencies' mtime under Python 3.

v0.10beta2 (2013/01/23)

- Improved `pythontex*.py`'s handling of the name of the file being processed. A warning is no longer raised if the name is given with an extension; extensions are now processed (stripped) automatically. The filename may now contain a path to the file, so you need not run `pythontex*.py` from within the document's directory.
- Added command-line option `--verbose` for more verbose output. Currently, this prints a list of all processes that are launched.
- Fixed a bug that could crash `pythontex*.py` when the package option `pygments=false`.
- Added documentation about `autoprint` behavior in the preamble. Summary: `code` commands and environments are allowed in the preamble as of v0.10beta. `autoprint` only applies to the body of the document, because nothing can be typeset in the preamble. Content printed in the preamble can be brought in by explicitly using `\printpythontex`, but this should be used with great care.
- Revised `\stdoutpythontex` and `\printpythontex` so that they work in the preamble. Again, this should be used with great care if at all.
- Revised treatment of any content that custom code attempts to print. Custom code is not allowed to print to the document (see documentation). If custom code attempts to print, a warning is raised, and the printed content is included in the `pythontex*.py` run summary.
- One-line entries in `stderr`, such as those produced by Python's `warnings.warn()`, were not previously parsed because they are of the form `:<linenumber>:` rather than `line <linenumber>`. These are now parsed and synchronized with the document. They are also correctly parsed for inclusion in the document via `\stderrpythontex`.
- If the package option `stderrfilename` is changed, all sessions that produced errors or warnings are now re-executed automatically, so that their `stderr` content is properly updated with the new filename.

v0.10beta (2013/01/09)

- Backward-incompatible: Redid treatment of command-line options for `pythontex*.py`, using Python's `argparse` module. Run `pythontex*.py` with option `-h` to see new command line options.

- **Deprecated:** `\setpythontexcustomecode` is deprecated in favor of the `\pythontexcustomecode` command and `pythontexcustomecode` environment. These allow entry of pure code, unlike `\setpythontexcustomecode`. These also allow custom code to be added to the beginning or end of a session, via an optional argument. Improved treatment of errors and warnings associated with custom code.
- The summary of errors and warnings now correctly differentiates errors and warnings produced by user code, rather than treating all of them as errors. By default, `pythontex*.py` now returns an exit code of 1 if there were errors.
- The PythonTeX utilities class now allows external file dependencies to be specified via `pytex.add_dependencies()`, so that sessions are automatically re-executed when external dependencies are modified (modification is determined via either hash or mtime; this is governed by the new `hashdependencies` option).
- The PythonTeX utilities class now allows created files to be specified via `pytex.add_created()`, so that created files may be automatically cleaned up (deleted) when the code that created them is modified (for example, name change for a saved plot).
- Added the following package options.
 - `stdout` (or `print`): Allows input of stdout to be disabled. Useful for debugging.
 - `runall`: Executes everything. Useful when code depends on external data.
 - `rerun`: Determines when code is re-executed. Code may be set to always run (same as `runall` option), or only run when it is modified or when it produces errors or warnings. By default, code is always re-executed if there are errors or modifications, but not re-executed if there are warnings.
 - `hashdependencies`: Determines whether external dependencies (data, external code files highlighted with Pygments, etc.) are checked for modification via hashing or modification time. Modification time is default for performance reasons.
- Added the following new command line options. The options that are equivalent to package options are overridden by the package options when present.
 - `--error-exit-code`: Determines whether an exit code of 1 is returned if there were errors. On by default, but can be turned off since it is undesirable when working with some editors.
 - `--runall`: Equivalent to new package option.
 - `--rerun`: Equivalent to new package option.
 - `--hashdependencies`: Equivalent to new package option.

- Modified the `fixlr` option, so that it only patches commands if they have not already been patched (avoids package conflicts).
- Added `\setpythontexautoprint` command for toggling `autoprint` on/off within the body of the document.
- Installer now attempts to create symlinks under OS X and Linux with TeX Live, and under OS X with MacPorts TeX Live.
- Performed compatibility testing under `lualatex` and `xelatex` (previously, had only tested with `pdflatex`). Added documentation for using these TeX engines; at most, slightly different preambles are needed. Modified the PythonTeX gallery to support all three engines.
- Code commands and environments may now be used in the preamble. This, combined with the new treatment of custom code, allows PythonTeX to be used in creating LaTeX packages.
- Added documentation for using PythonTeX in LaTeX programming.
- Fixed a bug that sometimes caused incorrect line numbers with `stderr` content. Improved processing of `stderr`.
- Fixed a bug in automatic detection of pre-existing listings environment.
- Improved the detection of imports from `__future__`. Detection should now be stricter, faster, and more accurate.

v0.9beta3 (2012/07/17)

- Added Unicode support, which required the Python code to be split into one set for Python 2 and another set for Python 3. This will require any old installation to be completely removed, and a new installation created from scratch.
- Refactoring of Python code. Documents should automatically re-execute all code after updating to the new version. Otherwise, you should delete the PythonTeX directory and run PythonTeX.
- Improved installation script.
- Added package options: `pyfuture`, `stderr`, `upquote`, `pyglexer`, `pyginline`. Renamed the `pygextfile` option to `fvextfile`.
- Added custom code and `workingdir` commands.
- Added the console environment and associated options.
- Rewrote `pythontex_utils*.py`, creating a new, context-aware interface to SymPy's `LatexPrinter` class.
- Content brought in via macros no longer uses labels. Rather, long defs are used, which allows line breaks.
- Pygments highlighting is now default for PythonTeX commands and environments

v0.9beta2 (2012/05/09)

- Changed Python output extension to `.stdout`.

v0.9beta (2012/04/27)

- Initial public beta release.

9 Implementation

This section describes the technical implementation of the package. Unless you wish to understand all the fine details or need to use the package in extremely sophisticated ways, you should not need to read it.

The prefix `pytx@` is used for all PythonTeX macros, to prevent conflict with other packages. Macros that simply store text or a value for later retrieval are given names completely in lower case. For example, `\pytx@packagename` stores the name of the package, `PythonTeX`. Macros that actually perform some operation in contrast to simple storage are named using CamelCase, with the first letter after the prefix being capitalized. For example, `\pytx@CheckCounter` checks to see if a counter exists, and if not, creates it. Thus, macros are divided into two categories based on their function, and named accordingly.

9.1 Package opening

We store the name of the package in a macro for later use in warnings and error messages.

```
1 \newcommand{\pytx@packagename}{PythonTeX}
2 \newcommand{\pytx@packageversion}{v0.12}
```

9.2 Required packages

A number of packages are required. `fancyvrb` is used to typeset all code that is not inline, and its internals are used to format inline code as well. `etex` provides extra registers, to avoid the (probably unlikely) possibility that the many counters required by PythonTeX will exhaust the supply. `etoolbox` is used for string comparison and boolean flags. `xstring` provides string manipulation. `pgfopts` is used to process package options, via the `pgfkeys` package. `newfloat` allows the creation of a floating environment for code listings. `currfile` is needed to allow errors and warnings to be synchronized with content brought in via `\input`, `\include`, etc. `xcolor` or `color` is needed for syntax highlighting with Pygments.

```
3 \RequirePackage{fancyvrb}
4 \RequirePackage{etex}
5 \RequirePackage{etoolbox}
6 \RequirePackage{xstring}
7 \RequirePackage{pgfopts}
8 \RequirePackage{newfloat}
9 \RequirePackage{currfile}
10 \AtBeginDocument{\@ifpackageloaded{color}{\RequirePackage{xcolor}}}
```

9.3 Package options

We now proceed to define package options, using the `pgfopts` package that provides a package-level interface to `pgfkeys`. All keys for package-level options are placed in the key tree under the path `/PYTX/pkgopt/`, to prevent conflicts with any other packages that may be using `pgfkeys`.

9.3.1 Enabling command and environment families

`\pytx@families` This option determines which command and environment families are defined beyond `py`, `pylab`, and `sympy`. Additional families are not automatically defined since some of them create commands or environment that may conflict with other packages.³¹

```
11 \def\pytx@families{}
12 \pgfkeys{/PYTX/pkgopt/usefamily/.estore in=\pytx@families}
```

9.3.2 Gobble

`\pytx@opt@gobble` This option determines how leading whitespace in user code is treated.

```
13 \def\pytx@opt@gobble{none}
14 \pgfkeys{/PYTX/pkgopt/gobble/.is choice}
15 \pgfkeys{/PYTX/pkgopt/gobble/none/.code=\def\pytx@opt@gobble{none}}
16 \pgfkeys{/PYTX/pkgopt/gobble/auto/.code=\def\pytx@opt@gobble{auto}}
```

9.3.3 Beta

`pytx@opt@beta` This option provides compatibility with the beta releases from before the full v0.11 release. It should be removed after a few major releases.

```
17 \newbool{pytx@opt@beta}
18 \pgfkeys{/PYTX/pkgopt/beta/.default=true}
19 \pgfkeys{/PYTX/pkgopt/beta/.is choice}
20 \pgfkeys{/PYTX/pkgopt/beta/true/.code=\booltrue{pytx@opt@beta}}
21 \pgfkeys{/PYTX/pkgopt/beta/false/.code=\boolfalse{pytx@opt@beta}}
```

9.3.4 Runall

`pytx@opt@rerun` This option causes all code to be executed, regardless of whether it has been modified. It is primarily useful for re-executing code that has not changed, when the code depends on external files that **have** changed. Since it shares functionality with the `rerun` option, both options share a single macro. Note that the macro is initially set to `default`, rather than the default value of `errors`, so that the Python side can distinguish whether a value was actually set by the user on the `TeX` side, and thus any potential conflicts between command-line options and package options can be resolved in favor of package options.

```
22 \def\pytx@opt@rerun{default}
```

³¹For example, a `\ruby` command for Ruby code, and the `\ruby` command defined by the Ruby package in the [CJK package](#).

```

23 \pgfkeys{/PYTX/pkgopt/runall/.default=true}
24 \pgfkeys{/PYTX/pkgopt/runall/.is choice}
25 \pgfkeys{/PYTX/pkgopt/runall/true/.code=\def\pytx@opt@rerun{always}}
26 \pgfkeys{/PYTX/pkgopt/runall/false/.code=\relax}

```

9.3.5 Rerun

This option determines the conditions under which code is rerun. It stores its state in a macro shared with `runall`.

```

27 \pgfkeys{/PYTX/pkgopt/rerun/.is choice}
28 \pgfkeys{/PYTX/pkgopt/rerun/never/.code=\def\pytx@opt@rerun{never}}
29 \pgfkeys{/PYTX/pkgopt/rerun/modified/.code=\def\pytx@opt@rerun{modified}}
30 \pgfkeys{/PYTX/pkgopt/rerun/errors/.code=\def\pytx@opt@rerun{errors}}
31 \pgfkeys{/PYTX/pkgopt/rerun/warnings/.code=\def\pytx@opt@rerun{warnings}}
32 \pgfkeys{/PYTX/pkgopt/rerun/always/.code=\def\pytx@opt@rerun{always}}
33 \pgfkeys{/PYTX/pkgopt/rerun/all/.code=\def\pytx@opt@rerun{always}}%
34 \PackageWarning{\pytx@packagename}{rerun=all is deprecated; use rerun=always}}

```

9.3.6 Hashdependencies

`pytx@opt@hashdependencies`

This option determines whether dependencies (either code to be highlighted, or dependencies such as data that have been specified within a session) are checked for modification via modification time or via hashing.

```

35 \def\pytx@opt@hashdependencies{default}
36 \pgfkeys{/PYTX/pkgopt/hashdependencies/.is choice}
37 \pgfkeys{/PYTX/pkgopt/hashdependencies/.default=true}
38 \pgfkeys{/PYTX/pkgopt/hashdependencies/true/.code=\def\pytx@opt@hashdependencies{true}}
39 \pgfkeys{/PYTX/pkgopt/hashdependencies/false/.code=\def\pytx@opt@hashdependencies{false}}

```

9.3.7 Autoprint

`pytx@opt@autoprint`

The `autoprint` option determines whether content printed within a code command or environment is automatically included at the location of the command or environment. If the option is not used, `autoprint` is turned on by default. If the option is used, but without a setting (`\usepackage[autoprint]{pythontex}`), it is true by default. We use the key handler `\key/<key>/.is choice` to ensure that only true/false values are allowed. The code for the true branch is redundant, but is included for symmetry.

```

40 \newbool{pytx@opt@autoprint}
41 \booltrue{pytx@opt@autoprint}
42 \pgfkeys{/PYTX/pkgopt/autoprint/.default=true}
43 \pgfkeys{/PYTX/pkgopt/autoprint/.is choice}
44 \pgfkeys{/PYTX/pkgopt/autoprint/true/.code=\booltrue{pytx@opt@autoprint}}
45 \pgfkeys{/PYTX/pkgopt/autoprint/false/.code=\boolfalse{pytx@opt@autoprint}}
46 \pgfkeys{/PYTX/pkgopt/autostdout/.default=true}
47 \pgfkeys{/PYTX/pkgopt/autostdout/.is choice}
48 \pgfkeys{/PYTX/pkgopt/autostdout/true/.code=\booltrue{pytx@opt@autoprint}}
49 \pgfkeys{/PYTX/pkgopt/autostdout/false/.code=\boolfalse{pytx@opt@autoprint}}

```

`\setpythontexautoprint` Sometimes it may be useful to switch `autoprint` on and off within different parts of a document, rather than setting it to a single setting for the entire document. So we provide a command for that purpose. Note that the command overrides the package-level option.

```

50 \newcommand{\setpythontexautoprint}[1]{%
51   \Depythontex{cmd:setpythontexautoprint:m:n}%
52   \ifstrequal{#1}{true}{\booltrue{pytx@opt@autoprint}}{}%
53   \ifstrequal{#1}{false}{\boolfalse{pytx@opt@autoprint}}{}%
54 }
55 \newcommand{\setpythontexautostdout}[1]{%
56   \Depythontex{cmd:setpythontexautostdout:m:n}%
57   \ifstrequal{#1}{true}{\booltrue{pytx@opt@autoprint}}{}%
58   \ifstrequal{#1}{false}{\boolfalse{pytx@opt@autoprint}}{}%
59 }

```

9.3.8 Debug

`pytx@opt@stdout` This option determines whether printed content/content written to `stdout` is included in the document. Disabling the inclusion of printed content is useful when the printed content contains \LaTeX errors that would prevent successful compilation.

```

60 \newbool{pytx@opt@stdout}
61 \booltrue{pytx@opt@stdout}
62 \pgfkeys{/PYTX/pkgopt/debug/.code=\boolfalse{pytx@opt@stdout}}
63 \pgfkeys{/PYTX/pkgopt/stdout/.default=true}
64 \pgfkeys{/PYTX/pkgopt/stdout/.is choice}
65 \pgfkeys{/PYTX/pkgopt/stdout/true/.code=\booltrue{pytx@opt@stdout}}%
66   \PackageWarning{\pytx@packagename}{Option stdout is deprecated; use option debug}}
67 \pgfkeys{/PYTX/pkgopt/stdout/false/.code=\boolfalse{pytx@opt@stdout}}%
68   \PackageWarning{\pytx@packagename}{Option stdout is deprecated; use option debug}}
69 \pgfkeys{/PYTX/pkgopt/print/.default=true}
70 \pgfkeys{/PYTX/pkgopt/print/.is choice}
71 \pgfkeys{/PYTX/pkgopt/print/true/.code=\booltrue{pytx@opt@stdout}}%
72   \PackageWarning{\pytx@packagename}{Option print is deprecated; use option debug}}
73 \pgfkeys{/PYTX/pkgopt/print/false/.code=\boolfalse{pytx@opt@stdout}}%
74   \PackageWarning{\pytx@packagename}{Option print is deprecated; use option debug}}
75 \AtBeginDocument{%
76   \ifbool{pytx@opt@stdout}{}{%
77     \PackageWarning{\pytx@packagename}{Using package option debug}}%
78   }%
79 }

```

9.3.9 makestderr

`pytx@opt@stderr` The `makestderr` option determines whether `stderr` is saved and may be included in the document via `\stderrpythontex`.

```

80 \newbool{pytx@opt@stderr}
81 \pgfkeys{/PYTX/pkgopt/makestderr/.default=true}

```

```

82 \pgfkeys{/PYTX/pkgopt/makestderr/.is choice}
83 \pgfkeys{/PYTX/pkgopt/makestderr/true/.code=\booltrue{pytx@opt@stderr}}
84 \pgfkeys{/PYTX/pkgopt/makestderr/false/.code=\boolfalse{pytx@opt@stderr}}
85 \pgfkeys{/PYTX/pkgopt/stderr/.default=true}
86 \pgfkeys{/PYTX/pkgopt/stderr/.is choice}
87 \pgfkeys{/PYTX/pkgopt/stderr/true/.code=\booltrue{pytx@opt@stderr}}%
88   \PackageWarning{\pytx@packagename}{Option stderr is deprecated; use option makestderr}}
89 \pgfkeys{/PYTX/pkgopt/stderr/false/.code=\boolfalse{pytx@opt@stderr}}%
90   \PackageWarning{\pytx@packagename}{Option stderr is deprecated; use option makestderr}}

```

9.3.10 stderrfilename

`\pytx@opt@stderrfilename` This option determines how the file name appears in `stderr`.

```

91 \def\pytx@opt@stderrfilename{full}
92 \pgfkeys{/PYTX/pkgopt/stderrfilename/.default=full}
93 \pgfkeys{/PYTX/pkgopt/stderrfilename/.is choice}
94 \pgfkeys{/PYTX/pkgopt/stderrfilename/full/.code=\def\pytx@opt@stderrfilename{full}}
95 \pgfkeys{/PYTX/pkgopt/stderrfilename/session/.code=\def\pytx@opt@stderrfilename{session}}
96 \pgfkeys{/PYTX/pkgopt/stderrfilename/genericfile/.code=%
97   \def\pytx@opt@stderrfilename{genericfile}}
98 \pgfkeys{/PYTX/pkgopt/stderrfilename/genericscript/.code=%
99   \def\pytx@opt@stderrfilename{genericscript}}

```

9.3.11 Python's `__future__` module

`\pytx@opt@pyfuture` The `pyfuture` option determines what is imported from the `__future__` module under Python 2. It has no effect under Python 3.

```

100 \def\pytx@opt@pyfuture{default}
101 \pgfkeys{/PYTX/pkgopt/pyfuture/.is choice}
102 \pgfkeys{/PYTX/pkgopt/pyfuture/default/.code=\def\pytx@opt@pyfuture{default}}
103 \pgfkeys{/PYTX/pkgopt/pyfuture/all/.code=\def\pytx@opt@pyfuture{all}}
104 \pgfkeys{/PYTX/pkgopt/pyfuture/none/.code=\def\pytx@opt@pyfuture{none}}

```

`\pytx@opt@pyconfuture` The `pyconfuture` option determines what is automatically imported from the `__future__` module under Python 2, for console content. It has no effect under Python 3.

```

105 \def\pytx@opt@pyconfuture{none}
106 \pgfkeys{/PYTX/pkgopt/pyconfuture/.is choice}
107 \pgfkeys{/PYTX/pkgopt/pyconfuture/default/.code=\def\pytx@opt@pyconfuture{default}}
108 \pgfkeys{/PYTX/pkgopt/pyconfuture/all/.code=\def\pytx@opt@pyconfuture{all}}
109 \pgfkeys{/PYTX/pkgopt/pyconfuture/none/.code=\def\pytx@opt@pyconfuture{none}}

```

9.3.12 Upquote

`pytx@opt@upquote` The `upquote` option determines whether the `upquote` package is loaded. It makes quotes within verbatim contexts `'` rather than `'`. This is important, because it means that code may be copied directly from the compiled PDF and executed without any errors due to quotes `'` being copied as acute accents `´`.

```

110 \newbool{pytx@opt@upquote}
111 \booltrue{pytx@opt@upquote}
112 \pgfkeys{/PYTX/pkgopt/upquote/.default=true}
113 \pgfkeys{/PYTX/pkgopt/upquote/.is choice}
114 \pgfkeys{/PYTX/pkgopt/upquote/true/.code=\booltrue{pytx@opt@upquote}}
115 \pgfkeys{/PYTX/pkgopt/upquote/false/.code=\boolfalse{pytx@opt@upquote}}

```

9.3.13 Fix math spacing

`pytx@opt@fixlr` The `fixlr` option fixes extra, undesirable spacing in mathematical formulae introduced by the commands `\left` and `\right`. For example, compare the results of `\sin(x)` and `\sin\left(x\right)`: $\sin(x)$ and $\sin(x)$. The `fixlr` option fixes this, using a solution proposed by Mateus Araújo, Philipp Stephani, and Heiko Oberdiek.³²

```

116 \newbool{pytx@opt@fixlr}
117 \pgfkeys{/PYTX/pkgopt/fixlr/.default=true}
118 \pgfkeys{/PYTX/pkgopt/fixlr/.is choice}
119 \pgfkeys{/PYTX/pkgopt/fixlr/true/.code=\booltrue{pytx@opt@fixlr}}
120 \pgfkeys{/PYTX/pkgopt/fixlr/false/.code=\boolfalse{pytx@opt@fixlr}}

```

9.3.14 Keep temporary files

`\pytx@opt@keeptemps` By default, Python_T_EX tries to be very tidy. It creates many temporary files, but deletes all that are not required to compile the document, keeping the overall file count very low. At times, particularly during debugging, it may be useful to keep these temporary files, so that code, errors, and output may be examined more directly. The `keeptemps` option makes this possible.

```

121 \def\pytx@opt@keeptemps{none}
122 \pgfkeys{/PYTX/pkgopt/keeptemps/.default=all}
123 \pgfkeys{/PYTX/pkgopt/keeptemps/.is choice}
124 \pgfkeys{/PYTX/pkgopt/keeptemps/all/.code=\def\pytx@opt@keeptemps{all}}
125 \pgfkeys{/PYTX/pkgopt/keeptemps/code/.code=\def\pytx@opt@keeptemps{code}}
126 \pgfkeys{/PYTX/pkgopt/keeptemps/none/.code=\def\pytx@opt@keeptemps{none}}

```

9.3.15 Pygments

`pytx@opt@pygments` By default, Python_T_EX uses `fancyvrb` to typeset code. This provides nice formatting and font options, but no syntax highlighting. The `prettyprinter` options, and `pygments` alias, determine whether Pygments or `fancyvrb` is used to typeset code. Pygments is a generic syntax highlighter written in Python. Since Python_T_EX sends code to Python anyway, having Pygments process the code is only a small additional step and in many cases takes little if any extra time to execute.³³

³² <http://tex.stackexchange.com/questions/2607/spacing-around-left-and-right>

³³Pygments code highlighting is executed as a separate process by `pythontex.py`, so it runs in parallel on a multicore system. Pygments usage is optimized by saving highlighted code and only reprocessing it when changed.

Command and environment families obey the `prettyprinter` option by default, but they may be set to override it and always use Pygments or always use `fancyvrb`, via `\setpythontexprettyprinter` and `\setpygmentsprettyprinter`.

```

127 \newbool{pytx@opt@pygments}
128 \booltrue{pytx@opt@pygments}
129 \pgfkeys{/PYTX/pkgopt/prettyprinter/.is choice}
130 \pgfkeys{/PYTX/pkgopt/prettyprinter/pygments/.code=\booltrue{pytx@opt@pygments}}
131 \pgfkeys{/PYTX/pkgopt/prettyprinter/fancyvrb/.code=\boolfalse{pytx@opt@pygments}}
132 \pgfkeys{/PYTX/pkgopt/pygments/.default=true}
133 \pgfkeys{/PYTX/pkgopt/pygments/.is choice}
134 \pgfkeys{/PYTX/pkgopt/pygments/true/.code=\booltrue{pytx@opt@pygments}}
135 \pgfkeys{/PYTX/pkgopt/pygments/false/.code=\boolfalse{pytx@opt@pygments}}

```

`pytx@opt@pyginline` This option governs whether, when Pygments is in use, it highlights inline content.

```

136 \newbool{pytx@opt@pyginline}
137 \booltrue{pytx@opt@pyginline}
138 \pgfkeys{/PYTX/pkgopt/prettyprintinline/.default=true}
139 \pgfkeys{/PYTX/pkgopt/prettyprintinline/.is choice}
140 \pgfkeys{/PYTX/pkgopt/prettyprintinline/true/.code=\booltrue{pytx@opt@pyginline}}
141 \pgfkeys{/PYTX/pkgopt/prettyprintinline/false/.code=\boolfalse{pytx@opt@pyginline}}
142 \pgfkeys{/PYTX/pkgopt/pyginline/.default=true}
143 \pgfkeys{/PYTX/pkgopt/pyginline/.is choice}
144 \pgfkeys{/PYTX/pkgopt/pyginline/true/.code=\booltrue{pytx@opt@pyginline}}
145 \pgfkeys{/PYTX/pkgopt/pyginline/false/.code=\boolfalse{pytx@opt@pyginline}}

```

`pytx@pyglexer` For completeness, we need a way to set the Pygments lexer for all content. Note that in general, resetting the lexers for all content is not desirable.

```

146 \def\pytx@pyglexer{}
147 \pgfkeys{/PYTX/pkgopt/pyglexer/.code=\def\pytx@pyglexer{#1}}

```

`\pytx@pygopt` We also need a way to specify Pygments options at the package level. This is accomplished via the `pygopt` option: `pygopt={\langle options \rangle}`. Note that the options must be enclosed in curly braces since they contain equals signs and thus must be distinguishable from package options.

Currently, three options may be passed in this manner: `style=\langle style \rangle`, which sets the formatting style; `texcomments`, which allows \LaTeX in code comments to be rendered; and `mathescape`, which allows \LaTeX math mode ($\$...\$$) in comments. The `texcomments` and `mathescape` options may be used with a boolean argument; if an argument is not supplied, true is assumed. As an example of `pygopt` usage, consider the following:

```
pygopt={style=colorful, texcomments=True, mathescape=False}
```

The usage of capitalized `True` and `False` is more pythonic, but is not strictly require.

While the package-level `pygments` option may be overridden by individual commands and environments (though it is not by default), the package-level Pygments options cannot be overridden by individual commands and environments.

```

148 \def\pytx@pygopt{}
149 \pgfkeys{/PYTX/pkgopt/pygopt/.code=\def\pytx@pygopt{#1}}

```

`\pytx@fvextfile` By default, code highlighted by Pygments, the `console` environment, and some other content is brought back via `fancyvrb`'s `SaveVerbatim` macro, which saves verbatim content into a macro and then allows it to be restored. This makes it possible for all Pygments content to be brought back in a single file, keeping the total file count low (which is a major priority for Python_T_E_X!). This approach does have a disadvantage, though, because `SaveVerbatim` slows down as the length of saved code increases.³⁴ To deal with this issue, we create the `fvextfile` option. This option takes an integer, `fvextfile=<integer>`. All content that is more than `<integer>` lines long will be saved to its own external file and inputted from there, rather than saved and restored via `SaveVerbatim` and `UseVerbatim`. This provides a workaround should speed ever become a hindrance for large blocks of code.

A default value of 25 is set. There is nothing special about 25; it is just a relatively reasonable cutoff. If the option is unused, it has a value of `-1`, which is converted to the maximum integer on the Python side.

```

150 \def\pytx@fvextfile{-1}
151 \pgfkeys{/PYTX/pkgopt/fvextfile/.default=25}
152 \pgfkeys{/PYTX/pkgopt/fvextfile/.code=\IfInteger{#1}{%
153   \ifnum#1>0\relax
154     \def\pytx@fvextfile{#1}%
155   \else
156     \PackageError{\pytx@packagename}{option fvextfile must be an integer > 0}{}%
157   \fi}%
158 {\PackageError{\pytx@packagename}{option fvextfile must be an integer > 0}{}}%
159 }

```

9.3.16 Python console environment

`\pytx@opt@pyconbanner` This option governs the appearance (or disappearance) of a banner at the beginning of Python console environments. The options `none` (no banner), `standard` (standard Python banner), `default` (default banner for Python's code module, standard banner plus interactive console class name), and `pyversion` (banner in the form `Python x.y.z`) are accepted.

```

160 \def\pytx@opt@pyconbanner{none}
161 \pgfkeys{/PYTX/pkgopt/pyconbanner/.is choice}
162 \pgfkeys{/PYTX/pkgopt/pyconbanner/none/.code=\def\pytx@opt@pyconbanner{none}}
163 \pgfkeys{/PYTX/pkgopt/pyconbanner/standard/.code=\def\pytx@opt@pyconbanner{standard}}
164 \pgfkeys{/PYTX/pkgopt/pyconbanner/default/.code=\def\pytx@opt@pyconbanner{default}}
165 \pgfkeys{/PYTX/pkgopt/pyconbanner/pyversion/.code=\def\pytx@opt@pyconbanner{pyversion}}

```

`\pytx@opt@pyconfilename` This option governs the file name that appears in error messages in the console. The file name may be either `stdin`, as it is in a standard interactive interpreter,

³⁴The macro in which code is saved is created by grabbing the code one line at a time, and for each line redefining the macro to be its old value with the additional line tacked on. This is rather inefficient, but apparently there isn't a good alternative.

or `console`, as it would typically be for the Python code module.

```
Traceback (most recent call last):
  File "<file name>", line <line no>, in <module>
```

```
166 \def\pytx@opt@pyconfilename{stdin}
167 \pgfkeys{/PYTX/pkgopt/pyconfilename/.is choice}
168 \pgfkeys{/PYTX/pkgopt/pyconfilename/stdin/.code=\def\pytx@opt@pyconfilename{stdin}}
169 \pgfkeys{/PYTX/pkgopt/pyconfilename/console/.code=\def\pytx@opt@pyconfilename{console}}
```

9.3.17 `depythontex`

`pytx@opt@depythontex` This option governs whether Python_TE_X saved data that can be used to create a version of the `.tex` file that does not require Python_TE_X to be compiled. This option should be useful for converting a Python_TE_X document into a more standard _TE_X document when sharing or publishing documents.

While we're at it, we go ahead and define dummy versions of the `depythontex` macros, so that they can be used in defining commands that are used within the package, not just outside of it.

```
170 \newbool{pytx@opt@depythontex}
171 \pgfkeys{/PYTX/pkgopt/depythontex/.default=true}
172 \pgfkeys{/PYTX/pkgopt/depythontex/.is choice}
173 \pgfkeys{/PYTX/pkgopt/depythontex/true/.code=\booltrue{pytx@opt@depythontex}}
174 \pgfkeys{/PYTX/pkgopt/depythontex/false/.code=\boolfalse{pytx@opt@depythontex}}
175 \let\Depythontex@gobble
176 \let\DepyFile@gobble
177 \let\DepyMacro@gobble
178 \let\DepyListing@empty
```

9.3.18 Process options

Now we process the package options.

```
179 \ProcessPgfPackageOptions{/PYTX/pkgopt}
```

The `fixlr` option only affects one thing, so we go ahead and take care of that. Notice that before we patch `\left` and `\right`, we make sure that they have not already been patched by checking how `\left` is expanded. This is important if the user has manually patched these commands, is using the `mleftright` package, or accidentally loads Python_TE_X twice.

```
180 \ifbool{pytx@opt@fixlr}{
181   \IfStrEq{\detokenize\expandafter{\left}}{\detokenize{\left}}{
182     \let\originalleft\left
183     \let\originalright\right
184     \renewcommand{\left}{\mathopen{}\mathclose\bgroup\originalleft}
185     \renewcommand{\right}{\aftergroup\egroup\originalright}
186   }{}
187 }
```

Likewise, the `upquote` option.

```
188 \ifbool{pytx@opt@upquote}{\RequirePackage{upquote}}{}
```

If the `depythontex` option is used, we also need to disable Pygments highlighting. This is necessary because some content, such as `console` environments, is needed in a non-highlighted form, so that it will not contain any special macros.

```
189 \ifbool{pytx@opt@depythontex}{\boolfalse{pytx@opt@pygments}}{}
```

9.4 Utility macros and input/output setup

Once options are processed, we proceed to define a number of utility macros and setup the file input/output that is required by Python \TeX . We also create macros and perform setup needed by `depythontex`, since these are closely related to input/output.

9.4.1 Automatic counter creation

`\pytx@CheckCounter` We will be using counters to give each command/environment a unique identifier, as well as to manage line numbering of code when desired. We don't know the names of the counters ahead of time (this is actually determined by the user's naming of code sessions), so we need a macro that checks whether a counter exists, and if not, creates it.

```
190 \def\pytx@CheckCounter#1{%  
191   \ifcsname c@#1\endcsname\else\newcounter{#1}\fi  
192 }
```

9.4.2 Saving verbatim content in macros

`\pytx@SVMCR` Commands like `\py` bring in string representations of objects. Printed content is saved to external files, but commands like `\py` bring in content by saving it in macros. A single large file of macro definitions is brought in, rather than many external files.

This prevents the creation of unnecessary files, but it also has a significant drawback: only some content can be saved in a standard macro. In particular, verbatim content using `\verb` and `verbatim` will not work. So we need a way to save anything in a macro. The solution is to create a special macro that captures its argument verbatim. The argument is then tokenized when it is used via `\scantokens`. All of this requires a certain amount of catcode trickery.

While this approach works with the Xe \TeX and pdf \TeX engines, it does not work with the Lua \TeX engine, which has a known bug in its implementation of `\scantokens`.³⁵ So we provide a separate version for Lua \TeX that does not support verbatim. The space after the `#1` is intentional, so that the newline at the beginning of the macro definition is gobbled, and the macro content will start with text rather than leading whitespace.

```
193 \def\pytx@SVMCR#1{%
```

³⁵<http://tracker.luatex.org/view.php?id=733>

```

194 \edef\pytx@tmp{\csname #1\endcsname}%
195 \begingroup
196 \endlinechar\^^J
197 \let\do\@makeother\dospecials
198 \pytx@SVMCR@i}
199 \begingroup
200 \catcode'\!=0
201 !catcode'\=12
202 !long!gdef!pytx@SVMCR@i#1\endpytx@SVMCR^^J{%
203 !endgroup
204 !expandafter!gdef!pytx@tmp{%
205 !expandafter!scantokens!expandafter{#1!empty}}}%
206 }%
207 !endgroup
208 \expandafter\ifx\csname directlua\endcsname\relax\else
209 \def\pytx@SVMCR#1 {%
210 \edef\pytx@tmp{\csname #1\endcsname}%
211 \pytx@SVMCR@i}
212 \long\def\pytx@SVMCR@i#1\endpytx@SVMCR{%
213 \expandafter\gdef\pytx@tmp{#1}%
214 }
215 \fi

```

9.4.3 Code context

```

\pytx@context
\pytx@SetContext
\definepythontexcontext

```

It would be nice if when our code is executed, we could know something about its context, such as the style of its surroundings or information about page size.

By default, no contextual information is passed to L^AT_EX. There is a wide variety of information that could be passed, but most use cases would only need a very specific subset. Instead, the user can customize what information is passed to L^AT_EX. The `\definepythontexcontext` macro defines what is passed. It creates the `\pytx@SetContext` macro, which creates `\pytx@context`, in which the expanded context information is stored. The context should only be defined in the preamble, so that it is consistent throughout the document.

If you are interested in typesetting mathematics based on math styles, you should use the `\mathchoice` macro rather than attempting to pass contextual information.

```

216 \newcommand{\definepythontexcontext}[1]{%
217 \def\pytx@SetContext{%
218 \edef\pytx@context{#1}%
219 }%
220 }
221 \definepythontexcontext{}
222 \@onlypreamble\definepythontexcontext

```

9.4.4 Code groups

By default, Python_{TEX} executes code based on sessions. All of the code entered within a command and environment family is divided based on sessions, and each session is saved to a single external file and executed. If you have a calculation that will take a while, you can simply give it its own named session, and then the code will only be executed when there is a change within that session.

While this approach is appropriate for many scenarios, it is sometimes inefficient. For example, suppose you are writing a document with multiple chapters, and each chapter needs its own session. You could manually do this, but that would involve a lot of commands like `\py[chapter x]{some code}`, which means lots of extra typing and extra session names. So we need a way to subdivide or restart sessions, based on context such as chapter, section, or subsection.

“Groups” provide a solution to this problem. Each session is subdivided based on groups behind the scenes. By default, this changes nothing, because each session is put into a single default group. But the user can redefine groups based on chapter, section, and other counters, so that sessions are automatically subdivided accordingly. Note that there is no continuity between sessions thus subdivided. For example, if you set groups to change between chapters, there will be no continuity between the code of those chapters, even if all the code is within the same named session. If you require continuity, the groups approach is probably not appropriate. You could consider saving results at the end of one chapter and loading them at the beginning of the next, but that introduces additional issues in keeping all code properly synchronized, since code is executed only when it changes, not when any data it loads may have changed.

`\restartpythontexsession` We begin by creating the `\restartpythontexsession` macro. It creates the
`\pytx@group` `\pytx@SetGroup*` macros, which create `\pytx@group`, in which the expanded
`\pytx@SetGroup` context information is stored. The context should only be defined in the
`\pytx@SetGroupVerb` preamble, so that it is consistent throughout the document. Note that groups
`\pytx@SetGroupCons` should be defined so that they will only contain characters that are valid in
file names, because groups are used in naming temporary files. It is also a
good idea to avoid using periods, since L^AT_EX input of file names containing
multiple periods can sometimes be tricky. For best results, use A-Z, a-z, 0-9,
and the hyphen and underscore characters to define groups. If groups contain
numbers from multiple sources (for example, chapter and section), the num-
bers should be separated by a non-numeric character to prevent unexpected
collisions (for example, distinguishing chapter 1-11 from 11-1). For example,
`\restartpythontexsession{\arabic{chapter}-\arabic{section}}` could be a
good approach.

Three forms of `\pytx@SetGroup*` are provided. `\pytx@SetGroup` is for general code use. `\pytx@SetGroupVerb` is for use in verbatim contexts. It splits verbatim content off into its own group. That way, verbatim content does not affect the instance numbers of code that is actually executed. This prevents code from needing to be run every time verbatim content is added or removed; code is only executed when it is actually changed. `pytx@SetGroupCons` is for console environments. It

separate console content from executed code and from verbatim content, again for efficiency reasons.

```

223 \newcommand{\restartpythontexsession}[1]{%
224   \Depyhtontex{cmd:restartpythontexsession:m:n}%
225   \def\pytx@SetGroup{%
226     \edef\pytx@group{#1}%
227   }%
228   \def\pytx@SetGroupVerb{%
229     \edef\pytx@group{#1verb}%
230   }%
231   \def\pytx@SetGroupCons{%
232     \edef\pytx@group{#1cons}%
233   }%
234   \AtBeginDocument{%
235     \pytx@SetGroup
236     \IfSubStr{\pytx@group}{verb}{%
237       \PackageError{\pytx@packagename}%
238         {String "verb" is not allowed in \string\restartpythontexsession}%
239         {Use \string\restartpythontexsession with a valid argument}}{}%
240     \IfSubStr{\pytx@group}{cons}{%
241       \PackageError{\pytx@packagename}%
242         {String "cons" is not allowed in \string\restartpythontexsession}%
243         {Use \string\restartpythontexsession with a valid argument}}{}%
244   }%
245 }

```

For the sake of consistency, we only allow group behaviour to be set in the preamble. And if the group is not set by the user, then we use a single default group for each session.

```

246 \@onlypreamble\restartpythontexsession
247 \restartpythontexsession{default}

```

9.4.5 File input and output

`\pytx@jobname` We will need to create directories and files for Python_{TEX} output, and some of these will need to be named using `\jobname`. This presents a problem. Ideally, the user will choose a job name that does not contain spaces. But if the job name does contain spaces, then we may have problems bringing in content from a directory or file that is named based on the job, due to the space characters. So we need a “sanitized” version of `\jobname`. We replace spaces with hyphens. We replace double quotes " with nothing. Double quotes are placed around job names containing spaces by _{TEX} Live, and thus may be the first and last characters of `\jobname`. Since we are replacing any spaces with hyphens, quote delimiting is no longer needed, and in any case, some operating systems (Windows) balk at creating directories or files with names containing double quotes. We also replace asterisks with hyphens, since _{MiK}TEX (at least v. 2.9) apparently replaces spaces

with asterisks in `\jobname`,³⁶ and some operating systems may not be happy with names containing asterisks.

This approach to “sanitizing” `\jobname` is not foolproof. If there are ever two files in a directory that both use Python_TE_X, and if their names only differ by these substitutions for spaces, quotes, and asterisks, then the output of the two files will collide. We believe that it is better to graciously handle the possibility of space characters at the expense of nearly identical file names, since nearly identical file names are arguably a much worse practice than file names containing spaces, and since such nearly identical file names should be much rarer. At the same time, in rare cases a collision might occur, and in even rarer cases it might go unnoticed.³⁷ To prevent such issues, `pythontex.py` checks for collisions and issues a warning if a potential collision is detected.

```
248 \StrSubstitute{\jobname}{ }{-}[\pytx@jobname]
249 \StrSubstitute{\pytx@jobname}{"}{-}[\pytx@jobname]
250 \StrSubstitute{\pytx@jobname}{*}{-}[\pytx@jobname]
```

`\pytx@outputdir` To keep things tidy, all Python_TE_X files are stored in a directory that is
`\setpythontexoutputdir` created in the document root directory. By default, this directory is called `pythontex-files-{sanitized jobname}`, but we want to provide the user with the option to customize this. For example, when *{sanitized jobname}* is very long, it might be convenient to use `pythontex-{abbreviated name}`.

The command `\setpythontexoutputdir` stores the name of Python_TE_X’s output directory in `\pytx@outputdir`. If the `graphicx` package is loaded, the output directory is also added to the graphics path at the beginning of the document, so that files in the output directory may be included within the main document without the necessity of specifying path information. The command `\setpythontexoutputdir` is only allowed in the preamble, because the location of Python_TE_X content should be specified before the body of the document is typeset.

```
251 \newcommand{\setpythontexoutputdir}[1]{%
252   \Depythontex{cmd:setpythontexoutputdir:m:n}%
253   \def\pytx@outputdir{#1}}
254 \setpythontexoutputdir{pythontex-files-\pytx@jobname}
255 \AtBeginDocument{%
256   \@ifpackageloaded{graphicx}{%
257     \ifx\Ginput@path\undefined
258       \graphicspath{{\pytx@outputdir/}}%
259     \else
260       \g@addto@macro\Ginput@path{{\pytx@outputdir/}}%
261     \fi
262   }{}}%
```

³⁶<http://tex.stackexchange.com/questions/14949/why-does-jobname-give-s-instead-of-spaces-and-how-do-i-fix-this>

³⁷In general, a collision would produce errors, and the user would thereby become aware of the collision. The dangerous case is when the two files with similar names use exactly the same Python_TE_X commands, the same number of times, so that the naming of the output is identical. In that case, no errors would be issued.

```

263 }
264 \@onlypreamble\setpythontexoutputdir

```

`pytx@workingdir` We need to be able to set the current working directory for the scripts executed by Python_{TEX}. By default, the working directory should be the same as the output directory. That way, any files saved in the current working directory will be in the Python_{TEX} output directory, and will thus be kept separate. But in some cases the user may wish to specify a different working directory, such as the document root.

```

\setpythontexworkingdir
265 \newcommand{\setpythontexworkingdir}[1]{%
266     \Depyhtontex{cmd:setpythontexworkingdir:m:n}%
267     \def\pytx@workingdir{#1}%
268 }
269 \@onlypreamble\setpythontexworkingdir
270 \AtBeginDocument{%
271     \ifcsname pytx@workingdir\endcsname\else
272         %\setpythontexworkingdir{\pytx@outputdir}\fi Depyhtontex
273         \let\pytx@workingdir\pytx@outputdir\fi
274 }

```

`pytx@usedpygments` Once we have specified the output directory, we are free to pull in content from it. Most content from the output directory will be pulled in manually by the user (for example, via `\includegraphics`) or automatically by Python_{TEX} as it goes along. But content “printed” by code commands and environments (via macros) as well as code typeset by Pygments needs to be included conditionally, based on whether it exists and on user preferences.

This gets a little tricky. We only want to pull in the Pygments content if it is actually used, since Pygments content will typically use `fancyvrb`’s `SaveVerb` environment, and this can slow down compilation when very large chunks of code are saved. It doesn’t matter if the code is actually used; saving it in a macro is what potentially slows things down. So we create a `bool` to keep track of whether Pygments is ever actually used, and only bring in Pygments content if it is.³⁸ This `bool` must be set to `true` whenever a command or environment is created that makes use of Pygments (in practice, we will simply set it to `true` when a family is created). Note that we cannot use the `pytx@opt@pygments` `bool` for this purpose, because it only tells us if the package option for Pygments usage is `true` or `false`. Typically, this will determine if any Pygments content is used. But it is possible for the user to create a command and environment family that overrides the package option (indeed, this may sometimes be desirable, for example, if the

³⁸The same effect could be achieved by having `pythontex.py` delete the Pygments content whenever it is run and Pygments is not used. But that approach is faulty in two regards. First, it requires that `pythontex.py` be run, which is not necessarily the case if the user simply sets the package option `pygments` to `false` and the recompiles. Second, even if it could be guaranteed that the content would be deleted, such an approach would not be optimal. It is quite possible that the user wishes to temporarily turn off Pygments usage to speed compilation while working on other parts of the document. In this case, deleting the Pygments content is simply deleting data that must be recreated when Pygments is turned back on.

user wishes code in a particular language never to be highlighted). Thus, a new bool is needed to allow detection in such nonstandard cases.

```
275 \newbool{pytx@usedpygments}
```

Now we can conditionally bring in the Pygments content. Note that we must use the `etoolbox` macro `\AfterEndPreamble`. This is because commands and environments are created using `\AtBeginDocument`, so that the user can change their properties in the preamble before they are created. And since the commands and environments must be created before we know the final state of `pytx@usedpygments`, we must bring in Pygments content after that.

```
276 \AfterEndPreamble{%
277   \ifbool{pytx@usedpygments}%
278     {\InputIfFileExists{\pytx@outputdir/\pytx@jobname.pytxpyg}{-}{-}}%
279 }
```

While we are pulling in content, we also pull in the file of macros that stores some inline “printed” content, if the file exists. Since we need this file in general, and since it will not typically involve a noticeable speed penalty, we bring it in at the beginning of the document without any special conditions.

```
280 \AtBeginDocument{%
281   \makeatletter
282   \InputIfFileExists{\pytx@outputdir/\pytx@jobname.pytxmcr}{-}{-}%
283   \makeatother
284 }
```

`\pytx@codefile` We create a new write, named `\pytx@codefile`, to which we will save code. All the code from the document will be written to this single file, interspersed with information specifying where in the document it came from. PythonTeX parses this file to separate the code into individual sessions and groups. These are then executed, and the identifying information is used to tie code output back to the original code in the document.³⁹

```
285 \newwrite\pytx@codefile
286 \immediate\openout\pytx@codefile=\jobname.pytxcode
```

In the code file, information from PythonTeX must be interspersed with the code. Some type of delimiting is needed for PythonTeX information. All PythonTeX content is written to the file in the form `=>PYTHONTEX#(content)#`.

³⁹The choice to write all code to a single file is the result of two factors. First, TeX has a limited number of output registers available (16), so having a separate output stream for each group or session is not possible. The `morewrites` package from Bruno Le Floch potentially removes this obstacle, but since this package is very recent (README from 2011/7/10), we will not consider using additional writes in the immediate future. Second, one of the design goals of PythonTeX is to minimize the number of persistent files created by a run. This keeps directories cleaner and makes file synchronization/transfer somewhat simpler. Using one write per session or group could result in numerous code files, and these could only be cleaned up by `pythontex.py` since L^ATeX cannot delete files itself (well, without unrestricted `writes18`). Using a single output file for code does introduce a speed penalty since the code does not come pre-sorted by session or group, but in typical usage this should be minimal. Adding an option for single or multiple code files may be something to reconsider at a later date.

When this content involves package options, the delimiter is modified to the form `=>PYTHONTEX:SETTINGS#<content>#`. The `#` symbol is also used as a subdelimiter within `<content>`. The `#` symbol is convenient as a delimiter since it has a special meaning in \TeX and is very unlikely to be accidentally entered by the user in unexpected locations without producing errors. Note that the usage of “=>PYTHONTEX#” as a beginning delimiter for Python \TeX data means that this string should **never** be written by the user at the beginning of a line, because `pythontex.py` will try to interpret it as data and will fail.

`\pytx@delimchar` We create a macro to store the delimiting character.

```
287 \edef\pytx@delimchar{\string#}
```

`\pytx@delim` We create a macro to store the starting delimiter.

```
288 \edef\pytx@delim{=\string>PYTHONTEX\string#}
```

`\pytx@delimsettings` And we create a second macro to store the starting delimiter for settings that are passed to Python.

```
289 \edef\pytx@delimsettings{=\string>PYTHONTEX:SETTINGS\string#}
```

Settings need to be written to the code file. Some of these settings are not final until the beginning of the document, since they may be modified by the user within the preamble. Thus, all settings should be written at the end of the document, so that they will all be together and will not be interspersed with any code that was entered in the preamble. The order in which the settings are written is not significant, but for symmetry it should mirror the order in which they were defined.

```
290 \AtEndDocument{%
291   \immediate\write\pytx@codefile{\pytx@delimsettings}%
292   \immediate\write\pytx@codefile{version=\pytx@packageversion}%
293   \immediate\write\pytx@codefile{outputdir=\pytx@outputdir}%
294   \immediate\write\pytx@codefile{workingdir=\pytx@workingdir}%
295   \immediate\write\pytx@codefile{gobble=\pytx@opt@gobble}%
296   \immediate\write\pytx@codefile{rerun=\pytx@opt@rerun}%
297   \immediate\write\pytx@codefile{hashdependencies=\pytx@opt@hashdependencies}%
298   \immediate\write\pytx@codefile{makestderr=\ifbool{pytx@opt@stderr}{true}{false}}%
299   \immediate\write\pytx@codefile{stderrfilename=\pytx@opt@stderrfilename}%
300   \immediate\write\pytx@codefile{keeptemps=\pytx@opt@keeptemps}%
301   \immediate\write\pytx@codefile{pyfuture=\pytx@opt@pyfuture}%
302   \immediate\write\pytx@codefile{pyconfuture=\pytx@opt@pyconfuture}%
303   \immediate\write\pytx@codefile{pygments=\ifbool{pytx@opt@pygments}{true}{false}}%
304   \immediate\write\pytx@codefile{pyglobal=:GLOBAL|\pytx@pyglexer|\pytx@pygopt}%
305   \immediate\write\pytx@codefile{fvextfile=\pytx@fvextfile}%
306   \immediate\write\pytx@codefile{pyconbanner=\pytx@opt@pyconbanner}%
307   \immediate\write\pytx@codefile{pyconfilename=\pytx@opt@pyconfilename}%
308   \immediate\write\pytx@codefile{depythontex=\ifbool{pytx@opt@depythontex}{true}{false}}%
309 }
```

`\pytx@WriteCodefileInfo` Later, we will frequently need to write Python \TeX information to the code file in standardized form. We create a macro to simplify that process. We also create `\pytx@WriteCodefileInfoExt`

an alternate form, for use with external files that must be inputted or read in by PythonTeX and processed. While the standard form employs a counter that is incremented elsewhere, the version for external files substitutes a zero (0) for the counter, because each external file must be unique in name and thus numbering via a counter is redundant.⁴⁰

```

310 \def\pytx@argsrun{}
311 \def\pytx@argspprint{}
312 \def\pytx@WriteCodefileInfo{%
313     \ifcurrfile{\currfilebase}{\jobname}%
314     {\let\pytx@currfile\empty}{\let\pytx@currfile\currfilename}%
315     \immediate\write\pytx@codefile{\pytx@delim\pytx@type\pytx@delimchar%
316     \pytx@session\pytx@delimchar\pytx@group\pytx@delimchar%
317     \arabic{\pytx@counter}\pytx@delimchar\pytx@cmd\pytx@delimchar%
318     \pytx@context\pytx@delimchar\pytx@argsrun\pytx@delimchar%
319     \pytx@argspprint\pytx@delimchar%
320     \pytx@currfile\pytx@delimchar%
321     \the\inputlineno\pytx@delimchar}%
322 }
323 \newcommand{\pytx@WriteCodefileInfoExt}[1][{}]{%
324     \ifcurrfile{\currfilebase}{\jobname}%
325     {\let\pytx@currfile\empty}{\let\pytx@currfile\currfilename}%
326     \immediate\write\pytx@codefile{\pytx@delim\pytx@type\pytx@delimchar%
327     \pytx@session\pytx@delimchar\pytx@group\pytx@delimchar%
328     0\pytx@delimchar\pytx@cmd\pytx@delimchar%
329     \pytx@context\pytx@delimchar\pytx@argsrun\pytx@delimchar%
330     \pytx@argspprint\pytx@delimchar%
331     \pytx@currfile\pytx@delimchar%
332     \the\inputlineno\pytx@delimchar#1}%
333 }

```

9.4.6 Interface to fancyvrb

The `fancyvrb` package is used to typeset lines of code, and its internals are also used to format inline code snippets. We need a way for each family of PythonTeX commands and environments to have its own independent `fancyvrb` settings.

`\pytx@fvsettings` The macro `\setpythontexfv[⟨family⟩]{⟨settings⟩}` takes `⟨settings⟩` and stores them in a macro that is run through `fancyvrb`'s `\fvset` at the beginning of PythonTeX code. If a `⟨family⟩` is specified, the settings are stored in `\pytx@fvsettings@⟨family⟩`, and the settings only apply to typeset code belonging to that family. If no optional argument is given, then the settings are stored in `\pytx@fvsettings`, and the settings apply to all typeset code.

In the current implementation, `\setpythontexfv` and `\fvset` differ because the former is not persistent in the same sense as the latter. If we use `\fvset`

⁴⁰The external-file form also takes an optional argument. This corresponds to a command-line argument that is passed to an external file during the file's execution. Currently, executing external files, with or without arguments, is not implemented. But this feature is under consideration, and the macro retains the optional argument for the potential future compatibility.

to set one property, and then use it later to set another property, the setting for the original property is persistent. It remains until another `\fvset` command is issued to change it. In contrast, every time `\setpythontexfv` is used, it clears all prior settings and only the current settings actually apply. This is because `\fvset` stores the state of each setting in its own macro, while `\setpythontexfv` simply stores a string of settings that is passed to `\fvset` at the appropriate times. For typical use scenarios, this distinction shouldn't be important—usually, we will want to set the behavior of `fancyvrb` for all Python \TeX content, or for a family of Python \TeX content, and leave those settings constant throughout the document. Furthermore, environments that typeset code take `fancyvrb` commands as their second optional argument, so there is already a mechanism in place for changing the settings for a single environment. However, if we ever want to change the typesetting of code for only a small portion of a document (larger than a single environment), this persistence distinction does become important.⁴¹

```

334 \newcommand{\setpythontexfv}[2] [] {%
335     \Depythontex{cmd:setpythontexfv:om:n}%
336     \ifstrempy{#1}%
337         {\gdef\pytx@fvsettings{#2}}%
338         {\expandafter\gdef\csname pytx@fvsettings@#1\endcsname{#2}}%
339 }%

```

Now that we have a mechanism for applying global settings to typeset Python \TeX code, we go ahead and set a default tab size for all environments. If `\setpythontexfv` is ever invoked, this setting will be overwritten, so that must be kept in mind.

```

340 \setpythontexfv{tabsize=4}

```

`\pytx@FVSet` Once the `fancyvrb` settings for Python \TeX are stored in macros, we need a way to actually invoke them. `\pytx@FVSet` applies family-specific settings first, then Python \TeX -wide settings second, so that Python \TeX -wide settings have precedence and will override family-specific settings. Note that by using `\fvset`, we are overwriting `fancyvrb`'s settings. Thus, to keep the settings local to the Python \TeX code, `\pytx@FVSet` must always be used within a `\begingroup ... \endgroup` block.

```

341 \def\pytx@FVSet{%
342     \expandafter\let\expandafter\pytx@fvsettings@@%
343         \csname pytx@fvsettings@\pytx@type\endcsname
344     \ifdefstring{\pytx@fvsettings@@}{}%
345         {}%
346         {\expandafter\fvset\expandafter{\pytx@fvsettings@@}}%
347     \ifdefstring{\pytx@fvsettings}{}%
348         {}%

```

⁴¹An argument could be made for having `\setpythontexfv` behave exactly like `\fvset`. Properly implementing this behavior would be tricky, because of inheritance issues between Python \TeX -wide and family-specific settings (this is probably a job for `pgfkeys`). Full persistence would likely require a large number of macros and conditionals. At least from the perspective of keeping the code clean and concise, the current approach is superior, and probably introduces minor annoyances at worst.

```

349         {\expandafter\fvset\expandafter{\pytx@fvsettings}}%
350 }

```

`\pytx@FVB@SaveVerbatim` and `pytx@FancyVerbLineTemp` `fancyvrb`'s `SaveVerbatim` environment will be used extensively to include code highlighted by Pygments and other processed content. Unfortunately, when the saved content is included in a document with the corresponding `UseVerbatim`, line numbering does not work correctly. Based on a web search, this appears to be a known bug in `fancyvrb`. We begin by fixing this, which requires patching `fancyvrb`'s `\FVB@SaveVerbatim` and `\FVE@SaveVerbatim`. We create a patched `\pytx@FVB@SaveVerbatim` by inserting `\FV@StepLineNo` and `\FV@CodeLineNo=1` at appropriate locations. We also delete an unnecessary `\gdef\SaveVerbatim@Name{#1}`. Then we create a `\pytx@FVE@SaveVerbatim`, and add code so that the two macros work together to prevent `FancyVerbLine` from incorrectly being incremented within the `SaveVerbatim` environment. This involves using the counter `pytx@FancyVerbLineTemp` to temporarily store the value of `FancyVerbLine`, so that it may be restored to its original value after verbatim content has been saved.

Typically, we `\let` our own custom macros to the corresponding macros within `fancyvrb`, but only within a command or environment. In this case, however, we are fixing behavior that should be considered a bug even for normal `fancyvrb` usage. So we let the buggy macros to the patched macros immediately after defining the patched versions.

```

351 \newcounter{pytx@FancyVerbLineTemp}
352 \def\pytx@FVB@SaveVerbatim#1{%
353     \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
354     \bsphack
355     \begingroup
356     \FV@UseKeyValues
357     \def\SaveVerbatim@Name{#1}%
358     \def\FV@ProcessLine##1{%
359         \expandafter\gdef\expandafter\FV@TheVerbatim\expandafter{%
360             \FV@TheVerbatim\FV@StepLineNo\FV@ProcessLine{##1}}%
361     \gdef\FV@TheVerbatim{\FV@CodeLineNo=1}%
362     \FV@Scan}
363 \def\pytx@FVE@SaveVerbatim{%
364     \expandafter\global\expandafter\let
365     \csname FV@SV@\SaveVerbatim@Name\endcsname\FV@TheVerbatim
366     \endgroup\@esphack
367     \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}
368 \let\FVB@SaveVerbatim\pytx@FVB@SaveVerbatim
369 \let\FVE@SaveVerbatim\pytx@FVE@SaveVerbatim

```

9.4.7 Access to printed content (stdout)

The `autoprint` package option automatically pulls in printed content from code commands and environments. But this does not cover all possible use cases, because we could have print statements/functions in `block` commands and environments as well. Furthermore, sometimes we may print content, but then desire

to bring it back into the document multiple times, without duplicating the code that creates the content. Here, we create a number of macros that allow access to printed content. All macros are created in two identical forms, one based on the name `print` and one based on the name `stdout`. Which macros are used depends on user preference. The macros based on `stdout` provide symmetry with `stderr` access.

`\pytx@stdfile` We begin by defining a macro to hold the base name for stdout and stderr content. The name of this file is updated by most commands and environments so that it stays current.⁴² It is important, however, to initially set the name empty for error-checking purposes.

```
370 \def\pytx@stdfile{}
```

`\pytx@FetchStdoutfile` Now we create a generic macro for bringing in the stdout file. This macro can input the content in verbatim form, applying `fancyvrb` options if present. Usage: `\pytx@FetchStdoutfile[<mode>][<options>]{<file path>}`. We must disable the macro in the event that the `debug` option is false. Also, the warning text should not be included if we are in the preamble.

```
371 \def\pytx@stdout@warntext{}
372 \def\pytx@FetchStdoutfile[#1][#2]#3{%
373     \IfFileExists{\pytx@outputdir/#3.stdout}{%
374         \ifstrepty{#1}{\input{\pytx@outputdir/#3.stdout}}{%
375         \ifstrequal{#1}{raw}{\input{\pytx@outputdir/#3.stdout}}{%
376         \ifstrequal{#1}{verb}{\BVerbatimInput[#2]{\pytx@outputdir/#3.stdout}}{%
377         \ifstrequal{#1}{verbatim}{\VerbatimInput[#2]{\pytx@outputdir/#3.stdout}}{%
378         \DepyFile{p:\pytx@outputdir/#3.stdout:mode=#1}%
379     }%
380     {\pytx@stdout@warntext
381     \PackageWarning{\pytx@packagename}{Non-existent printed content}}%
382 }
383 \ifbool{pytx@opt@stdout}{\def\pytx@FetchStdoutfile[#1][#2]#3{}}
384 \AtBeginDocument{\def\pytx@stdout@warntext{\textbf{??~\pytx@packagename~??}}}
```

`\printpythontex` We define a macro that pulls in the content of the most recent stdout file, accepting
`\stdoutpythontex` verbatim settings and also `fancyvrb` settings if they are given.

```
385 \def\stdoutpythontex{%
386     \Depythontex{cmd:stdoutpythontex:oo:p}%
387     \@ifnextchar[{\pytx@Stdout}{\pytx@Stdout[raw]}%
388 }
389 \def\pytx@Stdout[#1]{%
390     \@ifnextchar[{\pytx@Stdout@i[#1]}{\pytx@Stdout@i[#1] []}%
391 }
392 \def\pytx@Stdout@i[#1][#2]{%
393     \pytx@FetchStdoutfile[#1][#2]{\pytx@stdfile}%
```

⁴²It is only updated by those commands and environments that interact with `pythontex.py` and thus increment a type-session-group counter so that they can be distinguished. `verb` commands and environments that use `fancyvrb` for typesetting do not interact with `pythontex.py`, do not increment a counter, and thus do not update the stdout file.

```

394 }
395 \def\printpythontex{%
396   \Depyhtontex{cmd:printpythontex:oo:p}%
397   \@ifnextchar[{\pytx@Stdout}{\pytx@Stdout[raw]}%
398 }

```

`\saveprintpythontex` Sometimes, we may wish to use printed content at multiple locations in a document. Because `\pytx@stdfile` is changed by every command and environment that could print, the printed content that `\printpythontex` tries to access is constantly changing. Thus, `\printpythontex` is of use only immediately after content has actually been printed, before any additional PythonTeX commands or environments change the definition of `\pytx@stdfile`. To get around this, we create `\saveprintpythontex{<name>}`. This macro saves the current name of `\pytx@stdfile` so that it is associated with `<name>` and thus can be retrieved later, after `\pytx@stdfile` has been redefined.

```

399 \def\savestdoutpythontex{%
400   \Depyhtontex{cmd:savestdoutpythontex:m:n}%
401   \savestdoutpythontex@i
402 }
403 \def\savestdoutpythontex@i#1{%
404   \ifcsname pytx@SVout@#1\endcsname
405     \PackageError{\pytx@packagename}%
406       {Attempt to save content using an already-defined name}%
407       {Use a name that is not already defined}%
408   \else
409     \expandafter\edef\csname pytx@SVout@#1\endcsname{\pytx@stdfile}%
410   \fi
411 }
412 \def\saveprintpythontex{%
413   \Depyhtontex{cmd:saveprintpythontex:m:n}%
414   \savestdoutpythontex@i
415 }

```

`\useprintpythontex` Now that we have saved the current `\pytx@stdoutfile` under a new, user-chosen name, we need a way to retrieve the content of that file later, using the name.

```

\usestdoutpythontex
416 \def\usestdoutpythontex{%
417   \Depyhtontex{cmd:usestdoutpythontex:oom:p}%
418   \@ifnextchar[{\pytx@UseStdout}{\pytx@UseStdout[]}%
419 }
420 \def\pytx@UseStdout[#1]{%
421   \@ifnextchar[{\pytx@UseStdout@i[#1]}{\pytx@UseStdout@i[#1][]}%
422 }
423 \def\pytx@UseStdout@i[#1][#2]#3{%
424   \ifcsname pytx@SVout@#3\endcsname
425     \pytx@FetchStdoutfile[#1][#2]{\csname pytx@SVout@#3\endcsname}%
426   \else
427     \textbf{??~\pytx@packagename~??}%
428     \PackageWarning{\pytx@packagename}{Non-existent saved printed content}%
429   \fi

```

```

430 }
431 \def\useprintpythontex{%
432   \Depyhtontex{cmd:useprintpythontex:oom:p}%
433   \@ifnextchar[\pytx@UseStdout]{\pytx@UseStdout []}%
434 }

```

9.4.8 Access to stderr

We need access to stderr, if it is enabled via the package `makestderr` option.

Both stdout and stderr share the same base file name, stored in `\pytx@stdfile`. Only the file extensions, `.stdout` and `.stderr`, differ.

stderr and stdout are treated identically, except that stderr is brought in verbatim by default, while stdout is brought in raw by default.

`\pytx@FetchStderrfile` Create a generic macro for bringing in the stderr file.

```

435 \def\pytx@FetchStderrfile[#1][#2]#3{%
436   \IfFileExists{\pytx@outputdir/#3.stderr}{%
437     \ifstrequal{#1}{raw}{\input{\pytx@outputdir/#3.stderr}}{%
438     \ifstreempty{#1}{\VerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{%
439     \ifstrequal{#1}{verb}{\BVerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{%
440     \ifstrequal{#1}{verbatim}{\VerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{%
441     \DepyFile{p:\pytx@outputdir/#3.stderr:mode=#1}%
442   }%
443   {\textbf{??~\pytx@packagename~??}}%
444   \PackageWarning{\pytx@packagename}{Non-existent stderr content}}%
445 }

```

`\stderrpythontex` We define a macro that pulls in the content of the most recent error file, accepting verbatim settings and also fancyvrb settings if they are given.

```

446 \def\stderrpythontex{%
447   \Depyhtontex{cmd:stderrpythontex:oo:p}%
448   \@ifnextchar[\pytx@Stderr]{\pytx@Stderr[verbatim]}%
449 }
450 \def\pytx@Stderr[#1]{%
451   \@ifnextchar[\pytx@Stderr@i[#1]]{\pytx@Stderr@i[#1] []}%
452 }
453 \def\pytx@Stderr@i[#1][#2]{%
454   \pytx@FetchStderrfile[#1][#2]{\pytx@stdfile}%
455 }

```

A mechanism is provided for saving and later using stderr. This should be used with care, since stderr content may lose some of its meaning if isolated from the larger code context that produced it.

`\savestderrpythontex`

```

456 \def\savestderrpythontex#1{%
457   \Depyhtontex{cmd:savestderrpythontex:m:n}%
458   \ifcsname pytx@SVerr@#1\endcsname
459     \PackageError{\pytx@packagename}%

```

```

460             {Attempt to save content using an already-defined name}%
461             {Use a name that is not already defined}%
462     \else
463         \expandafter\edef\csname pytx@SVerr@#1\endcsname{\pytx@stdfile}%
464     \fi
465 }

```

`\usestderrpythontex`

```

466 \def\usestderrpythontex{%
467     \Depythontex{cmd:usestderrpythontex:oom:p}%
468     \@ifnextchar[{\pytx@UseStderr}{\pytx@UseStderr[verb]}%
469 }
470 \def\pytx@UseStderr[#1]{%
471     \@ifnextchar[{\pytx@UseStderr@i[#1]}{\pytx@UseStderr@i[#1] []}%
472 }
473 \def\pytx@UseStderr@i[#1][#2]#3{%
474     \ifcsname pytx@SVerr@#3\endcsname
475         \pytx@FetchStderrfile[#1][#2]{\csname pytx@SVerr@#3\endcsname}%
476     \else
477         \textbf{??~\pytx@packagename~??}%
478         \PackageWarning{\pytx@packagename}{Non-existent saved stderr content}%
479     \fi
480 }

```

9.4.9 depythontex

The purpose of `depythontex` is to create a version of the original L^AT_EX document that does not rely on the Python_TE_X package. All uses of Python_TE_X are replaced by their output. This is particularly useful when submitting a paper to a journal, because Python_TE_X can simplify the writing process, but many journals frown upon “special” packages or custom macros. Note that if you just need to share a Python_TE_X document with someone, you can always include a copy of `pythontex.sty` and the Python_TE_X output directory with the document, and then non-Python parts of the document can be edited just like a normal L^AT_EX document, without running any Python code.

The general strategy for `depythontex` is to write an auxiliary file that contains information about all environments and macros that need to be replaced, including location, format, and the content with which they are to be replaced. This auxiliary file is then used to perform substitutions on a copy of the original document. It would be possible to simply create a list of all Python_TE_X macros and environments, and use that to perform substitutions. But that approach would have to track the state of Python_TE_X more carefully than the auxiliary file approach. For example, in the auxiliary file approach, it is easy to track whether `autoprint` is on or off, because commands and environments will write to the auxiliary file if they do indeed use `autoprint`. But without an auxiliary file, you would have to search for `\setpythontexautoprint` and devise an algorithm for determining where it is on or off. Furthermore, once there is a large set of macros, a general search-and-replace could be quite expensive computationally.

These commands need to be defined after all the other settings commands, because some of the other settings commands are used within this package after being defined, and thus don't need replacement because they're in the package. At the same time, the `depythontex` commands have to exist so that other commands can be defined with them. So dummy versions are created earlier. During the next refactoring, the order will be cleaned up and clarified.

`\pytx@depyfile` If the `depythontex` package option is on, we need to open an auxiliary file for writing `depythontex` information.

```
481 \ifbool{pytx@opt@depythontex}{%
482   \newwrite\pytx@depyfile
483   \immediate\openout\pytx@depyfile=\jobname.depytx
484 }{}
```

`\Depythontex` Each command or environment that is to work with `depythontex` will write the following information to the auxiliary file:

```
=>DEPYTHONTEX#<type>:<name>:<args>:<typeset>:<line>:[<Pygments lexer>]#
```

where `<type>` is `cmd` or `env`; `<name>` is the complete name of the command or environment; `<args>` is a string representing the arguments taken (`o`=optional, `m`=mandatory, `v`=mandatory verbatim, `n`=none); `<typeset>` is a string representing what is typeset (`c`=code, `p`=printed, `n`=null), and `<line>` is `\the\inputlineno`. The last one can be determined automatically without user input, but the first four must be entered when a macro is created. Optionally, the Pygments lexer is written to file if it is available (if `\pytx@lexer` is not `\relax`). These pieces of information are needed for the following reasons.

- `<type>` We need to know whether we are dealing with a command or environment, so we know how to deal with it. There is no way to detect this automatically, since a command could always be inside some environment.
- `<name>` We need to know the name of what is to be replaced. There's no way to automatically get this.
- `<args>` We need to know the form of the arguments, so we can assemble an appropriate regular expression. In some cases, a command might be created in such a way that this could be detected or easily passed on to PythonTeX (for example, if the command was defined using the `xparse` package), but in general there isn't a simple way to detect it.
- `<typeset>` Technically, this could be determined from `\pytx@cmd` in many instances. But it couldn't be determined for cases like `\printpythontex` and `\stderrpythontex`. Furthermore, we want a very general interface suitable for users writing custom commands and environments.
- `<line>` This can be determined automatically.

- `<Pygments lexer>` This is needed if so that the language can be specified in the output. In general, `\pytx@lexer` can be defined automatically by a command and environment generator.

We need a command that writes this information to the auxiliary file. Since this command may be employed by users writing custom macros, we choose a capitalized name not containing any ampersands `@`. Since we need to be able to easily disable the macro, we create the real macro with name ending in `@orig`, and then `\let` the intended name to it.

```

485 \let\pytx@lexer\relax
486 \def\Depythontex@orig#1{%
487     \immediate\write\pytx@depyfile{=>DEPYTHONTEX\pytx@delimchar#1:%
488         \the\inputlineno:\ifx\pytx@lexer\relax\else\pytx@lexer\fi\pytx@delimchar}%
489     \let\pytx@lexer\relax}
490 \ifbool{pytx@opt@depythontex}%
491     {\let\Depythontex\Depythontex@orig}%
492     {\let\Depythontex@gobble}
493 \ifbool{pytx@opt@depythontex}{%
494 \AtEndDocument{%
495     \immediate\write\pytx@depyfile{=>DEPYTHONTEX:SETTINGS\pytx@delimchar version=%
496         \pytx@packageversion\pytx@delimchar}%
497     \immediate\write\pytx@depyfile{=>DEPYTHONTEX:SETTINGS\pytx@delimchar macrofile=%
498         \pytx@outputdir/\pytx@jobname.pytxmcr\pytx@delimchar}%
499     \immediate\write\pytx@depyfile{=>DEPYTHONTEX:SETTINGS\pytx@delimchar outputdir=%
500         \pytx@outputdir\pytx@delimchar}%
501     \immediate\write\pytx@depyfile{=>DEPYTHONTEX:SETTINGS\pytx@delimchar graphicx=%
502         \ifcsname graphicspath\endcsname true\else false\fi\pytx@delimchar}%
503     \immediate\write\pytx@depyfile{=>DEPYTHONTEX:SETTINGS\pytx@delimchar gobble=%
504         \pytx@opt@gobble\pytx@delimchar}%
505 }%
506 }{}

```

`\DepyMacro` We need a macro that will write the appropriate information to the auxiliary file if substitution with the contents of a macro is needed. The argument is of the form `<typeset>:<macro name>`, where `<typeset>` is the type of content (`p`=print, `c`=code).

```

507 \def\DepyMacro@orig#1{%
508     \immediate\write\pytx@depyfile{MACRO:#1}%
509 }
510 \ifbool{pytx@opt@depythontex}%
511     {\let\DepyMacro\DepyMacro@orig}%
512     {\let\DepyMacro@gobble}

```

`\DepyFile` We also need a macro that will write the appropriate information to the auxiliary file if substitution with the contents of a file is needed. As an argument, this command takes `<typeset>:<filename>[:mode=<format>]`, where `<typeset>` is the type of content (`p`=print, `c`=code), `<filename>` is the full filename, and the optional `mode` is the format in which the file is brought in (`raw`, `verb`, `verbatim`).

If `mode` is not specified, it defaults to reasonable defaults. In general, `mode` is only needed for `p` content; `c` content is verbatim of one form or another.

```
513 \def\DePyFile@orig#1{%
514   \immediate\write\pytx@depyfile{FILE:#1}%
515 }%
516 \ifbool{pytx@opt@depythontex}%
517   {\let\DePyFile\DePyFile@orig}%
518   {\let\DePyFile\@gobble}
```

`\DePyListing` We need a macro that will write information to the auxiliary file for code listings, specifically whether line numbers were used, and if so, what the starting number was. This is non-trivial, because it is possible to change both of these via an environment's second optional argument. One approach would be to capture all optional arguments, pass the second to `fancyvrb`, and then attempt to evaluate the status of line numbers via an examination of `fancyvrb`'s internals. That approach would require a good deal of work and would likely involve a patch for `fancyvrb`. Instead, we redefine `\theFancyVerbLine`, so that it saves the line number to file the first time it is used, and then redefines itself to its original form.

Since we are redefining `\theFancyVerbLine`, `\DePyListing` can only be used with commands (such as `\inputpygments`) if it is in a group (`\begingroup ... \endgroup`). This prevents the redefinition from “escaping,” if line numbering is not used. (Environments are wrapped in groups automatically, so this doesn't apply to them.)

```
519 \newcommand{\pytx@DePyListing@write}{%
520   \immediate\write\pytx@depyfile{LISTING:firstnumber=\arabic{FancyVerbLine}}%
521 }
522 \def\DePyListing@orig{%
523   \let\oldFancyVerbLine\theFancyVerbLine
524   \def\theFancyVerbLine{%
525     \pytx@DePyListing@write
526     \expandafter\gdef\expandafter\theFancyVerbLine\expandafter{\oldFancyVerbLine}%
527     \theFancyVerbLine
528   }%
529 }
530 \ifbool{pytx@opt@depythontex}%
531   {\let\DePyListing\DePyListing@orig}%
532   {\let\DePyListing\@empty}
```

`\DePythontexOn` We need a way to switch `depythontex` on and off. When `depythontex` is being used, it needs to be on throughout the entire main document. But it must be switched off for any commands or environments that are brought in via external files (for example, in a package). Since anything that is brought in isn't actually in the text of the main document, substitution is both impossible and unnecessary.

```
533 \newcommand{\DePythontexOn}{%
534   \let\DePythontex\DePythontex@orig
535   \let\DePyMacro\DePyMacro@orig
536   \let\DePyFile\DePyFile@orig
537   \let\DePyListing\DePyListing@orig
```

```

538 }
539 \newcommand{\DepyhtontexOff}{%
540   \let\Depyhtontex@gobble
541   \let\DepyMacro@gobble
542   \let\DepyFile@gobble
543   \let\DepyListing@empty
544 }

```

9.5 Inline commands

9.5.1 Inline core macros

All inline commands use the same core of inline macros. Inline commands invoke the `\pytx@Inline` macro, and this then branches through a number of additional macros depending on the details of the command and the usage context. `\@ifnextchar` and `\let` are used extensively to control branching.

`\pytx@Inline`, and the macros it calls, perform the following series of operations.

- If there is an optional argument, capture it. The optional argument is the session name of the command. If there is no session name, use the “`default`” session.
- Determine the delimiting character(s) used for the code encompassed by the command. Any character except for the space character and the opening curly brace `{` may be used as a delimiting character, just as for `\verb`. The opening curly brace `{` may be used, but in this case the closing delimiting character is the closing curly brace `}`. If paired curly braces are used as delimiters, then the code enclosed may only contain paired curly braces.
- Using the delimiting character(s), capture the code. Perform some combination of the following tasks: typeset the code, save it to the code file, and bring in content created by the code.

`\pytx@Inline` This is the gateway to all inline core macros. It is called by all inline commands. Because the delimiting characters could be almost anything, we need to turn off all special category codes before we peek ahead with `\@ifnextchar` to see if an optional argument is present, since `\@ifnextchar` sets the category code of the character it examines. But we set the opening curly brace `{` back to its standard catcode, so that matched braces can be used to capture an argument as usual. The catcode changes are enclosed withing `\begingroup ... \endgroup` so that they may be contained.

The macro `\pytx@Inline0arg` which is called at the end of `\pytx@Inline` takes an argument enclosed by square brackets. If an optional argument is not present, then we supply an empty one, which invokes default treatment in `\pytx@Inline0arg`.

```

545 \def\pytx@Inline{%
546   \begingroup

```

```

547 \let\do\@makeother\dospecials
548 \catcode'\{=1
549 \@ifnextchar[{\endgroup\pytx@InlineOarg}{\endgroup\pytx@InlineOarg[]}%
550 }%

```

`\pytx@InlineOarg` This macro captures the optional argument (or the empty default substitute), which corresponds to the code session. Then it determines whether the delimiters of the actual code are a matched pair of curly braces or a pair of other, identical characters, and calls the next macro accordingly.

We begin by testing for an empty argument (either from the user or from the default empty substitute), and setting the default value if this is indeed the case. It is also possible that the user chose a session name containing a colon. If so, we substitute a hyphen for the colon. This is because temporary files are named based on session, and file names often cannot contain colons.

Then we turn off all special catcodes and set the catcodes of the curly braces back to their default values. This is necessary because we are about to capture the actual code, and we need all special catcodes turned off so that the code can contain any characters. But curly braces still need to be active just in case they are being used as delimiters. We also make the space and tab characters active, since `fancyvrb` needs them that way.⁴³ Using `\@ifnextchar` we determine whether the delimiters are curly braces. If so, we proceed to `\pytx@InlineMargBgroup` to capture the code using curly braces as delimiters. If not, we reset the catcodes of the braces and proceed to `\pytx@InlineMargOther`, which uses characters other than the opening curly brace as delimiters.

```

551 \def\pytx@InlineOarg[#1]{%
552   \ifstrempy{#1}{\edef\pytx@session{default}}{\StrSubstitute{#1}{:}{-}[\pytx@session]}%
553   \begingroup
554   \let\do\@makeother\dospecials
555   \catcode'\{=1
556   \catcode'\}=2
557   \catcode'\ =\active
558   \catcode'\^^I=\active
559   \@ifnextchar\bgroup
560     {\pytx@InlineMargBgroup}%
561     {\catcode'\{=12
562       \catcode'\}=12
563       \pytx@InlineMargOther}%
564 }

```

`\pytx@InlineMargOther` This macro captures code delimited by a pair of identical non-brace characters. `\pytx@InlineMargOtherGet` Then it passes the code on to `\pytx@InlineMargBgroup` for processing. This approach means that the macro definition may be kept concise, and that the processing code must only be defined once.

The macro captures only the next character. This will be the delimiting character. We must begin by ending the group that was left open by `\pytx@InlineOarg`,

⁴³Part of this may be redundant, since we detokenize later and then retokenize during typesetting if `Pygments` isn't used. But the detokenizing and saving eliminates tab characters if they aren't active here.

so that catcodes return to normal. Next we check to see if the delimiting character is a space character. If so, we issue an error, because that is not allowed. If the delimiter is valid, we define a macro `\pytx@InlineMargOtherGet` that will capture all content up to the next delimiting character and pass it to the `\pytx@InlineMargBgroup` macro for processing. That macro does exactly what is needed, except that part of the retokenization is redundant since curly braces were not active when the code was captured.

Once the custom capturing macro has been created, we turn off special catcodes and call the capturing macro.

```

565 \def\pytx@InlineMargOther#1{%
566   \endgroup
567   \ifstrequal{#1}{ }{%
568     \PackageError{\pytx@packagename}%
569       {The space character cannot be used as a delimiting character}%
570       {Choose another delimiting character}}{%
571   \def\pytx@InlineMargOtherGet##1#1{\pytx@InlineMargBgroup{##1}}%
572   \begingroup
573   \let\do\@makeother\dospecials
574   \pytx@InlineMargOtherGet
575 }

```

`\pytx@InlineMargBgroup` We are now ready to capture code using matched curly braces as delimiters, or to process previously captured code that used another delimiting character.

At the very beginning, we must end the group that was left open from `\pytx@InlineOarg` (or by `\pytx@InlineMargOther`), so that catcodes return to normal.

We save a detokenized version of the argument in `\pytx@argdetok`. Even though the argument was captured under special catcode conditions, this is still necessary. If the argument was delimited by curly braces, then any internal curly braces were active when the argument was captured, and these need their catcodes corrected. If the code contains any unicode characters, detokenization is needed so that they may be correctly saved to file.

We save a retokenized version of the argument in `\pytx@argretok`. This is needed for typesetting with `fancyvrb`. The code must be retokenized so that space characters are active, since `fancyvrb` allows space characters to be visible or invisible by making them active.

The **name** of the counter corresponding to this code is assembled. It is needed for keeping track of the instance, and is used for bringing in content created by the code and for bringing in highlighting created by Pygments.

Next we call a series of macros that determine whether the code is shown (typeset), whether it is saved to the code file, and whether content created by the code (“printed”) should be brought in. These macros are `\let` to appropriate values when an inline command is called; they are not defined independently.

Finally, the counter for the code is incremented.

```

576 \def\pytx@InlineMargBgroup#1{%
577   \endgroup
578   \def\pytx@argdetok{\detokenize{#1}}%

```

```

579 \def\pytx@arg{#1}%
580 \xdef\pytx@counter{\pytx@pytx@type @\pytx@session @\pytx@group}%
581 \pytx@CheckCounter{\pytx@counter}%
582 \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
583 \pytx@InlineShow
584 \pytx@InlineSave
585 \pytx@InlinePrint
586 \stepcounter{\pytx@counter}%
587 }%

```

`\pytx@InlineShow` The three macros `\pytx@InlineShow`, `\pytx@InlineSave`, and `\pytx@InlinePrint` will be `\let` to appropriate values when commands are called. We must now define `\pytx@InlineSave` the macros to which they may be `\let`.

`\pytx@InlinePrint` Code may be typeset with `fancyvrb`. `fancyvrb` settings are invoked via `\pytx@FVSet`, but this must be done within a group so that the settings remain local. Most of the remainder of the commands are from `fancyvrb`'s `\FV@FormattingPrep`, and take care of various formatting matters, including spacing, font, whether space characters are shown, and any user-defined formatting. Finally, we create an `\hbox` and invoke `\FancyVerbFormatLine` to maintain parallelism with `BVerbatim`, which is used for inline content highlighted with Pygments. `\FancyVerbFormatLine` may be redefined to alter the typeset code, for example, by putting it in a colorbox via the following command:⁴⁴

```

\renewcommand{\FancyVerbFormatLine}[1]{\colorbox{green}{#1}}
588 \def\pytx@InlineShowFV{%
589 \def\pytx@argretok{%
590 \begingroup
591 \everyeof{\noexpand}%
592 \endlinechar-1\relax
593 \let\do\@makeother\dospecials
594 \catcode'\ =\active
595 \catcode'\^~I=\active
596 \expandafter\scantokens\expandafter{\pytx@arg}%
597 \endgroup}%
598 \begingroup
599 \pytx@FVSet
600 \FV@BeginVBox
601 \frenchspacing
602 \FV@SetupFont
603 \FV@DefineWhiteSpace
604 \FancyVerbDefineActive
605 \FancyVerbFormatCom
606 \FV@ObeyTabsInit
607 \hbox{\FancyVerbFormatLine{\pytx@argretok}}%

```

⁴⁴Currently, `\FancyVerbFormatLine` is global, as in `fancyvrb`. Allowing a family-specific variant may be considered in the future. In most cases, the `fancyvrb` option `formatcom`, combined with external formatting from packages like `mdframed`, should provide all formatting desired. But something family-specific might occasionally prove useful.

```

608   \FV@EndVBox
609   \endgroup
610 }

```

`\pytx@InlineShowPyg` Code may be typeset with Pygments. Processed Pygments content is saved in the `.pytxmcr` file, wrapped in `fancyvrb`'s `SaveVerbatim` environment. The content is then restored, in a form suitable for inline use, via `BUseVerbatim`. Unlike non-inline content, which may be brought in either via macro or via separate external file, inline content is always brought in via macro. The counter `pytx@FancyVerbLineTemp` is used to prevent `fancyvrb`'s line count from being affected by Python \TeX content. A group is necessary to confine the `fancyvrb` settings created by `\pytx@FVSet`.

```

611 \def\pytx@InlineShowPyg{%
612   \begingroup
613   \pytx@FVSet
614   \ifcsname FV@SV@\pytx@counter @\arabic{\pytx@counter}\endcsname
615     \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
616     \BUseVerbatim{\pytx@counter @\arabic{\pytx@counter}}%
617     \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}%
618   \else
619     \textbf{??}%
620     \PackageWarning{\pytx@packagename}{Non-existent Pygments content}%
621   \fi
622   \endgroup
623 }

```

`\pytx@InlineSaveCode` This macro writes Python \TeX information to the code file and then writes the actual code.

```

624 \def\pytx@InlineSaveCode{%
625   \pytx@WriteCodefileInfo
626   \immediate\write\pytx@codefile{\pytx@argdetok}%
627 }

```

`\pytx@InlineAutoprint` This macro brings in printed content automatically, if the package `autoprint` option is true. Otherwise, it does nothing. We must disable the macro in the event that the `debug` option is false. We wait until the beginning of the document to create the real macro, since any code commands and environments in the preamble shouldn't be printing and in any case we can't know what the `outputdir` is until the beginning of the document.

```

628 \let\pytx@InlineAutoprint\@empty
629 \AtBeginDocument{
630   \def\pytx@InlineAutoprint{%
631     \ifbool{pytx@opt@autoprint}{%
632       \InputIfFileExists{\pytx@outputdir/\pytx@stdfile.stdout}%
633       {\DepyFile{p:\pytx@outputdir/\pytx@stdfile.stdout}}{}}{}%
634   }
635   \ifbool{pytx@opt@stdout}{\let\pytx@InlineAutoprint\@empty}
636 }

```

`\pytx@InlineMacroprint` This macro brings in “printed” content that is brought in via macros in the `.pytxmcr` file. We must disable the macro in the event that the `debug` option is false.

```

637 \def\pytx@InlineMacroprint{%
638   \edef\pytx@mcr{\pytx@MCR@\pytx@type @\pytx@session @\pytx@group @\arabic{\pytx@counter}}%
639   \ifcsname\pytx@mcr\endcsname
640     \csname\pytx@mcr\endcsname
641     \DePyMacro{p:\pytx@mcr}%
642   \else
643     \textbf{??}%
644     \PackageWarning{\pytx@packagename}{Missing autoprint content}%
645   \fi
646 }
647 \ifbool{\pytx@opt@stdout}{\let\pytx@InlineMacroprint\@empty}

```

`\pytx@InlineMacroprintFV` This macro brings in “printed” content that is brought in via `SaveVerbatim` (only inline console references at the moment). We must disable the macro in the event that the `debug` option is false.

```

648 \def\pytx@InlineMacroprintFV{%
649   \edef\pytx@mcr{\pytx@\pytx@type @\pytx@session @\pytx@group @\arabic{\pytx@counter}}%
650   \ifcsname FV@SV@\pytx@mcr\endcsname
651     \BUseVerbatim{\pytx@mcr}%
652     \DePyMacro{c:\pytx@mcr}%
653   \else
654     \textbf{??}%
655     \PackageWarning{\pytx@packagename}{Missing autoprint content}%
656   \fi
657 }
658 \ifbool{\pytx@opt@stdout}{\let\pytx@InlineMacroprint\@empty}

```

9.5.2 Inline command constructors

With the core inline macros complete, we are ready to create constructors for different kinds of inline commands. All of these constructors take a string and define an inline command named using that string as a base name. Two forms of each constructor are created, one that uses Pygments and one that does not. The Pygments variants have names ending in “Pyg”.

`\pytx@MakeInlinebFV` These macros creates inline block commands, which both typeset code and save it so that it may be executed. The base name of the command is stored in `\pytx@type`. A string representing the kind of command is stored in `\pytx@cmd`. Then `\pytx@SetContext` is used to set `\pytx@context` and `\pytx@SetGroup` is used to set `\pytx@group`. Macros for showing, saving, and printing are set to appropriate values. Then the core inline macros are invoked through `\pytx@Inline`.

```

659 \newcommand{\pytx@MakeInlinebFV}[1]{%
660   \expandafter\newcommand\expandafter{\csname #1b\endcsname}{%
661     \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
662     \DePythontex{cmd:#1b:ov:c}%

```

```

663     \xdef\pytx@type{#1}%
664     \edef\pytx@cmd{b}%
665     \pytx@SetContext
666     \pytx@SetGroup
667     \let\pytx@InlineShow\pytx@InlineShowFV
668     \let\pytx@InlineSave\pytx@InlineSaveCode
669     \let\pytx@InlinePrint\@empty
670     \pytx@Inline
671   }%
672 }%
673 \newcommand{\pytx@MakeInlinebPyg}[1]{%
674   \expandafter\newcommand\expandafter{\csname #1b\endcsname}{%
675     \xdef\pytx@type{#1}%
676     \edef\pytx@cmd{b}%
677     \pytx@SetContext
678     \pytx@SetGroup
679     \let\pytx@InlineShow\pytx@InlineShowPyg
680     \let\pytx@InlineSave\pytx@InlineSaveCode
681     \let\pytx@InlinePrint\@empty
682     \pytx@Inline
683   }%
684 }%

```

`\pytx@MakeInlinevFV` This macro creates inline verbatim commands, which only typeset code. `\pytx@type`, `\pytx@cmd`, `\pytx@context`, and `\pytx@group` are still set, for symmetry with other commands. They are not needed for `fancyvrb` typesetting, though. We use `\pytx@SetGroupVerb` to split verbatim content (`v` and `verb`) off into its own group. That way, verbatim content doesn't affect the instance numbers of executed code, and thus executed code is not affected by the addition or removal of verbatim content.

```

685 \newcommand{\pytx@MakeInlinevFV}[1]{%
686   \expandafter\newcommand\expandafter{\csname #1v\endcsname}{%
687     \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
688     \Depythontex{cmd:#1v:ov:c}%
689     \xdef\pytx@type{#1}%
690     \edef\pytx@cmd{v}%
691     \pytx@SetContext
692     \pytx@SetGroupVerb
693     \let\pytx@InlineShow\pytx@InlineShowFV
694     \let\pytx@InlineSave\@empty
695     \let\pytx@InlinePrint\@empty
696     \pytx@Inline
697   }%
698 }%
699 \newcommand{\pytx@MakeInlinevPyg}[1]{%
700   \expandafter\newcommand\expandafter{\csname #1v\endcsname}{%
701     \xdef\pytx@type{#1}%
702     \edef\pytx@cmd{v}%
703     \pytx@SetContext

```

```

704     \pytx@SetGroupVerb
705     \let\pytx@InlineShow\pytx@InlineShowPyg
706     \let\pytx@InlineSave\pytx@InlineSaveCode
707     \let\pytx@InlinePrint\@empty
708     \pytx@Inline
709 }%
710 }%

```

`\pytx@MakeInlincecFV` This macro creates inline code commands, which save code for execution but do not typeset it. If the code prints content, this content is inputted automatically if the package option `autoprint` is on. Since no code is typeset, there is no difference between the `fancyvrb` and `Pygments` forms.

```

711 \newcommand{\pytx@MakeInlincecFV}[1]{%
712   \expandafter\newcommand\expandafter{\csname #1c\endcsname}{%
713     \Depyhtontex{cmd:#1c:ov:p}%
714     \xdef\pytx@type{#1}%
715     \edef\pytx@cmd{c}%
716     \pytx@SetContext
717     \pytx@SetGroup
718     \let\pytx@InlineShow\@empty
719     \let\pytx@InlineSave\pytx@InlineSaveCode
720     \let\pytx@InlinePrint\pytx@InlineAutoprint
721     \pytx@Inline
722   }%
723 }%
724 \let\pytx@MakeInlincecPyg\pytx@MakeInlincecFV

```

`\pytx@MakeInlineFV` This macro creates plain inline commands, which save code and then bring in the output of `pytex.formatter(code)` (`pytex.formatter()` is the `formatter` function in Python sessions that is provided by `pyhtontex_utils*.py`). The Python output is saved in a `TeX` macro, and the macro is written to a file shared by all Python`TeX` sessions. This greatly reduces the number of external files needed. Since no code is typeset, there is no difference between the `fancyvrb` and `Pygments` forms.

```

725 \newcommand{\pytx@MakeInlineFV}[1]{%
726   \expandafter\newcommand\expandafter{\csname #1\endcsname}{%
727     \Depyhtontex{cmd:#1:ov:p}%
728     \xdef\pytx@type{#1}%
729     \edef\pytx@cmd{i}%
730     \pytx@SetContext
731     \pytx@SetGroup
732     \let\pytx@InlineShow\@empty
733     \let\pytx@InlineSave\pytx@InlineSaveCode
734     \let\pytx@InlinePrint\pytx@InlineMacroprint
735     \pytx@Inline
736   }%
737 }%
738 \let\pytx@MakeInlinePyg\pytx@MakeInlineFV

```

`\pytx@MakeInlineConsFV` This is the inline form for console types. It brings in `SaveVerbatim`.

```

\pytx@MakeInlineConsPyg 739 \newcommand{\pytx@MakeInlineConsFV}[1]{%
740     \expandafter\newcommand\expandafter{\cename #1\endcename}{%
741         \Depyhtontex{cmd:#1:ov:c}%
742         \xdef\pytx@type{#1}%
743         \edef\pytx@cmd{i}%
744         \pytx@SetContext
745         \pytx@SetGroup
746         \let\pytx@InlineShow\@empty
747         \let\pytx@InlineSave\pytx@InlineSaveCode
748         \let\pytx@InlinePrint\pytx@InlineMacroprintFV
749         \pytx@Inline
750     }%
751 }%
752 \let\pytx@MakeInlineConsPyg\pytx@MakeInlineConsFV

```

`\pythontexcustomc` This macro takes a single line of code and adds it to all sessions within a family. It is the inline version of the `pythontexcustomcode` environment.

```

753 \newcommand{\pythontexcustomc}[2][begin]{%
754     \Depyhtontex{cmd:pythontexcustomc:omv:p}%
755     \ifstrequal{#1}{begin}{-}{%
756         \ifstrequal{#1}{end}{-}{\PackageError{\pytx@packagename}%
757             {Invalid optional argument for \string\pythontexcustomc}{-}
758         }%
759     }%
760     \xdef\pytx@type{CC:#2:#1}%
761     \edef\pytx@cmd{c}%
762     \def\pytx@context{}%
763     \def\pytx@group{none}%
764     \let\pytx@InlineShow\@empty
765     \let\pytx@InlineSave\pytx@InlineSaveCode
766     \let\pytx@InlinePrint\@empty
767     \pytx@Inline[none]%
768 }%

```

`\setpythontexcustomcode` This macro is a holdover from 0.9beta3. It has been deprecated in favor of `\pythontexcustomc` and `pythontexcustomcode`.

```

769 \def\setpythontexcustomcode#1{%
770     \Depyhtontex{cmd:setpythontexcustomcode:mv:p}%
771     \PackageWarning{\pytx@packagename}{The command
772         \string\setpythontexcustomcode\space has been deprecated;
773         use \string\pythontexcustomc\space or pythontexcustomcode instead}%
774     \begingroup
775     \let\do\@makeother\dospecials
776     \catcode'\{=1
777     \catcode'\}=2
778     \catcode'\^M=10\relax
779     \pytx@SetCustomCode{#1}%
780 }

```

```

781 \long\def\pytx@SetCustomCode#1#2{%
782   \endgroup
783   \pythontexcustomec{#1}{pythontexcustocode=[#2];
784     exec('for expr in pythontexcustocode: exec(expr)');
785     del(pythontexcustocode)}
786 }
787 \@onlypreamble\setpythontexcustocode

```

9.6 Environments

The inline commands were all created using a common core set of macros, combined with short, command-specific constructors. In the case of environments, we do not have a common core set of macros. Each environment is coded separately, though there are similarities among environments. In the future, it may be worthwhile to attempt to consolidate the environment code base.

One of the differences between inline commands and environments is that environments may need to typeset code with line numbers. Each family of code needs to have its own line numbering (actually, its own numbering for code, verbatim, and console groups), and this line numbering should not overwrite any line numbering that may separately be in use by `fancyvrb`. To make this possible, we use a temporary counter extensively. When line numbers are used, `fancyvrb`'s line counter is copied into `pytx@FancyVerbLineTemp`, lines are numbered, and then `fancyvrb`'s line counter is restored from `pytx@FancyVerbLineTemp`. This keeps `fancyvrb` and Python_{TEX}'s line numbering separate, even though Python_{TEX} is using `fancyvrb` and its macros internally.

9.6.1 Block and verbatim environment constructors

We begin by creating `block` and `verb` environment constructors that use `fancyvrb`. Then we create Pygments versions.

`\pytx@FancyVerbGetLine` The `block` environment needs to both typeset code and save it so it can be executed. `fancyvrb` supports typesetting, but doesn't support saving at the same time. So we create a modified version of `fancyvrb`'s `\FancyVerbGetLine` macro which does. This is identical to the `fancyvrb` version, except that we add a line that writes to the code file. The material that is written is detokenized to avoid catcode issues and make unicode work correctly.

```

788 \begingroup
789 \catcode'\^M=\active
790 \gdef\pytx@FancyVerbGetLine#1^M{%
791   \@nil%
792   \FV@CheckEnd{#1}%
793   \ifx\@tempa\FV@EnvironName%
794     \ifx\@tempb\FV@@@CheckEnd\else\FV@BadEndError\fi%
795     \let\next\FV@EndScanning%
796   \else%
797     \def\FV@Line{#1}%
798     \def\next{\FV@PreProcessLine\FV@GetLine}%

```

```

799     \immediate\write\pytx@codefile{\detokenize{#1}}%
800     \fi%
801     \next}%
802 \endgroup

```

`\pytx@MakeBlockFV` Now we are ready to actually create block environments. This macro takes an environment base name $\langle name \rangle$ and creates a block environment $\langle name \rangle\text{block}$, using `fancyvrb`.

The block environment is a `Verbatim` environment, so we declare that with the `\VerbatimEnvironment` macro, which lets `fancyvrb` find the end of the environment correctly. We define the type, define the command, and set the context and group.

We need to check for optional arguments, so we begin a group and use `\obeylines` to make line breaks active. Then we check to see if the next char is an opening square bracket. If so, there is an optional argument, so we end our group and call the `\pytx@BeginBlockEnvFV` macro, which will capture the argument and finish preparing for the block content. If not, we end the group and call the same `\pytx@BeginBlockEnvFV` macro with an empty argument. The line breaks need to be active during this process because we don't care about content on the next line, including opening square brackets on the next line; we only care about content in the line on which the environment is declared, because only on that line should there be an optional argument. The problem is that since we are dealing with code, it is quite possible for there to be an opening square bracket at the beginning of the next line, so we must prevent that from being misinterpreted as an optional argument.

After the environment, we need to clean up several things. Much of this relates to what is done in the `\pytx@BeginBlockEnvFV` macro. The body of the environment is wrapped in a `Verbatim` environment, so we must end that. It is also wrapped in a group, so that `fancyvrb` settings remain local; we end the group. Then we define the name of the outfile for any printed content, so that it may be accessed by `\printpythontex` and company. Finally, we rearrange counters. The current code line number needs to be stored in `\pytx@linecount`, which was defined to be specific to the current type-session-group set. The `fancyvrb` line number needs to be set back to its original value from before the environment began, so that Python \TeX content does not affect the line numbering of `fancyvrb` content. Finally, the `\pytx@counter`, which keeps track of commands and environments within the current type-session-group set, needs to be incremented.

```

803 \newcommand{\pytx@MakeBlockFV}[1]{%
804     \expandafter\newenvironment{#1block}{%
805         \VerbatimEnvironment
806         \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
807         \Depyhtontex{env:#1block:ool:c}%
808         \DepyListing
809         \xdef\pytx@type{#1}%
810         \edef\pytx@cmd{block}%
811         \pytx@SetContext
812         \pytx@SetGroup

```

```

813     \begingroup
814     \obeylines
815     \@ifnextchar[{\endgroup\pytx@BeginBlockEnvFV}{\endgroup\pytx@BeginBlockEnvFV[]}]%
816   }%
817   {\end{Verbatim}}%
818   \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
819   \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
820   \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
821   \stepcounter{\pytx@counter}%
822   }%
823 }

```

`\pytx@BeginBlockEnvFV` This macro finishes preparations to actually begin the block environment. It captures the optional argument (or the empty argument supplied by default). If this argument is empty, then it sets the value of the argument to the default value. If not, then colons in the optional argument are replaced with underscores, and the modified argument is stored in `\pytx@session`. Colons are replaced with underscores because session names must be suitable for file names, and colons are generally not allowed in file names. However, we want to be able to *enter* session names containing colons, since colons provide a convenient method of indicating relationships, and are commonly used in L^AT_EX labels. For example, we could have a session named `plots:specialplot`.

Once the session is established, we are free to define the counter for the current type-session-group, and make sure it exists. We also define the counter that will keep track of line numbers for the current type-session-group, and make sure it exists. Then we do some counter trickery. We don't want `fancyvrb` line counting to be affected by Python_TE_X content, so we store the current line number held by `FancyVerbLine` in `pytx@FancyVerbLineTemp`; we will restore `FancyVerbLine` to this original value at the end of the environment. Then we set `FancyVerbLine` to the appropriate line number for the current type-session-group. This provides proper numbering continuity between different environments within the same type-session-group.

Next, we write environment information to the code file, now that all the necessary information is assembled. We begin a group, to keep some things local. We `\let` a `fancyvrb` macro to our custom macro. We set `fancyvrb` settings to those of the current type using `\pytx@FVSet`. Once this is done, we are finally ready to start the `Verbatim` environment. Note that the `Verbatim` environment will capture a second optional argument delimited by square brackets, if present, and apply this argument as `fancyvrb` formatting. Thus, the environment actually takes up to two optional arguments, but if you want to use `fancyvrb` formatting, you must supply an empty (default session) or named (custom session) optional argument for the Python_TE_X code.

```

824 \def\pytx@BeginBlockEnvFV[#1]{%
825   \ifstrempy{#1}{\edef\pytx@session{default}}{\StrSubstitute{#1}{:}{-}[\pytx@session]}%
826   \xdef\pytx@counter{\pytx@pytx@type @\pytx@session @\pytx@group}%
827   \pytx@CheckCounter{\pytx@counter}%
828   \edef\pytx@linecount{\pytx@counter @line}%

```

```

829 \pytx@CheckCounter{\pytx@linecount}%
830 \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
831 \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
832 \pytx@WriteCodefileInfo
833 \let\FancyVerbGetLine\pytx@FancyVerbGetLine
834 \pytx@FVSet
835 \begin{Verbatim}%
836 }

```

`\pytx@MakeVerbFV` The verbatim environments only typeset code; they do not save it for execution. Thus, we just use a standard `fancyvrb` environment with a few enhancements.

As in the `block` environment, we declare that we are using a `Verbatim` environment, define type and command, set context and group (note the use of the `Verb` group), and take care of optional arguments before calling a macro to wrap things up (in this case, `\pytx@BeginVerbEnvFV`). Currently, much of the saved information is unused, but it is provided to maintain parallelism with the `block` environment.

Ending the environment involves ending the `Verbatim` environment begun by `\pytx@BeginVerbEnvFV`, ending the group that kept `fancyvrb` settings local, and resetting counters. We define a `stdfile` and step the counter, even though there will never actually be any output to pull in, to force `\printpythontex` and company to be used immediately after the code they refer to and to maintain parallelism.

```

837 \newcommand{\pytx@MakeVerbFV}[1]{%
838   \expandafter\newenvironment{#1verbatim}{%
839     \VerbatimEnvironment
840     \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
841     \Depyhtontex{env:#1verbatim:oo|:c}%
842     \DepyListing
843     \xdef\pytx@type{#1}%
844     \edef\pytx@cmd{verbatim}%
845     \pytx@SetContext
846     \pytx@SetGroupVerb
847     \begingroup
848     \obeylines
849     \@ifnextchar[{\endgroup\pytx@BeginVerbEnvFV}{\endgroup\pytx@BeginVerbEnvFV []}%
850   }%
851   {\end{Verbatim}}%
852   \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
853   \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
854   \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
855   \stepcounter{\pytx@counter}%
856 }%
857 }

```

`\pytx@BeginVerbEnvFV` This macro captures the optional argument of the environment (or the default empty argument that is otherwise supplied). If the argument is empty, it assigns a default value; otherwise, it substitutes underscores for colons in the argument.

The argument is assigned to `\pytx@session`. A line counter is created, and its existence is checked. We do the standard line counter trickery. Then we begin a group to keep `fancyvrb` settings local, invoke the settings via `\pytx@FVSet`, and begin the `Verbatim` environment.

```

858 \def\pytx@BeginVerbEnvFV[#1]{%
859   \ifstrempy{#1}{\edef\pytx@session{default}}{\StrSubstitute{#1}{:}{-}[\pytx@session]}%
860   \xdef\pytx@counter{\pytx@type @\pytx@session @\pytx@group}%
861   \pytx@CheckCounter{\pytx@counter}%
862   \edef\pytx@linecount{\pytx@counter @line}%
863   \pytx@CheckCounter{\pytx@linecount}%
864   \setcounter{\pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
865   \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
866   \pytx@FVSet
867   \begin{Verbatim}%
868 }

```

Now for the Pygments forms of `block` and `verb`. Since all code must be saved now (either to be executed or processed by Pygments, or both), the environment code may be simplified compared to the non-Pygments case.

`\pytx@MakePygEnv` The `block` and `verb` environments are created via the same macro. The `\pytx@MakePygEnv` macro takes two arguments: first, the code type, and second, the environment (`block` or `verb`). The reason for using the same macro is that both must now save their code externally, and bring back the result typeset by Pygments. Thus, on the \LaTeX side, their behavior is identical. The only difference is on the Python side, where the `block` code is executed and thus there may be output available via `\printpythontex` and company.

The actual workings of the macro are a combination of those of the non-Pygments macros, so please refer to those for details. The only exception is the code for bringing in Pygments output, but this is done using almost the same approach as that used for the inline Pygments commands. There are two differences: first, the `block` and `verb` environments use `\UseVerbatim` rather than `\BUseVerbatim`, since they are not typesetting code inline; and second, they accept a second, optional argument containing `fancyvrb` commands and this is used in typesetting the saved content. Any `fancyvrb` commands are saved in `\pytx@fvopttmp` by `\pytx@BeginEnvPyg@i`, and then used when the code is typeset.

Note that the positioning of all the `FancyVerbLine` trickery in what follows is significant. Saving the `FancyVerbLine` counter to a temporary counter before the beginning of `VerbatimOut` is important, because otherwise the `fancyvrb` numbering can be affected.

```

869 \newcommand{\pytx@MakePygEnv}[2]{%
870   \expandafter\newenvironment{#1#2}{%
871     \VerbatimEnvironment
872     \xdef\pytx@type{#1}%
873     \edef\pytx@cmd{#2}%
874     \pytx@SetContext

```

```

875     \ifstrequal{#2}{block}{\pytx@SetGroup}{
876     \ifstrequal{#2}{verbatim}{\pytx@SetGroupVerb}{
877     \begingroup
878     \obeylines
879     \@ifnextchar[{\endgroup\pytx@BeginEnvPyg}{\endgroup\pytx@BeginEnvPyg[]}%
880 }%
881 {\end{VerbatimOut}}%
882 \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
883 \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
884 \pytx@FVSet
885 \ifdefstring{\pytx@fvopttmp}{-}{\expandafter\fvset\expandafter{\pytx@fvopttmp}}%
886 \ifcsname FV@SV@\pytx@counter @\arabic{\pytx@counter}\endcsname
887   \UseVerbatim{\pytx@counter @\arabic{\pytx@counter}}%
888 \else
889   \InputIfFileExists{\pytx@outdir/\pytx@stdfile.pygtex}{%
890     {\textbf{??~\pytx@packagename~??}}%
891     \PackageWarning{\pytx@packagename}{Non-existent Pygments content}}%
892 \fi
893 \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
894 \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
895 \stepcounter{\pytx@counter}%
896 }%
897 }%

```

`\pytx@BeginEnvPyg` This macro finishes preparing for the content of a verb or block environment with Pygments content. It captures an optional argument corresponding to the session name and sets up instance and line counters. Finally, it calls an additional macro that handles the possibility of a second optional argument.

```

898 \def\pytx@BeginEnvPyg[#1]{%
899   \ifstreempty{#1}{\edef\pytx@session{default}}{\StrSubstitute{#1}{:}{-}[\pytx@session]}%
900   \xdef\pytx@counter{\pytx@type @\pytx@session @\pytx@group}%
901   \pytx@CheckCounter{\pytx@counter}%
902   \edef\pytx@linecount{\pytx@counter @line}%
903   \pytx@CheckCounter{\pytx@linecount}%
904   \pytx@WriteCodefileInfo
905   \begingroup
906   \obeylines
907   \@ifnextchar[{\endgroup\pytx@BeginEnvPyg@i}{\endgroup\pytx@BeginEnvPyg@i[]}%
908 }%

```

`\pytx@BeginEnvPyg@i` This macro captures a second optional argument, corresponding to `fancyvrb` options. Note that not all `fancyvrb` options may be passed to saved content when it is actually used, particularly those corresponding to how the content was read in the first place (for example, command characters). But at least most formatting options such as line numbering work fine. As with the non-Pygments environments, `\begin{VerbatimOut}` doesn't take a second mandatory argument, since we are using a custom version and don't need to specify the file in which Verbatim content is saved. It is important that the `FancyVerbLine` saving be done here; if

it is done later, after the end of `VerbatimOut`, then numbering can be off in some circumstances (for example, a single `pyverbatim` between two `Verbatim`'s).

```

909 \def\pytx@BeginEnvPyg@i[#1]{%
910   \def\pytx@fvopttmp{#1}%
911   \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
912   \let\FVB@VerbatimOut\pytx@FVB@VerbatimOut
913   \let\FVE@VerbatimOut\pytx@FVE@VerbatimOut
914   \begin{VerbatimOut}%
915 }%

```

Since we are using the same code to create both `block` and `verb` environments, we now create a specific macro for creating each case, to make usage equivalent to that for the non-Pygments case.

`\pytx@MakeBlockPyg` The block environment is constructed via the `\pytx@MakePygEnv` macro.

```

916 \newcommand{\pytx@MakeBlockPyg}[1]{\pytx@MakePygEnv{#1}{block}}

```

`\pytx@MakeVerbPyg` The verb environment is constructed likewise.

```

917 \newcommand{\pytx@MakeVerbPyg}[1]{\pytx@MakePygEnv{#1}{verbatim}}

```

9.6.2 Code environment constructor

The `code` environment merely saves code to the code file; nothing is typeset. To accomplish this, we use a slightly modified version of `fancyvrb`'s `VerbatimOut`.

`\pytx@WriteDetok` We can use `fancyvrb` to capture the code, but we will need a way to write the code in detokenized form. This is necessary so that `TEX` doesn't try to process the code as it is written, which would generally be disastrous.

```

918 \def\pytx@WriteDetok#1{%
919   \immediate\write\pytx@codefile{\detokenize{#1}}}%

```

`\pytx@FVB@VerbatimOut` We need a custom version of the macro that begins `VerbatimOut`. We don't need `fancyvrb`'s key values, and due to our use of `\detokenize` to write content, we don't need its space and tab treatment either. We do need `fancyvrb` to write to our code file, not the file to which it would write by default. And we don't need to open any files, because the code file is already open. These last two are the only important differences between our version and the original `fancyvrb` version. Since we don't need to write to a user-specified file, we don't require the mandatory argument of the original macro.

```

920 \def\pytx@FVB@VerbatimOut{%
921   \@bsphack
922   \begingroup
923   \let\FV@ProcessLine\pytx@WriteDetok
924   \let\FV@FontScanPrep\relax
925   \let\@noligs\relax
926   \FV@Scan}%

```

```

\pytx@FVE@VerbatimOut Similarly, we need a custom version of the macro that ends VerbatimOut. We
                        don't want to close the file to which we are saving content.
927 \def\pytx@FVE@VerbatimOut{\endgroup\@esphack}%

\pytx@EnvAutoprint We also need a macro for bringing in autoprint content. This is a separate macro
                    so that it can be easily disabled by the package option debug. We wait until the
                    beginning of the document to create the real macro, since any code commands
                    and environments in the preamble shouldn't be printing and in any case we can't
                    know what the outputdir is until the beginning of the document.
928 \let\pytx@EnvAutoprint\@empty
929 \AtBeginDocument{
930   \def\pytx@EnvAutoprint{%
931     \ifbool{pytx@opt@autoprint}{%
932       \InputIfFileExists{\pytx@outputdir/\pytx@stdfile.stdout}%
933       {\DePyFile{p:\pytx@outputdir/\pytx@stdfile.stdout}}{}}{}%
934   }
935   \ifbool{pytx@opt@stdout}{\let\pytx@EnvAutoprint\@empty}
936 }

\pytx@MakeCodeFV Now that the helper macros for the code environment have been defined, we are
                  ready to create the macro that makes code environments. Everything at the
                  beginning of the environment is similar to the block and verb environments.

                  After the environment, we need to close the VerbatimOut environment begun
                  by \pytx@BeginCodeEnv@i and end the group it began. We define the outfile,
                  and bring in any printed content if the autoprint setting is on. We must still
                  perform some FancyVerbLine trickery to prevent the fancyvrb line counter from
                  being affected by writing content! Finally, we step the counter.
937 \newcommand{\pytx@MakeCodeFV}[1]{%
938   \expandafter\newenvironment{#1code}{%
939     \VerbatimEnvironment
940     \DePythontex{env:#1code:oo|:p}%
941     \xdef\pytx@type{#1}%
942     \edef\pytx@cmd{code}%
943     \pytx@SetContext
944     \pytx@SetGroup
945     \begingroup
946     \obeylines
947     \@ifnextchar[{\endgroup\pytx@BeginCodeEnv}{\endgroup\pytx@BeginCodeEnv[]}%
948   }%
949   {\end{VerbatimOut}}%
950   \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
951   \pytx@EnvAutoprint
952   \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
953   \stepcounter{\pytx@counter}%
954   }%
955 }%

\pytx@BeginCodeEnv This macro finishes setting things up before the code environment contents. It
                    processes the optional argument, defines a counter and checks its existence, writes

```

info to the code file, and then calls the `\pytx@BeginCodeEnv@i` macro. This macro is necessary so that the environment can accept two optional arguments. Since the `block` and `verb` environments can accept two optional arguments (the first is the name of the session, the second is `fancyvrb` options), the code environment also should be able to, to maintain parallelism (for example, `pyblock` should be able to be swapped with `pycode` without changing environment arguments—it should just work). However, `VerbatimOut` doesn't take an optional argument. So we need to capture and discard any optional argument, before starting `VerbatimOut`.

```

956 \def\pytx@BeginCodeEnv[#1]{%
957   \ifstrempy{#1}{\edef\pytx@session{default}}{\StrSubstitute{#1}{:}{-}[\pytx@session]}%
958   \xdef\pytx@counter{\pytx@\pytx@type @\pytx@session @\pytx@group}%
959   \pytx@CheckCounter{\pytx@counter}%
960   \pytx@WriteCodefileInfo
961   \begingroup
962   \obeylines
963   \@ifnextchar[{\endgroup\pytx@BeginCodeEnv@i}{\endgroup\pytx@BeginCodeEnv@i []}%
964 }%

```

`\pytx@BeginCodeEnv@i` As described above, this macro captures a second optional argument, if present, and then starts the `VerbatimOut` environment. Note that `VerbatimOut` does not have a mandatory argument, because we are invoking our custom `\pytx@FVB@VerbatimOut` macro. The default `fancyvrb` macro needs an argument to tell it the name of the file to which to save the verbatim content. But in our case, we are always writing to the same file, and the custom macro accounts for this by not having a mandatory file name argument. We must perform the typical `FancyVerbLine` trickery, to prevent the `fancyvrb` line counter from being affected by **writing** content!

```

965 \def\pytx@BeginCodeEnv@i[#1]{%
966   \setcounter{\pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
967   \let\FVB@VerbatimOut\pytx@FVB@VerbatimOut
968   \let\FVE@VerbatimOut\pytx@FVE@VerbatimOut
969   \begin{VerbatimOut}%
970 }%

```

`\pytx@MakeCodePyg` Since the code environment simply saves code for execution and typesets nothing, the Pygments version is identical to the non-Pygments version, so we simply let the former to the latter.

```

971 \let\pytx@MakeCodePyg\pytx@MakeCodeFV

```

`pythontexcustocode` This environment is used for adding custom code to all sessions within a command and environment family. It is the environment equivalent of the inline command `\pythontexcustomc`.

```

972 \newenvironment{pythontexcustocode}[2][begin]{%
973   \VerbatimEnvironment
974   \Deptyhontex{env:pythontexcustocode:om:n}%
975   \ifstrequal{#1}{begin}{}{%
976     \ifstrequal{#1}{end}{}{\PackageError{\pytx@packagename}%
977       {Invalid optional argument for pythontexcustocode}{%
978       }}%

```

```

979 }%
980 \xdef\pytx@type{CC:#2:#1}%
981 \edef\pytx@cmd{code}%
982 \def\pytx@context{}%
983 \def\pytx@group{none}%
984 \pytx@BeginCodeEnv[none]}%
985 {\end{VerbatimOut}}%
986 \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}%
987 \stepcounter{\pytx@counter}%
988 }%

```

9.6.3 Console environment constructor

The `console` environment needs to write all code contained in the environment to the code file, and then bring in the console output.

An environment suffix is not enforced for flexibility. For Python, the convention is that `console` type names will end with `con`, and then the environment will use the suffix `sole`. For example, the `pycon` type has the `pyconsole` environment.

`\pytx@MakeConsoleFV`

```

989 \newcommand{\pytx@MakeConsFV}[2]{%
990   \expandafter\newenvironment{#1#2}{%
991     \VerbatimEnvironment
992     \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
993     \Depyhontex{env:#1#2:ool:c}%
994     \DepyListing
995     \xdef\pytx@type{#1}%
996     \edef\pytx@cmd{console}%
997     \pytx@SetContext
998     \pytx@SetGroup
999     \begingroup
1000     \obeylines
1001     \@ifnextchar[{\endgroup\pytx@BeginConsEnvFV}{\endgroup\pytx@BeginConsEnvFV []}%
1002   }%
1003   {\end{VerbatimOut}}%
1004   \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
1005   \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
1006   \pytx@FVSet
1007   \ifdefstring{\pytx@fvopttmp}{-}{\expandafter\fvset\expandafter{\pytx@fvopttmp}}%
1008   \ifcsname FV@SV@\pytx@counter @\arabic{\pytx@counter}\endcsname
1009     \UseVerbatim{\pytx@counter @\arabic{\pytx@counter}}%
1010     \DepyMacro{c:\pytx@counter @\arabic{\pytx@counter}}%
1011   \else
1012     \InputIfFileExists{\pytx@outputdir/\pytx@stdfile.tex}%
1013     {\DepyFile{c:\pytx@outputdir/\pytx@stdfile.tex}}%
1014     {\textbf{??~\pytx@packagename~??}}%
1015     \PackageWarning{\pytx@packagename}{Non-existent console content}}%
1016   \fi
1017   \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%

```

```

1018 \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}%
1019 \stepcounter{pytx@counter}%
1020 }%
1021 }

```

\pytx@BeginConsEnvFV

```

1022 \def\pytx@BeginConsEnvFV[#1]{%
1023 \ifstrempy{#1}{\edef\pytx@session{default}}{\StrSubstitute{#1}{:}{-}[\pytx@session]}%
1024 \xdef\pytx@counter{pytx@\pytx@type @\pytx@session @\pytx@group}%
1025 \pytx@CheckCounter{\pytx@counter}%
1026 \edef\pytx@linecount{\pytx@counter @line}%
1027 \pytx@CheckCounter{\pytx@linecount}%
1028 \pytx@WriteCodefileInfo
1029 \begingroup
1030 \obeylines
1031 \@ifnextchar[{\endgroup\pytx@BeginConsEnvFV@i}{\endgroup\pytx@BeginConsEnvFV@i []}%
1032 }%

```

\pytx@BeginConsEnvFV@i

```

1033 \def\pytx@BeginConsEnvFV@i[#1]{%
1034 \def\pytx@fvopttmp{#1}%
1035 \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
1036 \let\FVB@VerbatimOut\pytx@FVB@VerbatimOut
1037 \let\FVE@VerbatimOut\pytx@FVE@VerbatimOut
1038 \begin{VerbatimOut}%
1039 }%

```

\pytx@MakeConsPyg The Pygments version of the console environment is identical to the fancyvrb version, except that .pygtex rather than .tex files are brought in.

```

1040 \newcommand{\pytx@MakeConsPyg}[2]{%
1041 \expandafter\newenvironment{#1#2}{%
1042 \VerbatimEnvironment
1043 \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
1044 \Depyhtextex{env:#1#2:oo|c}%
1045 \DepyListing
1046 \xdef\pytx@type{#1}%
1047 \edef\pytx@cmd{console}%
1048 \pytx@SetContext
1049 \pytx@SetGroup
1050 \begingroup
1051 \obeylines
1052 \@ifnextchar[{\endgroup\pytx@BeginConsEnvFV}{\endgroup\pytx@BeginConsEnvFV []}%
1053 }%
1054 {\end{VerbatimOut}}%
1055 \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
1056 \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
1057 \pytx@FVSet
1058 \ifdefstring{\pytx@fvopttmp}{-}{\expandafter\fvset\expandafter{\pytx@fvopttmp}}%
1059 \ifcsname FV@SV@\pytx@counter @\arabic{\pytx@counter}\endcsname

```

```

1060     \UseVerbatim{\pytx@counter @\arabic{\pytx@counter}}%
1061     \DePyMacro{c:\pytx@counter @\arabic{\pytx@counter}}%
1062   \else
1063     \InputIfFileExists{\pytx@outputdir/\pytx@stdfile.pygtex}%
1064     {\DePyFile{c:\pytx@outputdir/\pytx@stdfile.pygtex}}%
1065     {\textbf{??~\pytx@packagename~??}}%
1066     \PackageWarning{\pytx@packagename}{Non-existent console content}}%
1067   \fi
1068   \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
1069   \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
1070   \stepcounter{\pytx@counter}%
1071   }%
1072 }

```

9.7 Constructors for command and environment families

Everything is now in place to create commands and environments, with and without Pygments usage. To make all of this more readily usable, we need macros that will create a whole family of commands and environments at once, using a base name. For example, we need a way to create all commands and environments based off of the `py` base name.

`\makepythontexfamily` This macro creates a family of commands. It needs a some `pgfkeys` to handle the optional arguments. The actual creation of all non-code commands and environments is delayed using `\AtBeginDocument`, so that the user has the option to choose whether `fancyvrb` or Pygments is used for the family.

```

1073 \pgfkeys{
1074   /PYTX/family/.is family,
1075   /PYTX/family,
1076   prettyprinter/.estore in = \pytx@tmp@pprinter,
1077   pyglexer/.estore in = \pytx@tmp@pyglexer,
1078   pygopt/.estore in = \pytx@tmp@pygopt,
1079   console/.estore in = \pytx@tmp@console,
1080   default/.style = {prettyprinter=auto, pyglexer=text, pygopt={}, console=false}
1081 }
1082 \def\pytx@MakeFamilyFV#1{%
1083   \pytx@MakeInlineFV{#1}%
1084   \pytx@MakeInlinevFV{#1}%
1085   \pytx@MakeInlineFV{#1}%
1086   \pytx@MakeBlockFV{#1}%
1087   \pytx@MakeVerbFV{#1}%
1088 }
1089 \def\pytx@MakeFamilyPyg#1{%
1090   \ifbool{\pytx@opt@pyginline}%
1091     {\pytx@MakeInlinePyg{#1}\pytx@MakeInlinevPyg{#1}}%
1092     {\pytx@MakeInlineFV{#1}\pytx@MakeInlinevFV{#1}}%
1093   \pytx@MakeInlinePyg{#1}%
1094   \pytx@MakeBlockPyg{#1}%
1095   \pytx@MakeVerbPyg{#1}%

```

```

1096     \booltrue{pytx@usedpygments}%
1097     \AtEndDocument{\immediate\write\pytx@codefile{pygfamily=#1|%
1098         \csname pytx@pyglexer@#1\endcsname|%
1099         \csname pytx@pygopt@#1\endcsname}%
1100     }%
1101 }
1102 \def\pytx@MakeFamilyFVCons#1{%
1103     \pytx@MakeInlineFV{#1}%
1104     \pytx@MakeInlineConsFV{#1}%
1105     \pytx@MakeConsFV{#1}{sole}%
1106     \pytx@MakeVerbFV{#1}%
1107 }
1108 \def\pytx@MakeFamilyPygCons#1{%
1109     \ifbool{pytx@opt@pyginline}%
1110         {\pytx@MakeInlinevPyg{#1}}%
1111         {\pytx@MakeInlinevFV{#1}}%
1112     \pytx@MakeInlineConsPyg{#1}%
1113     \pytx@MakeConsPyg{#1}{sole}%
1114     \pytx@MakeVerbPyg{#1}%
1115     \booltrue{pytx@usedpygments}%
1116     \AtEndDocument{\immediate\write\pytx@codefile{pygfamily=#1|%
1117         \csname pytx@pyglexer@#1\endcsname|%
1118         \csname pytx@pygopt@#1\endcsname}%
1119     }%
1120 }
1121 \newcommand{\makepythontexfamily}[2] [] {%
1122     \IfBeginWith{#2}{PYG}%
1123         {\PackageError{\pytx@packagename}%
1124             {Attempt to create macros with reserved prefix PYG}{}}%
1125     \pgfkeys{/PYTX/family, default, #1}
1126     \expandafter\xdef\csname pytx@macroformatter@#2\endcsname{\pytx@tmp@pprinter}
1127     \expandafter\xdef\csname pytx@fvsettings@#2\endcsname{}
1128     \expandafter\xdef\csname pytx@pyglexer@#2\endcsname{\pytx@tmp@pyglexer}
1129     \expandafter\xdef\csname pytx@pygopt@#2\endcsname{\pytx@tmp@pygopt}
1130     \expandafter\xdef\csname pytx@console@#2\endcsname{\pytx@tmp@console}
1131     \pytx@MakeInlineFV{#2}
1132     \pytx@MakeCodeFV{#2}
1133     \AtBeginDocument{%
1134         \ifcsstring{pytx@macroformatter@#2}{auto}{%
1135             \ifbool{pytx@opt@pygments}%
1136                 {\ifcsstring{pytx@console@#2}{true}%
1137                     {\pytx@MakeFamilyPygCons{#2}}{\pytx@MakeFamilyPyg{#2}}}%
1138                 {\ifcsstring{pytx@console@#2}{true}%
1139                     {\pytx@MakeFamilyFVCons{#2}}{\pytx@MakeFamilyFV{#2}}}%
1140             }{}%
1141         \ifcsstring{pytx@macroformatter@#2}{fancyvrb}%
1142             {\ifcsstring{pytx@console@#2}{true}%
1143                 {\pytx@MakeFamilyFVCons{#2}}{\pytx@MakeFamilyFV{#2}}}{}%
1144         \ifcsstring{pytx@macroformatter@#2}{pygments}%
1145             {\ifcsstring{pytx@console@#2}{true}%

```

```

1146             {\pytx@MakeFamilyPygCons{#2}}{\pytx@MakeFamilyPyg{#2}}{}}}%
1147     }%
1148 }
1149 \@onlypreamble\makepythontexfamily

```

`\setpythontexpygllexer` We need to be able to reset the lexer associated with a family after the family has already been created.

```

1150 \newcommand{\setpythontexpygllexer}[2] []{%
1151     \Depyhtontex{cmd:setpythontexpygllexer:om:n}%
1152     \ifstrepty{#1}{\def\pytx@pygllexer{#2}}{%
1153         \ifcsname pytx@pygllexer@#1\endcsname
1154             \expandafter\xdef\csname pytx@pygllexer@#1\endcsname{#2}%
1155         \else
1156             \PackageError{\pytx@packagename}%
1157                 {Cannot modify a non-existent family}{}%
1158         \fi
1159     }%
1160 }%
1161 \@onlypreamble\setpythontexpygllexer

```

`\setpythontexpygopt` The user may wish to modify the Pygments options associated with a family. This macro takes two arguments: first, the family base name; and second, the Pygments options to associate with the family. This macro is particularly useful in changing the Pygments style of default command and environment families.

Due to the implementation (and also in the interest of keeping typesetting consistent), the Pygments style for a family must remain constant throughout the document. Thus, we only allow changes to the style in the preamble.

```

1162 \newcommand{\setpythontexpygopt}[2] []{%
1163     \Depyhtontex{cmd:setpythontexpygopt:om:n}%
1164     \ifstrepty{#1}{\def\pytx@pygopt{#2}}{%
1165         \ifcsname pytx@pygopt@#1\endcsname
1166             \expandafter\xdef\csname pytx@pygopt@#1\endcsname{#2}%
1167         \else
1168             \PackageError{\pytx@packagename}%
1169                 {Cannot modify Pygments options for a non-existent family}{}%
1170         \fi
1171     }%
1172 }
1173 \@onlypreamble\setpythontexpygopt

```

`\setpythontexprettyprinter` We need to be able to reset the pretty printer used by a family among the options `auto`, `fancyvrb`, and `pygments`.

```

1174 \newcommand{\setpythontexprettyprinter}[2] []{%
1175     \Depyhtontex{cmd:setpythontexprettyprinter:om:n}%
1176     \ifstrepty{#1}{%
1177         \ifstrequal{#2}{fancyvrb}{\boolfalse{pytx@opt@pygments}}%
1178         \ifstrequal{#2}{pygments}{\booltrue{pytx@opt@pygments}}%
1179     }{%
1180         \ifcsname pytx@macroformatter@#1\endcsname

```

```

1181         \ifbool{pytx@opt@depythontex}{}{%
1182             \expandafter\xdef\csname pytx@macroformatter@#1\endcsname{#2}}
1183     \else
1184         \PackageError{\pytx@packagename}%
1185             {Cannot modify a family that does not exist or does not allow formatter choices.
1186             {Create the family with \string\makepythontexfamily}}%
1187     \fi
1188 }%
1189 }
1190 \@onlypreamble\setpythontexprettyprinter

```

9.8 Default commands and environment families

We are finally prepared to create the default command and environment families. We create a basic Python family with the base name `py`. We also create customized Python families for the SymPy package, using the base name `sympy`, and for the pylab module, using the base name `pylab`. All of these are created with a `console` environment.

All of these command and environment families are created conditionally, depending on whether the package option `pygments` is used, via `\makepythontexfamily`. We recommend that any custom families created by the user be constructed in the same manner.

```

1191 \makepythontexfamily[pyglexer=python]{py}
1192 \makepythontexfamily[pyglexer=pycon, console=true]{pycon}
1193 \makepythontexfamily[pyglexer=python]{sympy}
1194 \makepythontexfamily[pyglexer=pycon, console=true]{sympycon}
1195 \makepythontexfamily[pyglexer=python]{pylab}
1196 \makepythontexfamily[pyglexer=pycon, console=true]{pylabcon}

```

We also need to create any additional families specified via the `usefamily` package option.⁴⁵

```

1197 \renewcommand{\do}[1]{%
1198     \ifstrequal{#1}{ruby}{\makepythontexfamily[pyglexer=ruby]{ruby}}{}%
1199     \ifstrequal{#1}{rb}{\makepythontexfamily[pyglexer=ruby]{rb}}{}%
1200     \ifstrequal{#1}{julia}{\makepythontexfamily[pyglexer=julia]{julia}}{}%
1201     \ifstrequal{#1}{jl}{\makepythontexfamily[pyglexer=julia]{jl}}{}%
1202 }
1203 \expandafter\docsvlist\expandafter{\pytx@families}

```

9.9 Listings environment

`fancyvrb`, especially when combined with `Pygments`, provides most of the formatting options we could want. However, it simply typesets code within the flow of the document and does not provide a floating environment. So we create a floating environment for code listings via the `newfloat` package.

⁴⁵The loop here is accomplished via `etoolbox`. `pgffor` might be an alternative, but making definitions global requires trickery.

It is most logical to name this environment `listing`, but that is already defined by the `minted` package (although `PythonTeX` and `minted` are probably not likely to be used together, due to overlapping features). Furthermore, the `listings` package specifically avoided using the name `listing` for an environment due to the use of this name by other packages.

We have chosen to make a compromise. We create a macro that creates a float environment with a custom name for listings. If this macro is invoked, then a float environment for listings is created and nothing else is done. If it is not invoked, the package attempts to create an environment called `listing` at the beginning of the document, and issues a warning if another macro with that name already exists. This approach makes the logical `listing` name available in most cases, and provides the user with a simple fallback in the event that another package defining `listing` must be used alongside `PythonTeX`.

`\setpythontexlistingenv` We define a bool `pytx@listingenv` that keeps track of whether a listings environment has been created. Then we define a macro that creates a floating environment with a custom name, with appropriate settings for a listing environment. We only allow this macro to be used in the preamble, since later use would wreak havoc.

```

1204 \newbool{pytx@listingenv}
1205 \def\setpythontexlistingenv#1{%
1206     \Depyhtontex{cmd:setpythontexlistingenv:m:n}%
1207     \DeclareFloatingEnvironment[fileext=lopytx,listname={List of Listings},name=Listing]{#1}
1208     \booltrue{pytx@listingenv}
1209 }
1210 \@onlypreamble\setpythontexlistingenv

```

At the beginning of the document, we issue a warning if the `listing` environment needs to be created but cannot be due to a pre-existing macro (and no version with a custom name has been created). Otherwise, we create the `listing` environment.

```

1211 \AtBeginDocument{
1212     \ifcsname listing\endcsname
1213     \ifbool{pytx@listingenv}{}%
1214     {\PackageWarning{pytx@packagename}%
1215         {A "listing" environment already exists \MessageBreak
1216         \pytx@packagename\space will not create one \MessageBreak
1217         Use \string\setpythontexlistingenv to create a custom listing environment}}%
1218     \else
1219     \ifbool{pytx@listingenv}{\DeclareFloatingEnvironment[fileext=lopytx]{listing}}
1220     \fi
1221 }

```

9.10 Pygments for general code typesetting

After all the work that has gone into `PythonTeX` thus far, it would be a pity not to slightly expand the system to allow Pygments typesetting of any language Pygments supports. While `PythonTeX` currently can only *execute* Python code,

it is relatively easy to add support for *highlighting* any language supported by Pygments. We proceed to create a `\pygment` command, a `pygments` environment, and an `\inputpygments` command that do just this. The functionality of these is very similar to that provided by the `minted` package.

Both the commands and the environment are created in two forms: one that actually uses Pygments, which is the whole point in the first place; and one that uses `fancyvrb`, which may speed compilation or make editing faster since `pythontex.py` need not be invoked. By default, the two forms are switched between based on the package `pygments` option, but this may be easily modified as described below.

The Pygments commands and environment operate under the code type `PYG<lexer name>`. This allows Pygments typesetting of general code to proceed with very few additions to `pythontex.py`; in most situations, the Pygments code types behave just like standard `PythonTeX` types that don't execute any code. Due to the use of the `PYG` prefix for all Pygments content, the use of this prefix is not allowed at the beginning of a base name for standard `PythonTeX` command and environment families.

We have previously used the suffix `Pyg` to denote macro variants that use Pygments rather than `fancyvrb`. We continue that practice here. To distinguish the special Pygments typesetting macros from the regular `PythonTeX` macros, we use `Pygments` in the macro names, in addition to any `Pyg` suffix

9.11 Pygments utilities macros

`\pytx@CheckPygmentsInit` We need to see if macros exist for storing Pygments `fv` settings and `pygopt`. If not, create them, and make sure they will be written to file.

```

1222 \def\pytx@CheckPygmentsInit#1{%
1223     \ifcsname pytx@fvsettings@PYG#1\endcsname\else
1224         \expandafter\gdef\csname pytx@fvsettings@PYG#1\endcsname{%
1225             \expandafter\gdef\csname pytx@pygopt@PYG#1\endcsname{%
1226                 \AtEndDocument{\immediate\write\pytx@codefile{pygfamily=PYG#1|#1|
1227                     \csname pytx@pygopt@PYG#1\endcsname}}%
1228             \fi
1229 }
```

9.11.1 Inline Pygments command

`\pytx@MakePygmentsInlineFV` These macros create an inline command. They reuse the `\pytx@Inline` macro
`\pytx@MakePygmentsInlinePyg` sequence. The approach is very similar to the constructors for inline commands,
`\pygment` except for the way in which the type is defined and for the fact that we have to
check to see if a macro for `fancyvrb` settings exists. Just as for the `PythonTeX`
inline commands, we do not currently support `fancyvrb` options in Pygments
inline commands, since almost all options are impractical for inline usage, and the
few that might conceivably be practical, such as showing spaces, should probably
be used throughout an entire document rather than just for a tiny code snippet
within a paragraph.

We supply an empty optional argument to `\pytx@Inline`, so that the `\pygment` command can only take two mandatory arguments, and no optional argument (since sessions don't make sense for code that is merely typeset):

```
\pygment{<lexer>}{<code>}
```

```
1230 \def\pytx@MakePygmentsInlineFV{%
1231   \newcommand{\pygment}[1]{%
1232     \edef\pytx@lexer{##1}%
1233     \Depyhtontex{cmd:pygment:mv:c}%
1234     \edef\pytx@type{PYG##1}%
1235     \edef\pytx@cmd{v}%
1236     \pytx@SetContext
1237     \pytx@SetGroupVerb
1238     \let\pytx@InlineShow\pytx@InlineShowFV
1239     \let\pytx@InlineSave\@empty
1240     \let\pytx@InlinePrint\@empty
1241     \pytx@CheckPygmentsInit{##1}%
1242     \pytx@Inline[]%
1243   }%
1244 }
1245 \def\pytx@MakePygmentsInlinePyg{%
1246   \newcommand{\pygment}[1]{%
1247     \edef\pytx@type{PYG##1}%
1248     \edef\pytx@cmd{v}%
1249     \pytx@SetContext
1250     \pytx@SetGroupVerb
1251     \let\pytx@InlineShow\pytx@InlineShowPyg
1252     \let\pytx@InlineSave\pytx@InlineSaveCode
1253     \let\pytx@InlinePrint\@empty
1254     \pytx@CheckPygmentsInit{##1}%
1255     \pytx@Inline[]
1256   }%
1257 }
```

9.11.2 Pygments environment

`\pytx@MakePygmentsEnvFV` `pygments` The `pygments` environment is created to take an optional argument, which corresponds to `fancyvrb` settings, and one mandatory argument, which corresponds to the `Pygments` lexer to be used in highlighting the code.

The `pygments` environment begins by declaring that it is a `Verbatim` environment and setting variables. Again, some variables are unnecessary, but they are created to maintain uniformity with other `PythonTeX` environments. The environment code is very similar to that of `PythonTeX verb` environments.

```
1258 \def\pytx@MakePygmentsEnvFV{%
1259   \newenvironment{pygments}{%
1260     \VerbatimEnvironment
1261     \pytx@SetContext
1262     \pytx@SetGroupVerb
```

```

1263     \begingroup
1264     \obeylines
1265     \@ifnextchar[{\endgroup\pytx@BEPygmentsFV}{\endgroup\pytx@BEPygmentsFV[]}%
1266     }%
1267     {\end{Verbatim}}%
1268     \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
1269     \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}%
1270     }%
1271 }

```

`\pytx@BEPygmentsFV` This macro captures the optional argument containing `fancyvrb` commands.

```

1272 \def\pytx@BEPygmentsFV[#1]{%
1273     \def\pytx@fvopttmp{#1}%
1274     \begingroup
1275     \obeylines
1276     \pytx@BEPygmentsFV@i
1277 }

```

`\pytx@BEPygmentsFV@i` This macro captures the mandatory argument, containing the lexer name, and proceeds.

```

1278 \def\pytx@BEPygmentsFV@i#1{%
1279     \endgroup
1280     \edef\pytx@type{PYG#1}%
1281     \edef\pytx@lexer{#1}%
1282     \Depyhtontex{env:pygments:om:c}%
1283     \DepyListing
1284     \edef\pytx@cmd{verbatim}%
1285     \edef\pytx@session{default}%
1286     \edef\pytx@linecount{\pytx@\pytx@type @\pytx@session @\pytx@group @line}%
1287     \pytx@CheckCounter{\pytx@linecount}%
1288     \pytx@CheckPygmentsInit{#1}%
1289     \setcounter{\pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
1290     \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
1291     \pytx@FVSet
1292     \ifdefstring{\pytx@fvopttmp}{-}{\expandafter\fvset\expandafter{\pytx@fvopttmp}}%
1293     \begin{Verbatim}%
1294 }

```

`\pytx@MakePygmentsEnvPyg` The Pygments version is very similar, except that it must bring in external Pygments content.

```

1295 \def\pytx@MakePygmentsEnvPyg{%
1296     \newenvironment{pygments}{%
1297         \VerbatimEnvironment
1298         \pytx@SetContext
1299         \pytx@SetGroupVerb
1300         \begingroup
1301         \obeylines
1302         \@ifnextchar[{\endgroup\pytx@BEPygmentsPyg}{\endgroup\pytx@BEPygmentsPyg[]}%
1303     }%

```

```

1304   {\end{VerbatimOut}}%
1305       \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
1306       \pytx@FVSet
1307       \ifdefstring{\pytx@fvopttmp}{-}{\expandafter\fvset\expandafter{\pytx@fvopttmp}}%
1308       \ifcsname FV@SV@\pytx@counter @\arabic{\pytx@counter}\endcsname
1309           \UseVerbatim{\pytx@counter @\arabic{\pytx@counter}}%
1310       \else
1311           \InputIfFileExists{\pytx@outputdir/%
1312               \pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}.pygtex}{-}{%
1313               {\textbf{??~\pytx@packagename~??}}%
1314               \PackageWarning{\pytx@packagename}{Non-existent Pygments content}}%
1315       \fi
1316       \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
1317       \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
1318       \stepcounter{\pytx@counter}%
1319   }%
1320 }

```

`\pytx@BEPygmentsPyg` This macro captures the optional argument, which corresponds to `fancyvrb` settings.

```

1321 \def\pytx@BEPygmentsPyg[#1]{%
1322     \def\pytx@fvopttmp{#1}%
1323     \begingroup
1324     \obeylines
1325     \pytx@BEPygmentsPyg@i
1326 }

```

`\pytx@BEPygmentsPyg@i` This macro captures the mandatory argument, containing the lexer name, and proceeds.

```

1327 \def\pytx@BEPygmentsPyg@i#1{%
1328     \endgroup
1329     \edef\pytx@type{PYG#1}%
1330     \edef\pytx@cmd{verbatim}%
1331     \edef\pytx@session{default}%
1332     \xdef\pytx@counter{\pytx@\pytx@type @\pytx@session @\pytx@group}%
1333     \pytx@CheckCounter{\pytx@counter}%
1334     \edef\pytx@linecount{\pytx@counter @line}%
1335     \pytx@CheckCounter{\pytx@linecount}%
1336     \pytx@WriteCodefileInfo
1337     \pytx@CheckPygmentsInit{#1}%
1338     \setcounter{\pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
1339     \let\FVB@VerbatimOut\pytx@FVB@VerbatimOut
1340     \let\FVE@VerbatimOut\pytx@FVE@VerbatimOut
1341     \begin{VerbatimOut}%
1342 }

```

9.11.3 Special Pygments commands

Code highlighting may be used for some tasks that would never appear in a code execution context, which is what the `PythonTeX` part of this package focuses on.

We create some special Pygments macros to handle these highlighting cases.

`\pytx@MakePygmentsInputFV` For completeness, we need to be able to read in a file and highlight it. This
`\pytx@MakePygmentsInputPyg` is done through some trickery with the current system. We define the type as
 PYG<lexer>, and the command as `verb`. We set the context for consistency. We
 set the session as `EXT:<file name>`.⁴⁶ Next we define a `fancyvrb` settings macro
 for the type if it does not already exist. We write info to the code file using
`\pytx@WriteCodefileInfoExt`, which writes the standard info to the code file
 but uses zero for the instance, since external files that are not executed can only
 have one instance.

Then we check to see if the file actually exists, and issue a warning if not. This
 saves the user from running `pythontex.py` to get the same error. We perform our
 typical `FancyVerbLine` trickery. Next we make use of the saved content in the
 same way as the `pygments` environment. Note that we do not create a counter
 for the line numbers. This is because under typical usage an external file should
 have its lines numbered beginning with 1. We also encourage this by setting
`firstnumber=auto` before bringing in the content.

The current naming of the macro in which the Pygments content is saved is
 probably excessive. In almost every situation, a unique name could be formed with
 less information. The current approach has been taken to maintain parallelism,
 thus simplifying `pythontex.py`, and to avoid any rare potential conflicts.

```

1343 \def\pytx@MakePygmentsInputFV{
1344   \newcommand{\inputpygments}[3] []{%
1345     \edef\pytx@lexer{##2}%
1346     \Depythontex{cmd:inputpygments:omm:c}%
1347     \edef\pytx@type{PYG##2}%
1348     \edef\pytx@cmd{verbatim}%
1349     \pytx@SetContext
1350     \pytx@SetGroupVerb
1351     \edef\pytx@session{EXT:##3}%
1352     \pytx@CheckPygmentsInit{##2}%
1353     \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
1354     \begingroup
1355     \DepyListing %Always must be in a group
1356     \pytx@FVSet
1357     \fvset{firstnumber=auto}%
1358     \IfFileExists{##3}%
1359       {\DepyFile{c:##3:mode=verbatim}\VerbatimInput{##1}{##3}}%
1360       {\PackageWarning{\pytx@packagename}{Input file <##3> doesn't exist}}%
1361     \endgroup
1362     \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}%
1363   }%
1364 }
1365 \def\pytx@MakePygmentsInputPyg{
1366   \newcommand{\inputpygments}[3] []{%

```

⁴⁶There is no possibility of this session being confused with a user-defined session, because colons are substituted for hyphens in all user-defined sessions, before they are written to the code file.

```

1367     \edef\pytx@type{PYG##2}%
1368     \edef\pytx@cmd{verbatim}%
1369     \pytx@SetContext
1370     \pytx@SetGroupVerb
1371     \edef\pytx@session{EXT:##3}%
1372     \pytx@CheckPygmentsInit{##2}%
1373     \pytx@WriteCodefileInfoExt
1374     \IfFileExists{##3}{\PackageWarning{\pytx@packagename}%
1375       {Input file <##3> does not exist}}
1376     \setcounter{pytx@FancyVerbLineTemp}{\value{FancyVerbLine}}%
1377     \begingroup
1378     \pytx@FVSet
1379     \fvset{firstnumber=auto}%
1380     \ifcsname FV@SV\pytx@\pytx@type @\pytx@session @\pytx@group @0\endcsname
1381       \UseVerbatim[##1]{\pytx@\pytx@type @\pytx@session @\pytx@group @0}%
1382     \else
1383       \InputIfFileExists{\pytx@outputdir/##3_##2.pygtex}{%
1384         {\textbf{??}\pytx@packagename~??}%
1385         \PackageWarning{\pytx@packagename}{Non-existent Pygments content}}%
1386     \fi
1387     \endgroup
1388     \setcounter{FancyVerbLine}{\value{pytx@FancyVerbLineTemp}}%
1389   }%
1390 }

```

9.11.4 Creating the Pygments commands and environment

We are almost ready to actually create the Pygments commands and environments. First, though, we create some macros that allow the user to set `fancyvrb` settings, Pygments options, and formatting of Pygments content.

`\setpygmentsfv` This macro allows `fancyvrb` settings to be specified for a Pygments lexer. It takes the lexer name as the optional argument and the settings as the mandatory argument. If no optional argument (lexer) is supplied, then it sets the document-wide `fancyvrb` settings, and is in that case equivalent to `\setpythontexfv`.

```

1391 \newcommand{\setpygmentsfv}[2] []{%
1392   \Depythontex{cmd:setpygmentsfv:om:n}%
1393   \ifstrempy{#1}%
1394     {\gdef\pytx@fvsettings{#2}}%
1395     {\expandafter\gdef\csname pytx@fvsettings@PYG#1\endcsname{#2}}%
1396 }%

```

`\setpygmentspygopt` This macro allows the Pygments option to be set for a lexer. It takes the lexer name as the first argument and the options as the second argument. If this macro is used multiple times for a lexer, it will write the settings to the code file multiple times. But `pythontex.py` will simply process all settings, and each subsequent set of settings will overwrite any prior settings, so this is not a problem.

```

1397 \newcommand{\setpygmentspygopt}[2] []{%
1398   \Depythontex{cmd:setpygmentspygopt:om:n}%

```

```

1399 \ifstrempy{#1}{\def\pytx@pygopt{#2}}{%
1400 \expandafter\gdef\cname pytx@pygopt@PYG#1\endcname{#2}}%
1401 }
1402 \@onlypreamble\setpygmentspygopt

```

`\setpygmentsprettyprinter` This macro parallels `\setpythontexprettyprinter`. Currently, it takes no optional argument. Eventually, it may be desirable to allow an optional argument that sets the pretty printer on a per-lexer basis.

```

1403 \newcommand{\setpygmentsprettyprinter}[1]{%
1404 \Depythontex{cmd:setpygmentsprettyprinter:m:n}%
1405 \ifstrequal{#1}{fancyvrb}{\boolfalse{pytx@opt@pygments}}%
1406 \ifstrequal{#1}{pygments}{\booltrue{pytx@opt@pygments}}%
1407 }
1408 \@onlypreamble\setpygmentsprettyprinter
1409 \xdef\pytx@macroformatter@PYG{auto}

```

`\makepygmentsfv` This macro creates the Pygments commands and environment using `fancyvrb`, as a fallback when Pygments is unavailable or when the user desires maximum speed.

```

1410 \def\makepygmentsfv{%
1411 \pytx@MakePygmentsInlineFV
1412 \pytx@MakePygmentsEnvFV
1413 \pytx@MakePygmentsInputFV
1414 }%
1415 \@onlypreamble\makepygmentsfv

```

`\makepygmentspyg` This macro creates the Pygments commands and environment using Pygments. We must set the bool `pytx@usedpygments` true so that `pythontex.py` knows that Pygments content is present and must be highlighted.

```

1416 \def\makepygmentspyg{%
1417 \ifbool{pytx@opt@pyginline}%
1418 {\pytx@MakePygmentsInlinePyg}%
1419 {\pytx@MakePygmentsInlineFV}%
1420 \pytx@MakePygmentsEnvPyg
1421 \pytx@MakePygmentsInputPyg
1422 \booltrue{pytx@usedpygments}
1423 }%
1424 \@onlypreamble\makepygmentspyg

```

`\makepygments` This macro uses the two preceding macros to conditionally define the Pygments commands and environments, based on the package Pygments settings.

```

1425 \def\makepygments{%
1426 \AtBeginDocument{%
1427 \ifdefstring{\pytx@macroformatter@PYG}{auto}%
1428 {\ifbool{pytx@opt@pygments}%
1429 {\makepygmentspyg}{\makepygmentsfv}}{}
1430 \ifdefstring{\pytx@macroformatter@PYG}{pygments}%
1431 {\makepygmentspyg}{}
1432 \ifdefstring{\pytx@macroformatter@PYG}{fancyvrb}%
1433 {\makepygmentsfv}{}

```

```

1434     }%
1435 }%
1436 \@onlypreamble\makepygments

```

We conclude by actually creating the Pygments commands and environments.

```

1437 \makepygments

```

9.12 Final cleanup

At the end of the document, we need to close files.

```

1438 \AfterEndDocument{%
1439     \immediate\closeout\pytx@codefile
1440     \ifbool{pytx@opt@depythontex}{\immediate\closeout\pytx@depyfile}{}%
1441 }

```

9.13 Compatibility with beta releases

The following code maintains compatibility with the beta releases when the package option `beta` is used. It will be retained for several releases before being removed.

```

1442 \ifbool{pytx@opt@beta}{
1443
1444 % Revert changes in stdout and stderr modes
1445 \def\pytx@FetchStdoutfile[#1][#2]#3{%
1446     \IfFileExists{\pytx@outputdir/#3.stdout}{%
1447         \ifstrequal{#1}{\input{\pytx@outputdir/#3.stdout}}{}%
1448         \ifstrequal{#1}{raw}{\input{\pytx@outputdir/#3.stdout}}{}%
1449         \ifstrequal{#1}{verb}{\VerbatimInput[#2]{\pytx@outputdir/#3.stdout}}{}%
1450         \ifstrequal{#1}{inlineverb}{\BVerbatimInput[#2]{\pytx@outputdir/#3.stdout}}{}%
1451         \ifstrequal{#1}{v}{\BVerbatimInput[#2]{\pytx@outputdir/#3.stdout}}{}%
1452         \DePyFile{p:\pytx@outputdir/#3.stdout:mode=#1}%
1453     }%
1454     {\pytx@stdout@warntext
1455         \PackageWarning{\pytx@packagename}{Non-existent printed content}}%
1456 }
1457 \def\pytx@FetchStderrfile[#1][#2]#3{%
1458     \IfFileExists{\pytx@outputdir/#3.stderr}{%
1459         \ifstrequal{#1}{raw}{\input{\pytx@outputdir/#3.stderr}}{}%
1460         \ifstrequal{#1}{\VerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{}%
1461         \ifstrequal{#1}{verb}{\VerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{}%
1462         \ifstrequal{#1}{inlineverb}{\BVerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{}%
1463         \ifstrequal{#1}{v}{\BVerbatimInput[#2]{\pytx@outputdir/#3.stderr}}{}%
1464         \DePyFile{p:\pytx@outputdir/#3.stderr:mode=#1}%
1465     }%
1466     {\textbf{??~\pytx@packagename~??}%
1467         \PackageWarning{\pytx@packagename}{Non-existent stderr content}}%
1468 }
1469

```

```

1470
1471 % Old verb environment
1472 \renewcommand{\pytx@MakeVerbFV}[1]{%
1473   \expandafter\newenvironment{#1verb}{%
1474     \VerbatimEnvironment
1475     \expandafter\let\expandafter\pytx@lexer\csname pytx@pyglexer@#1\endcsname
1476     \Depyhtontex{env:#1verb:oo|:c}%
1477     \DepyListing
1478     \xdef\pytx@type{#1}%
1479     \edef\pytx@cmd{verb}%
1480     \pytx@SetContext
1481     \pytx@SetGroupVerb
1482     \begingroup
1483     \obeylines
1484     \@ifnextchar[{\endgroup\pytx@BeginVerbEnvFV}{\endgroup\pytx@BeginVerbEnvFV []}%
1485   }%
1486   {\end{Verbatim}}%
1487   \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
1488   \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
1489   \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
1490   \stepcounter{\pytx@counter}%
1491 }%
1492 }
1493 \renewcommand{\pytx@MakePygEnv}[2]{%
1494   \expandafter\newenvironment{#1#2}{%
1495     \VerbatimEnvironment
1496     \xdef\pytx@type{#1}%
1497     \edef\pytx@cmd{#2}%
1498     \pytx@SetContext
1499     \ifstrequal{#2}{block}{\pytx@SetGroup}{%
1500     \ifstrequal{#2}{verb}{\pytx@SetGroupVerb}{%
1501     \begingroup
1502     \obeylines
1503     \@ifnextchar[{\endgroup\pytx@BeginEnvPyg}{\endgroup\pytx@BeginEnvPyg []}%
1504   }%
1505   {\end{VerbatimOut}}%
1506   \xdef\pytx@stdfile{\pytx@type_\pytx@session_\pytx@group_\arabic{\pytx@counter}}%
1507   \setcounter{FancyVerbLine}{\value{\pytx@linecount}}%
1508   \pytx@FVSet
1509   \ifdefstring{\pytx@fvopttmp}{-}{\expandafter\fvset\expandafter{\pytx@fvopttmp}}%
1510   \ifcsname FV@SV@\pytx@counter @\arabic{\pytx@counter}\endcsname
1511     \UseVerbatim{\pytx@counter @\arabic{\pytx@counter}}%
1512   \else
1513     \InputIfFileExists{\pytx@outputdir/\pytx@stdfile.pygtex}{%
1514       {\textbf{??}\pytx@packagename??}%
1515       \PackageWarning{\pytx@packagename}{Non-existent Pygments content}}%
1516   \fi
1517   \setcounter{\pytx@linecount}{\value{FancyVerbLine}}%
1518   \setcounter{FancyVerbLine}{\value{\pytx@FancyVerbLineTemp}}%
1519   \stepcounter{\pytx@counter}%

```

```

1520     }%
1521 }%
1522 \renewcommand{\pytx@MakeVerbPyg}[1]{\pytx@MakePygEnv{#1}{verb}}
1523
1524
1525 % Settings macros
1526 \def\setpythontexpygllexer#1#2{%
1527     \Depythontex{cmd:setpythontexpygllexer:mm:n}%
1528     \ifcsname pytx@pygllexer@#1\endcsname
1529         \expandafter\xdef\csname pytx@pygllexer@#1\endcsname{#2}%
1530     \else
1531         \PackageError{\pytx@packagename}%
1532             {Cannot modify a non-existent family}{}%
1533     \fi
1534 }%
1535 \renewcommand{\setpythontexpygopt}[2]{%
1536     \Depythontex{cmd:setpythontexpygopt:mm:n}%
1537     \ifcsname pytx@pygopt@#1\endcsname
1538         \expandafter\xdef\csname pytx@pygopt@#1\endcsname{#2}%
1539     \else
1540         \PackageError{\pytx@packagename}%
1541             {Cannot modify Pygments options for a non-existent family}{}%
1542     \fi
1543 }
1544 \def\setpygmentspygopt#1#2{%
1545     \Depythontex{cmd:setpygmentspygopt:mm:n}%
1546     \AtEndDocument{\immediate\write\pytx@codefile{%
1547         \pytx@delimsettings pygfamily=PYG#1,#1,%
1548         \string{#2}\string}\pytx@delimchar}%
1549     }%
1550 }
1551
1552
1553 % Old formatters
1554 \def\setpythontexformatter#1#2{%
1555     \Depythontex{cmd:setpythontexformatter:mm:n}%
1556     \ifcsname pytx@macroformatter@#1\endcsname
1557         \ifbool{pytx@opt@depythontex}{}{%
1558             \expandafter\xdef\csname pytx@macroformatter@#1\endcsname{#2}}
1559     \else
1560         \PackageError{\pytx@packagename}%
1561             {Cannot modify a family that does not exist or does not allow formatter choices}%
1562             {Create the family with \string\makepythontexfamily}%
1563     \fi
1564 }
1565 \@onlypreamble\setpythontexformatter
1566 \def\setpygmentsformatter#1{%
1567     \Depythontex{cmd:setpygmentsformatter:m:n}%
1568     \ifbool{pytx@opt@depythontex}{}{\xdef\pytx@macroformatter@PYG{#1}}
1569 \@onlypreamble\setpygmentsformatter

```

1570
 1571
 1572
 1573
 1574 }{} %End beta

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	1436, 1565, 1569	B
<code>\=</code> 201	<code>\@tempa</code> 793	<code>\boolfalse</code> . . 21, 45,
<code>\@bsphack</code> 354, 921	<code>\@tempb</code> 794	49, 53, 58, 62,
<code>\@empty</code> 178, 314, 325,	<code>\@undefined</code> 257	67, 73, 84, 89,
532, 543, 628,	<code>\{</code> . . . 548, 555, 561, 776	115, 120, 131,
635, 647, 658,	<code>\}</code> 556, 562, 777	135, 141, 145,
669, 681, 694,	<code>\^</code> 196, 558, 595, 778, 789	174, 189, 1177, 1405
695, 707, 718,		<code>\booltrue</code> 20,
732, 746, 764,		41, 44, 48, 52,
766, 928, 935,	<code>_</code> 557, 594	57, 61, 65, 71,
1239, 1240, 1253		83, 87, 111, 114,
<code>\@esphack</code> 366, 927		119, 128, 130,
<code>\@gobble</code> 175–177, 492,	A	134, 137, 140,
512, 518, 540–542	<code>\active</code> 557,	144, 173, 1096,
<code>\@ifnextchar</code> 387, 390,	558, 594, 595, 789	1115, 1178,
397, 418, 421,	<code>\AfterEndDocument</code> 1438	1208, 1406, 1422
433, 448, 451,	<code>\AfterEndPreamble</code> . 276	<code>\BUseVerbatim</code> . 616, 651
468, 471, 549,	<code>\aftergroup</code> 185	<code>\BVerbatimInput</code> . . .
559, 815, 849,	<code>\arabic</code> 317, 520, 582,	376, 439, 1450,
879, 907, 947,	614, 616, 638,	1451, 1462, 1463
963, 1001, 1031,	649, 818, 852,	
1052, 1265,	882, 886, 887,	C
1302, 1484, 1503	950, 1004, 1008–	<code>\csname</code> 194,
<code>\@ifpackageloaded</code> .	1010, 1055,	208, 210, 338,
. 10, 256	1059–1061,	343, 365, 409,
<code>\@makeother</code> 197, 547,	1308, 1309,	425, 463, 475,
554, 573, 593, 775	1312, 1487,	640, 660, 661,
<code>\@nil</code> 791	1506, 1510, 1511	674, 686, 687,
<code>\@noligs</code> 925	<code>\AtBeginDocument</code> . .	700, 712, 726,
<code>\@onlypreamble</code> 10, 75, 234,	740, 806, 840,
. 222, 246, 264,	255, 270, 280,	992, 1043, 1098,
269, 787, 1149,	384, 629, 929,	1099, 1117,
1161, 1173,	1133, 1211, 1426	1118, 1126–
1190, 1210,	<code>\AtEndDocument</code>	1130, 1154,
1402, 1408,	290, 494, 1097,	1166, 1182,
1415, 1424,	1116, 1226, 1546	1224, 1225,
		1227, 1395,

1400, 1475, 1529, 1538, 1558	\currfilebase . 313, 324	\currfilename . 314, 325	\DepyhtonextOn 533	\detokenize 181, 578, 799, 919	938, 990, 992, 1007, 1041, 1043, 1058, 1126–1130, 1154, 1166, 1182, 1203, 1224, 1225, 1292, 1307, 1395, 1400, 1473, 1475, 1494, 1509, 1529, 1538, 1558
D			E			F
\DeclareFloatingEnvironment 1207, 1219	\definepythontexcontext 216	\DepyFile 176, 378, 441, 513, 536, 542, 633, 933, 1013, 1064, 1359, 1452, 1464	\DepyFile@orig 513, 517, 536	\DepyListing 178, 519, 537, 543, 808, 842, 994, 1045, 1283, 1355, 1477	\DepyListing@orig 522, 531, 537	\DepyMacro . . . 177, 507, 535, 541, 641, 652, 1010, 1061
\DepyMacro@orig 507, 511, 535	\Depyhtonext . . . 51, 56, 175, 224, 252, 266, 335, 386, 396, 400, 413, 417, 432, 447, 457, 467, 485, 534, 540, 662, 688, 713, 727, 741, 754, 770, 807, 841, 940, 974, 993, 1044, 1151, 1163, 1175, 1206, 1233, 1282, 1346, 1392, 1398, 1404, 1476, 1527, 1536, 1545, 1555, 1567	\Depyhtonext@orig 486, 491, 534	\DepyhtonextOff . . . 533	\endcsname . . . 191, 194, 208, 210, 271, 338, 343, 365, 404, 409, 424, 425, 458, 463, 474, 475, 502, 614, 639, 640, 650, 660, 661, 674, 686, 687, 700, 712, 726, 740, 806, 840, 886, 992, 1008, 1043, 1059, 1098, 1099, 1117, 1118, 1126–1130, 1153, 1154, 1165, 1166, 1180, 1182, 1212, 1223–1225, 1227, 1308, 1380, 1395, 1400, 1475, 1510, 1528, 1529, 1537, 1538, 1556, 1558	\endlinechar . . 196, 592	\endpytx@SVMCR 202, 212
\everyeof 591	\expandafter . . 181, 208, 213, 338, 342, 346, 349, 359, 364, 409, 463, 526, 596, 660, 661, 674, 686, 687, 700, 712, 726, 740, 804, 806, 838, 840, 870, 885,	\frenchspacing 601	\FV@@@CheckEnd 794	\FV@BadEndError . . . 794	\FV@BeginVBox 600	\FV@CheckEnd 792
\FV@CodeLineNo 361	\FV@DefineWhiteSpace 603	\FV@EndScanning . . . 795	\FV@EndVBox 608	\FV@EnvName 793	\FV@FontScanPrep . . 924	\FV@GetLine 798
\FV@Line 797	\FV@ObeyTabsInit . . 606	\FV@PreProcessLine . 798	\FV@ProcessLine 358, 360, 923			

<code>\FV@Scan</code>	362, 926	886, 1008, 1059,	1116, 1226,
<code>\FV@SetupFont</code>	602	1153, 1165,	1439, 1440, 1546
<code>\FV@StepLineNo</code>	360	1180, 1212,	<code>\input</code> 374, 375, 437,
<code>\FV@TheVerbatim</code>	359–361, 365	1223, 1308,	1447, 1448, 1459
<code>\FV@UseKeyValues</code>	356	1380, 1510,	<code>\InputIfFileExists</code> .
<code>\FVB@SaveVerbatim</code>	368	1528, 1537, 1556 278,
<code>\FVB@VerbatimOut</code>	912, 967, 1036, 1339	<code>\ifcsstring</code>	282, 632, 889,
<code>\FVE@SaveVerbatim</code>	369	... 1134, 1136,	932, 1012, 1063,
<code>\FVE@VerbatimOut</code>	913, 968, 1037, 1340	1138, 1141,	1311, 1383, 1513
<code>\fvset</code>	346, 349,	1142, 1144, 1145	<code>\inputlineno</code>
	885, 1007, 1058,	<code>\ifcurrfile</code> 321, 332, 488
	1292, 1307,	<code>\ifdefstring</code>	<code>\inputpygments</code>
	1357, 1379, 1509	... 344, 1344, 1366
		347, 885, 1007,	
		1058, 1292,	
		1307, 1427,	
		1430, 1432, 1509	
		<code>\IfFileExists</code>	J
		373, 436, 1358,	<code>\jobname</code> 248,
		1374, 1446, 1458	286, 313, 324, 483
G		<code>\IfInteger</code> 152	
<code>\g@addto@macro</code>	260	<code>\ifnum</code> 153	
<code>\gdef</code>	213, 337,	<code>\ifstrempy</code>	L
	338, 359, 361,	. 336, 374, 438,	<code>\left</code> 181, 182, 184
	526, 790, 1127,	552, 825, 859,	<code>\let</code> 175–178, 182,
	1224, 1225,	899, 957, 1023,	183, 197, 273,
	1394, 1395, 1400	1152, 1164,	314, 325, 342,
<code>\Ginput@path</code>	257, 260	1176, 1393,	364, 368, 369,
<code>\global</code>	364	1399, 1447, 1460	485, 489, 491,
<code>\graphicspath</code>	258	<code>\IfStrEq</code> 181	492, 511, 512,
		<code>\ifstrequal</code>	517, 518, 523,
		.. 52, 53,	531, 532, 534–
H		57, 58, 375–377,	537, 540–543,
<code>\hbox</code>	607	437, 439, 440,	547, 554, 573,
		567, 755, 756,	593, 628, 635,
		875, 876, 975,	647, 658, 661,
		976, 1177, 1178,	667–669, 679–
		1198–1201,	681, 687, 693–
		1405, 1406,	695, 705–707,
		1448–1451,	718–720, 724,
		1459, 1461–	732–734, 738,
		1463, 1499, 1500	746–748, 752,
		<code>\IfSubStr</code> 236, 240	764–766, 775,
		<code>\ifx</code> 208,	795, 806, 833,
		257, 488, 793, 794	840, 912, 913,
		<code>\immediate</code> 286,	923–925, 928,
		291–308, 315,	935, 967, 968,
		326, 483, 487,	971, 992, 1036,
		495, 497, 499,	1037, 1043,
		501, 503, 508,	1238–1240,
		514, 520, 626,	1251–1253,
		799, 919, 1097,	1339, 1340, 1475
			<code>\long</code> 212, 781

M		
<code>\makeatletter</code>	281	
<code>\makeatother</code>	283	
<code>\makepygments</code> 1425 , 1437		
<code>\makepygmentsfv</code> . . .		
.. 1410 , 1429, 1433		
<code>\makepygmentspyg</code> . .		
.. 1416 , 1429, 1431		
<code>\makepythontexfamily</code>		
... 1073 , 1186,		
1191–1196,		
1198–1201, 1562		
<code>\mathclose</code>	184	
<code>\mathopen</code>	184	
<code>\MessageBreak</code> 1215, 1216		
N		
<code>\newbool</code> 17, 40, 60, 80,		
110, 116, 127,		
136, 170, 275, 1204		
<code>\newcounter</code> . . . 191, 351		
<code>\newwrite</code> 285, 482		
<code>\next</code> 795, 798, 801		
<code>\noexpand</code> 591		
O		
<code>\obeylines</code> 814, 848,		
878, 906, 946,		
962, 1000, 1030,		
1051, 1264,		
1275, 1301,		
1324, 1483, 1502		
<code>\oldFancyVerbLine</code> .		
..... 523, 526		
<code>\openout</code> 286, 483		
<code>\originalleft</code> . 182, 184		
<code>\originalright</code> 183, 185		
P		
<code>\PackageError</code>		
.... 156, 158,		
237, 241, 405,		
459, 568, 756,		
976, 1123, 1156,		
1168, 1184,		
1531, 1540, 1560		
<code>\PackageWarning</code> 34,		
66, 68, 72, 74,		
77, 88, 90, 381,		
428, 444, 478,		
620, 644, 655,		
771, 891, 1015,		
1066, 1214,		
1314, 1360,		
1374, 1385,		
1455, 1467, 1515		
<code>\pgfkeys</code> 12,		
14–16, 18–21,		
23–33, 36–39,		
42–49, 62–65,		
67, 69–71, 73,		
81–87, 89, 92–		
96, 98, 101–		
104, 106–109,		
112–115, 117–		
120, 122–126,		
129–135, 138–		
145, 147, 149,		
151, 152, 161–		
165, 167–169,		
171–174, 1073, 1125		
<code>\printpythontex</code> . . . 385		
<code>\ProcessPgfPackageOptions</code>		
..... 179		
<code>\pygment</code> 1230		
<code>\pygments</code> .. 1258 , 1295		
<code>\pythontexcustomc</code> .		
.... 753 , 773, 783		
<code>\pythontexcustomcode</code>		
..... 972		
<code>\pytx@arg</code> 579, 596		
<code>\pytx@argdetok</code> 578, 626		
<code>\pytx@argretok</code> 589, 607		
<code>\pytx@argspprint</code> . .		
.... 311, 319, 330		
<code>\pytx@argsrun</code>		
.... 310, 318, 329		
<code>\pytx@BeginBlockEnvFV</code>		
..... 815, 824		
<code>\pytx@BeginCodeEnv</code> .		
.... 947, 956 , 984		
<code>\pytx@BeginCodeEnv@i</code>		
..... 963, 965		
<code>\pytx@BeginConsEnvFV</code>		
.. 1001, 1022 , 1052		
<code>\pytx@BeginConsEnvFV@i</code>		
..... 1031, 1033		
<code>\pytx@BeginEnvPyg</code> .		
... 879, 898 , 1503		
<code>\pytx@BeginEnvPyg@i</code>		
..... 907, 909		
<code>\pytx@BeginVerbEnvFV</code>		
... 849, 858, 1484		
<code>\pytx@BEPygmentsFV</code> .		
..... 1265, 1272		
<code>\pytx@BEPygmentsFV@i</code>		
..... 1276, 1278		
<code>\pytx@BEPygmentsPyg</code>		
..... 1302, 1321		
<code>\pytx@BEPygmentsPyg@i</code>		
..... 1325, 1327		
<code>\pytx@CheckCounter</code> .		
.... 190 , 581,		
827, 829, 861,		
863, 901, 903,		
959, 1025, 1027,		
1287, 1333, 1335		
<code>\pytx@CheckPygmentsInit</code>		
... 1222 , 1241,		
1254, 1288,		
1337, 1352, 1372		
<code>\pytx@cmd</code> 317,		
328, 664, 676,		
690, 702, 715,		
729, 743, 761,		
810, 844, 873,		
942, 981, 996,		
1047, 1235,		
1248, 1284,		
1330, 1348,		
1368, 1479, 1497		
<code>\pytx@codefile</code> 285 ,		
291–308, 315,		
326, 626, 799,		
919, 1097, 1116,		
1226, 1439, 1546		
<code>\pytx@context</code> . 216 ,		
318, 329, 762, 982		
<code>\pytx@counter</code> . 317,		
580–582, 586,		
614, 616, 638,		
649, 818, 821,		
826–828, 852,		
855, 860–862,		
882, 886, 887,		
895, 900–902,		
950, 953, 958,		
959, 987, 1004,		
1008–1010,		

1019, 1024–	1273, 1292,	\pytx@InlineSaveCode
1026, 1055,	1307, 1322, 1509 624, 668,
1059–1061,	\pytx@FVSet 341, 599,	680, 706, 719,
1070, 1308,	613, 834, 866,	733, 747, 765, 1252
1309, 1312,	884, 1006, 1057,	\pytx@InlineShow ..
1318, 1332–	1291, 1306, 583, 588,
1334, 1487,	1356, 1378, 1508	667, 679, 693,
1490, 1506,	\pytx@fvsettings ..	705, 718, 732,
1510, 1511, 1519	334, 347, 349, 1394	746, 764, 1238, 1251
\pytx@currfile	\pytx@fvsettings@@ .	\pytx@InlineShowFV .
. 314, 320, 325, 331 342, 344, 346	588, 667, 693, 1238
\pytx@delim 288, 315, 326	\pytx@group	\pytx@InlineShowPyg
\pytx@delimchar 223, 316, 327,	611, 679, 705, 1251
. 287, 315–321,	580, 582, 638,	\pytx@jobname . 248,
326–332, 487,	649, 763, 818,	254, 278, 282, 498
488, 495–504, 1548	826, 852, 860,	\pytx@lexer ... 485,
\pytx@delimsettings	882, 900, 950,	488, 489, 661,
... 289, 291, 1547	958, 983, 1004,	687, 806, 840,
\pytx@depyfile 481,	1024, 1055,	992, 1043, 1232,
487, 495, 497,	1286, 1312,	1281, 1345, 1475
499, 501, 503,	1332, 1380,	\pytx@linecount ...
508, 514, 520, 1440	1381, 1487, 1506 819, 828,
\pytx@DepyListing@write	\pytx@Inline .. 545,	829, 831, 853,
..... 519, 525	670, 682, 696,	862, 863, 865,
\pytx@EnvAutoprint .	708, 721, 735,	883, 893, 902,
..... 928, 951	749, 767, 1242, 1255	903, 1005, 1017,
\pytx@families 11, 1203	\pytx@InlineAutoprint	1026, 1027,
\pytx@FancyVerbGetLine 628, 720	1056, 1068,
..... 788, 833	\pytx@InlineMacroprint	1268, 1286,
\pytx@FancyVerbLineTemp 637, 658, 734	1287, 1290,
..... 351	\pytx@InlineMacroprintFV	1305, 1316,
\pytx@FetchStderrfile 648, 748	1334, 1335,
435, 454, 475, 1457	\pytx@InlineMargBgroup	1488, 1507, 1517
\pytx@FetchStdoutfile 560, 571, 576	\pytx@macroformatter@PYG
371, 393, 425, 1445	\pytx@InlineMargOther	... 1409, 1427,
\pytx@FVB@SaveVerbatim 563, 565	1430, 1432, 1568
..... 351	\pytx@InlineMargOtherGet	\pytx@MakeBlockFV .
\pytx@FVB@VerbatimOut 565 803, 1086
..... 912,	\pytx@InlineOarg ..	\pytx@MakeBlockPyg .
920, 967, 1036, 1339 549, 551 916, 1094
\pytx@FVE@SaveVerbatim	\pytx@InlinePrint .	\pytx@MakeCodeFV ..
..... 363, 369 585, 588,	... 937, 971, 1132
\pytx@FVE@VerbatimOut	669, 681, 695,	\pytx@MakeCodePyg . 971
..... 913,	707, 720, 734,	\pytx@MakeConsFV ..
927, 968, 1037, 1340	748, 766, 1240, 1253 989, 1105
\pytx@fvextfile 150, 305	\pytx@InlineSave ..	\pytx@MakeConsoleFV 989
\pytx@fvopttmp 584, 588,	\pytx@MakeConsPyg .
885, 910, 1007,	668, 680, 694, 1040, 1113
1034, 1058,	706, 719, 733,	\pytx@MakeFamilyFV .
	747, 765, 1239, 1252	.. 1082, 1139, 1143

\pytx@MakeFamilyFVCons	\pytx@opt@depythontex	1184,	1214,
.. 1102, 1139, 1143 170	1216,	1313,
\pytx@MakeFamilyPyg	\pytx@opt@fixlr ... 116	1314,	1360,
.. 1089, 1137, 1146	\pytx@opt@gobble ..	1374,	1384,
\pytx@MakeFamilyPygCons 13, 295, 504	1385,	1455,
.. 1108, 1137, 1146	\pytx@opt@hashdependencies	1466,	1467,
\pytx@MakeInlinebFV	35, 35, 38, 39, 297	1514,	1515,
.. 659, 1083, 1092	\pytx@opt@keeptemps	1531,	1540, 1560
\pytx@MakeInlinebPyg 121, 300	\pytx@packageversion 2, 292, 496
..... 659, 1091	\pytx@opt@pyconbanner	\pytx@pyglexer	146,
\pytx@MakeInlinecFV 160, 306	146,	147, 304, 1152
..... 711, 1131	\pytx@opt@pyconfilename	\pytx@pygopt
\pytx@MakeInlineConsFV 166, 307	\pytx@opt@pyconfuture	148, 304, 1164, 1399
..... 739, 1104	\pytx@opt@pyfuture .	\pytx@session .	316,
\pytx@MakeInlineConsPyg 105, 302	327,	552, 580,
..... 739, 1112	\pytx@opt@pyinline .	582,	638, 649,
\pytx@MakeInlinecPyg 100, 301	818,	825, 826,
..... 711	\pytx@opt@pygments . 127	852,	859, 860,
\pytx@MakeInlineFV .	\pytx@opt@rerun 22,	882,	899, 900,
..... 725, 1085	22, 25, 28–33, 296	950,	957, 958,
\pytx@MakeInlinePyg	\pytx@opt@stderr .. 80	1004,	1023,
..... 725, 1093	\pytx@opt@stderrfilename	1024,	1055,
\pytx@MakeInlinevFV 91, 299	1285,	1286,
.... 685, 1084,	\pytx@opt@stdout .. 60	1312,	1331,
1092, 1103, 1111	\pytx@opt@cupquote . 110	1332,	1351,
\pytx@MakeInlinevPyg	\pytx@outputdir 251,	1371,	1380,
.. 685, 1091, 1110	293, 373–378,	1381,	1487, 1506
\pytx@MakePygEnv 869,	436–441, 498,	\pytx@SetContext 216,	
916, 917, 1493, 1522	500, 632, 633,	665,	677, 691,
\pytx@MakePygmentsEnvFV	889, 932, 933,	703,	716, 730,
..... 1258, 1412	1012, 1013,	744,	811, 845,
\pytx@MakePygmentsEnvPyg	1063, 1064,	874,	943, 997,
..... 1295, 1420	1311, 1383,	1048,	1236,
\pytx@MakePygmentsInlineFV	.. 1230, 1411, 1419	1249,	1261,
.. 1230, 1411, 1419	1446–1452,	1298,	1349,
\pytx@MakePygmentsInlinePyg	1458–1464, 1513	1369,	1480, 1498
..... 1230, 1418	\pytx@packagename 1,	\pytx@SetCustomCode 779, 781
\pytx@MakePygmentsInputFV	34, 66, 68, 72,	\pytx@SetGroup
..... 1343, 1413	74, 77, 88, 90, 223, 666,	
\pytx@MakePygmentsInputPyg	156, 158, 237,	678,	717, 731,
..... 1343, 1421	241, 381, 384,	745,	812, 875,
\pytx@MakeVerbFV 837,	405, 427, 428,	944,	998, 1049, 1499
1087, 1106, 1472	443, 444, 459,	\pytx@SetGroupCons . 223	
\pytx@MakeVerbPyg .	477, 478, 568,	\pytx@SetGroupVerb .	.. 223, 692, 704,
..... 917,	620, 644, 655,	. 223, 692, 704,	
1095, 1114, 1522	756, 771, 890,	846,	876, 1237,
\pytx@mcr	891, 976, 1014,	1250,	1262,
.. 638–641, 649–652	1015, 1065,	1299,	1350,
\pytx@opt@autoprint 40	1066, 1123,		
\pytx@opt@beta	1156, 1168,		

1370, 1481, 1500	\pytx@UseStderr	468, 470	1068, 1069,
\pytx@Stderr .. 448, 450	\pytx@UseStderr@i	.	1268, 1269,
\pytx@Stderr@i 451, 453	471, 473	1289, 1290,
\pytx@Stdfile	\pytx@UseStdout	...	1305, 1316,
.... 370, 393,	418, 420, 433	1317, 1338,
409, 454, 463,	\pytx@UseStdout@i	.	1353, 1362,
582, 632, 633,	421, 423	1376, 1388,
818, 852, 882,	\pytx@workingdir	..	1488, 1489,
889, 932, 933,	.	265, 267, 273, 294	1507, 1517, 1518
950, 1004, 1012,	\pytx@WriteCodefileInfo	.	\setpygmentsformatter
1013, 1055,	.	310, 625, 832, 1566, 1569
1063, 1064,	904, 960, 1028, 1336		\setpygmentsfv ... 1391
1487, 1506, 1513	\pytx@WriteCodefileInfoExt		\setpygmentsprettyprinter
\pytx@Stdout	310, 1373 1403
.... 387, 389, 397	\pytx@WriteDetok	..	\setpygmentspygopt
\pytx@Stdout@i 390, 392	918, 923 1397, 1544
\pytx@Stdout@warntext			\setpythontexautoprint
371, 380, 384, 1454		 50
\pytx@SVMCR	R		\setpythontexautostdout
193	\relax	. 26, 153, 208, 50
\pytx@SVMCR@i	485, 488, 489,		\setpythontexcustomcode
.... 198, 211, 212	592, 778, 924, 925	 769
\pytx@tmp . 194, 210, 213	\renewcommand	. 184,	\setpythontexformatter
\pytx@tmp@console	.	185, 1197, 1472, 1554, 1565
..... 1079, 1130	1493, 1522, 1535		\setpythontexfv ... 334
\pytx@tmp@pprinter	\RequirePackage	...	\setpythontexlistingenv
..... 1076, 1126	3-10, 188 1204, 1217
\pytx@tmp@pyglexer	\restartpythontexsession	\setpythontexoutputdir
..... 1077, 1128	223, 246, 247 251
\pytx@tmp@pygopt ..	\right	183, 185
..... 1078, 1129			\setpythontexprettyprinter
\pytx@type ... 315,	S	 1174
326, 343, 580,	\saveprintpythontex	399	\setpythontexpyglexer
582, 638, 649,	\savestderrpythontex	1150, 1526
663, 675, 689,	456	\setpythontexpygopt
701, 714, 728,	\savestdoutpythontex	1162, 1535
742, 760, 809,	399	\setpythontexworkingdir
818, 826, 843,	\savestdoutpythontex@i	401, 403, 414
852, 860, 872,		\space ... 772, 773, 1216
882, 900, 941,	\SaveVerbatim@Name	.	\stderrpythontex .. 446
950, 958, 980,	357, 365	\stdoutpythontex .. 385
995, 1004, 1024,	\scantokens	596
1046, 1055,	\setcounter	353, 367,	\stepcounter 586, 821,
1234, 1247,	615, 617, 819,		855, 895, 953,
1280, 1286,	820, 830, 831,		987, 1019, 1070,
1312, 1329,	853, 854, 864,		1318, 1490, 1519
1332, 1347,	865, 883, 893,		\string
1367, 1380,	894, 911, 952,		238,
1381, 1478,	966, 986, 1005,		239, 242, 243,
1487, 1496, 1506	1017, 1018,		287-289, 757,
\pytx@usedpygments . 275	1035, 1056,		772, 773, 1186,
			1217, 1548, 1562

<code>\StrSubstitute</code>	248– 250, 552, 825, 859, 899, 957, 1023	853, 854, 864, 865, 883, 893, 894, 911, 952, 966, 986, 1005, 1017, 1018, 1035, 1056, 1068, 1069, 1268, 1269, 1289, 1290, 1305, 1316, 1317, 1338, 1353, 1362, 1376, 1388, 1488, 1489, 1507, 1517, 1518	315, 326, 487, 495, 497, 499, 501, 503, 508, 514, 520, 626, 799, 919, 1097, 1116, 1226, 1546
T			
<code>\textbf</code>	384, 427, 443, 477, 619, 643, 654, 890, 1014, 1065, 1313, 1384, 1466, 1514		
<code>\the</code> 321, 332, 488		
<code>\theFancyVerbLine</code>	. . 523, 524, 526, 527		
U			
<code>\useprintpythontex</code>	. 416	<code>\VerbatimEnvironment</code>	
<code>\usestderrpythontex</code>	466 805, 839, 871, 939, 973, 991, 1042, 1260, 1297, 1474, 1495	
<code>\usestdoutpythontex</code>	416		
<code>\UseVerbatim</code> 887, 1009, 1060, 1309, 1381, 1511	<code>\VerbatimInput</code>	377, 438, 440, 1359, 1449, 1460, 1461
V			
<code>\value</code> 353, 367, 615, 617, 819, 820, 830, 831,	W	
		<code>\write</code> 291–308,
		X	
		<code>\xdef</code> 580, 582, 663, 675, 689, 701, 714, 728, 742, 760, 809, 818, 826, 843, 852, 860, 872, 882, 900, 941, 950, 958, 980, 995, 1004, 1024, 1046, 1055, 1126, 1128–1130, 1154, 1166, 1182, 1332, 1409, 1478, 1487, 1496, 1506, 1529, 1538, 1558, 1568