



REV	ZONE	REVISION	DATE

MO.	NAME	MATERIAL	FINISH	Q'TY
1	GROUND TERM.	BRASS 0.20	TIN PLATED	1
2	TIP SPRING	PBS 0.25	TIN PLATED	1
3	RING SPRING	PBS 0.50	TIN PLATED	1
4	TIP BREAK	BRASS 0.20	TIN PLATED	1
5	RING BREAK	BRASS 0.40	TIN PLATED	1
6	HOUSING	NYLON PA9T		1
7	BUSHING	BRASS	NI PLATED	1

MODEL NO.	PJ-2001P	PJ-2001P- (COLOR)				
		A	B	C	D	E
HOUSING COLOR	BLACK	PINK	LIGHT BLUE	LIME	YELLOW	ORANGE
PANTONE		701C	284C	577C	123C	157C

Specification:  
Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz  
Insulation Resistance: 100M Ohm Min. At 500V DC.  
Rated Voltage And Current: DC 12V,2A Max  
Dielectric Withstanding Voltage: 500V AC For 1 Minute.  
Durability (Life Test):  
A: For Phosphor Bronze 1500 Cycles Minimun.  
B: For PBS 2000 Cycles Minimun.  
Insertion Force: 0.3~3.0 Kg.  
Extraction Force: 0.3~3.0Kg.

			COMPUTER NO.			UNIT	SCALE	PART NAME	
			D:\DWG\PJ-2001P-5			mm	1:1	ø3.5EARPHONE JACK	
			APPD.	CKD.	DWG.	DATE	TOLERANCE	PART NO.	REV.
							X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05		A0